THE NEW ZEALAND GAZETTE

PART III-MISCELLANEOUS-continued

Tariff Item No.	Goods	Rates of Duty					Part	List	Effective	
		B.P.	Aul.	Can.	MFN.	Gen.	II Ref.	No.	From	То
352 (b)	Rotary, designed to take delivery pipes exceed-	Free			20%S	25%				
	ing $3\frac{1}{4}$ in. in internal diameter except low- lift rotary-impellor type pumps designed for heads of water not exceeding 20 ft and for delivery pipes 24 in. or more in internal	1100	••	••	20700	20 /0	••	••	••	
52 (b)	diameter Vacuum designed to take suction pipes ex-	Free	••	••	20 %S	25%				
52 (Ъ)	ceeding $1\frac{3}{4}$ in. in internal diameter Vacuum, of any capacity, designed to main- tain a vacuum equivalent to 29 in. of mercury or greater under a barometric pressure of 30 in.	Free	••	••	20 %S	25%			•••	
					1 1		1	ļ i		
52 (a)	Refrigerating Valves of any material when peculiar to use with refrigerating apparatus	Erro			150/0	25.9/			1	
12 (a)	with refrigerating apparatus	rice	••	••	15%5	25%		••		••
52 (b)	Rope and twine making— Bobbins for use in rope and twinemaking machines	Free		•••	20 %S	25%				
i2 (b)	Rope and wire grips— Clips, wire rope, Crosby and Bulldog types, all sizes, used instead of splices for joining wire ropes	Free		•••	20%S	25%				
52 (b)	Ferrules, Esco, for use with choker and basket butt hooks	Free		•••	20 %S	25%			••	
2 (b) 2 (b)	Hooks, Bardon's patent Sockets, rope, being drop forgings with a taper hole, for use as terminals on wire rope and as substitutes for an eye splice and thimble	Free Free	••	 	20 %S 20 %S 20 %S	25 % 25 %	•••			••
on in an aige 20 Seitheachta 20 Seitheachta							1 1	I	I	
den de la	Scaffolding, fittings for-				.]			l		
i2 (b)	Fittings specially suited for metal scaffolding, such as quickgrip couplers, putlog couplers, combined joint pins and couplers, swivel couplers, reveal screws, castors, metal struts, props, and shores	Free		••	20%8	25%	•••	••		
2 (b)	Screens— Rotary wire, suitable for use in threshing machines, grain or seed cleaners, and	Free			20%S	25%				
	graders, and for other screening purposes, so constructed that the distance between the individual wires can be adjusted to suit the material being screened									
2 (a) 2 (b)	Separators, centrifugal Steering boosters, hydraulic	Free Free	 	•••	15%S 20%S	25 % 25 %	···	·· ··	 	••
 A A		. (
2 (b)	Stokers— Chain grate, including spare links therefor	Free		••	20%S	25%				
2 (b)	Mechanical, specially suited for firing flue type or Lancashire boilers	Free		••	20%S	25% 25%			••	•••
2 (b)	Overfeed spreader types	Free	•••	•••	20%S	25%	•••		••	••

Dated at Wellington this 25th day of June 1964.

J. F. CUMMINGS, Comptroller of Customs.