

Tariff Notice No. 1968/56—Application for Variation of Approval

NOTICE is hereby given that application has been made for variation of a current approval of the Minister of Customs as follows:

Appn No.	Tariff Item	Goods	Rates of Duty			Part II Ref.	List No.	Effective	
			B.P.	MFN.	Gen.			From	To
2543	84.61	<i>Current Approval—</i> Cocks and valves, EXCLUDING— (1) Penstocks, floodgates (2) Valves, gate, of the following types— (a) Stainless steel 3 in. to 18 in., or cast iron 3 in. to 14 in., specially suited for use with pulp or paper stock (b) Brass, $\frac{1}{2}$ in. and $\frac{3}{4}$ in. (c) Bronze, $\frac{3}{8}$ in. to 4 in. (3) Valves, globe, bronze or gunmetal, suited for use with steam at working pressures of 50 lb or over, of the following types— (a) Stainless steel seats, screwed, $\frac{3}{8}$ in. to 2 in. (b) Yoke top with bronze or stainless steel seats, flanged, $\frac{3}{4}$ in. to 6 in. (c) Angle, yoke top with bronze or stainless steel seats, flanged, 1 in. to 3 in. (d) Valves, safety, bronze, spring-loaded, screwed or flanged, $\frac{3}{8}$ in. to 4 in. (4) Valves, foot, of copper alloy, not exceeding 2 in. (5) Valves, float (sometimes known as "ball") of brass or other copper alloy, not exceeding 6 in. (NOTE—This approval does not cover taps, bib-cocks, or fire hydrants)	Free	20%	25%	10.2	6	1/7/67	31/12/69
	84.61	<i>Requested Approval—</i> Cocks and valves, EXCLUDING— (1) Penstocks, floodgates (2) Valves, gate, of the following types— (a) Stainless steel 3 in. to 18 in., or cast iron 3 in. to 14 in., specially suited for use with pulp or paper stock (b) Brass, $\frac{1}{2}$ in. and $\frac{3}{4}$ in. (c) Bronze, $\frac{3}{8}$ in. to 4 in. (3) Valves, globe, bronze or gunmetal, suited for use with steam at working pressures of 50 lb or over, of the following types— (a) Stainless steel seats, screwed, $\frac{3}{8}$ in. to 2 in. (b) Yoke top with bronze or stainless steel seats, flanged, $\frac{3}{4}$ in. to 6 in. (c) Angle, yoke top with bronze or stainless steel seats, flanged, 1 in. to 3 in. (d) Valves, safety, bronze, spring-loaded, screwed or flanged, $\frac{3}{8}$ in. to 4 in. (e) Fibre or teflon seats, screwed, $\frac{1}{2}$ in. to 2 in. (4) Valves, foot, of copper alloy, not exceeding 2 in. (5) Valves, float (sometimes known as "ball") of brass or other copper alloy, not exceeding 6 in. (6) Plugcocks, bronze, screwed and flanged, straight through or 3-way, $\frac{1}{2}$ in. to 4 in.	Free	20%	25%	10.2

Any person wishing to lodge an objection to the granting of this application should do so in writing on or before 11 July 1968. Submissions should include a reference to the application number, Tariff item, and description of goods concerned, be addressed to the Comptroller of Customs, Private Bag, Wellington, and supported by information as to:

- The range of equivalent goods manufactured locally;
- The proportion of New Zealand and imported materials used in manufacture;
- Present and potential output; and
- Details of factory cost in terms of materials, labour, overhead, etc.

Dated at Wellington this 20th day of June 1968.

V. W. THOMAS, Comptroller of Customs.

Tariff Notice No. 1968/58—Applications for Approval

NOTICE is hereby given that applications have been made for the approval of duty by the Minister of Customs as follows:

Appn No.	Tariff Item	Goods	Rates of Duty			Part II Ref.
			B.P.	MFN.	Gen.	
2521	30.03.09	Wormex, a poultry anthelmintic containing dibutyltin dilaurate, piperazine and phenothiazine	Free	20%	25%	10.2
2522 2523 2524 2525 2526	34.02.00	Ethylan TC, CH, PB, S4, and CP, surface active agents based on ethylene oxide condensates or, in the case of Ethylan S4, on polyglycol 400 stearate	Such rate not exceeding 25% .. 25% as the Minister may in any case direct			10.8
2527	38.19.99	Compounds which have an acid reaction or split off acid by heating, used to cure synthetic resins in textile finishing or cause them to form cross-linkages with cellulose	Such rate not exceeding 25% .. 25% as the Minister may in any case direct			10.8
2528	38.19.99	Stabaxoll being an anti-hydrolysis agent used in the manufacture of adhesives to improve their long term stability in damp conditions	Such rate not exceeding 25% .. 25% as the Minister may in any case direct			10.8