

Tariff Notice No. 1968/109—Application for Variation of Approval

NOTICE is hereby given that application has been made for variation of a current approval of the Minister of Customs as follows:

Appn No.	Tariff Item	Goods	Rates of Duty			Part II Ref.	List No.	Effective	
			B.P.	MFN.	Gen.			From	To
84.61		<p><i>Current Approval:</i> Cocks and valves .. .. .</p> <p>Excluding:</p> <ol style="list-style-type: none"> <li>(1) Penstocks, floodgates.</li> <li>(2) Valves, gate, of the following types—                             <ol style="list-style-type: none"> <li>(a) Stainless steel 3 in. to 18 in., or cast iron 3 in. to 14 in., specially suited for use with pulp or paper stock.</li> <li>(b) Brass, <math>\frac{1}{2}</math> in. and <math>\frac{3}{4}</math> in.</li> <li>(c) <math>\frac{3}{8}</math> in. to 4 in., of any kind of bronze.</li> </ol> </li> <li>(3) Valves, globe, of any kind of bronze, suited for use with steam at working pressures of 50 lb p.s.i. or over, of the following types—                             <ol style="list-style-type: none"> <li>(a) Stainless steel seats, screwed <math>\frac{3}{8}</math> in. to 2 in.</li> <li>(b) Yoke top with bronze or stainless steel seats, flanged, <math>\frac{3}{4}</math> in. to 6 in.</li> <li>(c) Angle, yoke top with bronze or stainless steel seats, flanged, 1 in. to 3 in.</li> </ol> </li> <li>(d) Valves, safety, spring-loaded, screwed or flanged, <math>\frac{3}{8}</math> in. to 4 in.</li> <li>(e) Fibre or teflon seats, screwed, sizes <math>\frac{1}{2}</math> in. to 2 in.</li> </ol> <ol style="list-style-type: none"> <li>(4) Valves, foot, of copper alloy, not exceeding 2 in.</li> <li>(5) Valves, float (sometimes known as "ball"), of brass or other copper alloy, not exceeding 6 in.</li> <li>(6) Sluice or wedge gate valves, cast iron, 4", 6", and 8" double flange or spigot ends, hand-operated waterworks pattern, for test pressures not exceeding 600 ft head of water, not including similar valves with zinc free bronze trim (U.K. Specification B.S. 1218 class 1).</li> <li>(7) Check valves (reflux), cast iron, 3", 4", and 6". Standard type for test pressures not exceeding 600 ft head of water, not including special nonconcussive types or valves with external operating levers.</li> <li>(8) Plugcocks, bronze, screwed and flanged straight through or 3-way, sizes <math>\frac{1}{2}</math> in. to 4 in. (but not sleeve packed plugcocks). (NOTE—This approval does not cover taps, bibcocks, or fire hydrants.)</li> </ol>	Free	20%	25%	10.2	33	1/7/68	31/12/69
4121	84.61	<p><i>Requested Approval:</i> Cocks and valves .. .. .</p> <p>Excluding:</p> <ol style="list-style-type: none"> <li>(1) Penstocks, floodgates.</li> <li>(2) Valves, gate, of the following types—                             <ol style="list-style-type: none"> <li>(a) Stainless steel 3 in., to 18 in., or cast iron 3 in. to 14 in., specially suited for use with pulp or paper stock.</li> <li>(b) Brass, <math>\frac{1}{2}</math> in. and <math>\frac{3}{4}</math> in.</li> <li>(c) <math>\frac{3}{8}</math> in. to 4 in., of any kind of bronze.</li> </ol> </li> <li>(3) Valves, globe, of any kind of bronze, suited for use with steam at working pressures of 50 lb p.s.i. or over, of the following types—                             <ol style="list-style-type: none"> <li>(a) Stainless steel seats, screwed <math>\frac{3}{8}</math> in. to 2 in.</li> <li>(b) Yoke top with bronze or stainless steel seats, flanged, <math>\frac{3}{4}</math> in. to 6 in.</li> <li>(c) Angle, yoke top with bronze or stainless steel seats, flanged, 1 in. to 3 in.</li> </ol> </li> <li>(d) Valves, safety, spring-loaded, screwed or flanged, <math>\frac{3}{8}</math> in. to 4 in.</li> <li>(e) Fibre or teflon seats, screwed, sizes <math>\frac{1}{2}</math> in. to 2 in.</li> <li>(f) Flanged bonnet top <math>\frac{3}{8}</math> in. to 3 in.</li> <li>(g) Flanged regulating check angle or straight type, <math>\frac{3}{8}</math> in. to 6 in.</li> </ol> <ol style="list-style-type: none"> <li>(4) Valves, foot, of copper alloy, not exceeding 2 in.</li> <li>(5) Valves, float (sometimes known as "ball"), of brass or other copper alloy, not exceeding 6 in.</li> <li>(6) Sluice or wedge gate valves, cast iron, 4 in., 6 in., and 8 in. double flange or spigot ends, hand-operated waterworks pattern for test pressures not exceeding 600 ft head of water, not including similar valves with zinc free bronze trim (U.K. Specification B.S. 1218, class 1.)</li> <li>(7) Check valves (reflux), cast iron, 3 in., 4 in., and 6 in. Standard type for test pressures not exceeding 600 ft head of water, not including special nonconcussive types or valves with external operating levers.</li> <li>(8) Plugcocks, bronze, screwed and flanged straight through or 3-way, sizes <math>\frac{1}{2}</math> in. to 4 in. (but not sleeve packed plugcocks). (NOTE—This approval does not cover taps, bibcocks, or fire hydrants.)</li> </ol>	Free	20%	25%	10.2	..	..	..