Tariff Notice No. 1969/98—Applications for Approval

NOTICE is hereby given that applications have been made for the approval of duty by the Minister of Customs as follows:

| Appn<br>No.  | Tariff Item          | Goods  | Rates of Duty  |                      |                      | Part       |
|--------------|----------------------|--|--|----------------------|----------------------|------------|
|              |                      |  | B.P.   | MFN.                 | Gen.                 | II<br>Ref. |
| 6288         | 21.07.19             | Gunthers, G400, V400 and D100 hydrolised proteins for use in the manufacture of foodstuff. These substances are vegetable protein whipping agents  | 25%*   | ••                   | 25%*                 | 10.8       |
| 6525         | 34.02.00             | NID 1000/PW being 90 percent active isopropylamine alkylbenzene sulphonate plus 10 percent water used in making hand cleaners  | 25%*   | ••                   | 25%*                 | 10.8       |
| 6523         | 34.02.00             | Teric 210 being a non-ionic ethylene oxide derivative used as an emulsi-<br>fier, surfactant and oil soluble detergent   | 25%*   | ••                   | 25%*                 | 10.8       |
| 5277         | 34.02.00             | Triton CF-32. This substance is an amine polyglycol condensate liquid non-ionic surfactant and is used for formulating metal cleaners and in-place dairy cleaners  | 25%*   | ••                   | 25%*                 | 10.8       |
| 6278         | 38.19.99             | Bovie liquid conductor, a non-drying, non-irritating, contact agent specifically formulated for use with Bovie and other electro-surgical units  | Free   | 10%                  | $12\frac{1}{2}\%$    | 23.8       |
| 6267         | 38.19.99             | Fungal Enzyme Concentrate A. This product consists of a stand-<br>ardised mixture of proteolytic and amylolytic enzymes from Asper-<br>gillus oryzae and Aspergillus flavus-oryzae and is used by the general<br>baking trade  | 25%*   | ••                   | 25%*                 | 10.8       |
| 5239         | 38.19.99             | Siccatolic Acid, to be used in the manufacture of synthetic driers for the paint industry  | 25%*   | ••                   | 25%*                 | 10.8       |
| 5320         | 39.07.99             | Glass reinforced polyester grids, used in Marley water cooling towers as splash bar supports   | Free   | 20%*                 | 25%*                 | 10.2       |
| 5220         | 40.09.01             | Hoses, high pressure nylon reinforced, "Woma" types NW20 and NW25, internal diameters \(\frac{4}{8}\)" and \(1''\), having working pressures of 850 psi. For use with "Woma" high pressure cleaning units, for   | Free   |                      | 25%                  |            |
| 5202         | 40.14.07             | drainage clearances, cleaning ships hulls etc.  Cylinder piston cups, made from "Hy-Car" synthetic rubber for use in   | 25%*   | ••                   | 25%*                 | 10.8       |
| 5367         | 73.40.99             | the assembly of air cylinders Ladles, foundry, of steel, sizes 2 in. to 12 in., having wall thickness of   | Free   | 20%*                 | 25%*                 | 10.2       |
| 5339         | 84.10.09             | <sup>1</sup> / <sub>8</sub> in. or over "Pumper Buoy" and "Pumperette", portable self-priming pumps, being self-buoyant floating water and sludge pumps, for use in  | Free   | 20%*                 | 25%*                 | 10.2       |
| 5245         | 84.10.09             | emptying ponds, ditches etc. Pumps, liquid, Vickers variable delivery, piston type, models PVB5, PVB6, PVB10, PVB15, PVB20, PVB29, PVB45, PVB90. Used for applications requiring pumps to withstand up to 3000 lb sq in. at drive speeds up to 1,800 rpm, and to produce up to 94 gpm. To be   | Free   | 20%*                 | 25%*                 | 10.2       |
| 5196         | 84.10.09             | capable of infinitely adjustable output by means of integral control Rotary gear pumps, Worthington-Simpson, used in conjunction with wood pulp stock machinery. These pumps have capacities up to 46 gpm with pressures to 150 psi  | Free   | 20%*                 | 25%*                 | 10.2       |
| 5252<br>5291 | 84.17.28             | Fryer, automatic, used in the manufacture of doughnuts   | Free   | 15%*                 | 25%*                 | 10.1       |
| 5244         | 84.22.15             | Fuller Kinyon pumps, used for pumping Portland cement  | Free   | 20 %*<br>20 %*       | 25 %*<br>25 %*       | 10.2       |
| 5223         | 84.23.19             | One Calweld Model 250A Drilling Rig mounted on a Foden 6 × 4 truck chassis. This rig is used for drilling for foundations of buildings, bridges etc.   | Free   | 20%*                 | 25%*                 | 10.2       |
| 5325         | 84.24.13             | Tractor operated rotary tillers specially suited for operation with "Holder" four wheel drive tractors used for agricultural inter-row work and field work   | Free   | Free                 | Free                 | 10.3       |
| 5226         | 84.58.00             | PARK-UR-SELF ticket dispensing machine operated mechanically or electrically by the money receiving shute/s or push button. This   | Free   | 20%*                 | 25%*                 | 10.2       |
| 5346         | 84.59.39             | machine is installed at the entrance to car parks "Jomac" damper roller cleaner-dryer, Model 86. Used for cleaning   | Free   | 20%*                 | 25%*                 | 10.2       |
| 5247         | 84.59.39             | and drying printers' dampener rollers Simplex Util-A-Tool set, used in the motor vehicle industry  | Free   | 20%*                 | 25%*                 | 10.2       |
| 5232<br>5233 | 84.59.39<br>84.63.09 | Vulcanisers, electric, for repairing rubber cases but not inner tubes Harmonic gear reducer. A high ratio, high torque unit with ratios from 80/1 to 260/1, used for power transmission requirements where very large reductions or increases, high torque capacities, extremely low back-lash or accurate angular positioning must be combined with | Free<br>Free   | 20%*<br>20%*<br>20%* | 25%*<br>25%*<br>25%* | 10.2       |
| 5231         | 85.22.27             | minimum size and weight Belling and Lee R.F.I. filter suppressors used for filtering impurities  | Free   | 20%*                 | 25%*                 | 10.2       |
|              |                      | from mains power current input, into laboratory screened rooms   | *or such lower rate of duty as the Minister may in any case direct |                      |                      |            |

Any person wishing to lodge an objection to the granting of these applications should do so in writing on or before 25 September 1969. Submissions should include a reference to the application number, Tariff item, and description of goods concerned, be addressed to the Comptroller of Customs, Private Bag, Wellington, and supported by information as to:

Dated at Wellington this 4th day of September 1969.

<sup>(</sup>a) The range of equivalent goods manufactured locally;
(b) The proportion of New Zealand and imported materials used in manufacture;
(c) Present and potential output; and
(d) Details of factory cost in terms of materials, labour, overhead, etc.