

Tariff Notice No. 1969/129—Application for Variation of Approval

NOTICE is hereby given that an application has been made for variation of a current approval of the Minister of Customs as follows:

Appn No.	Tariff Item	Goods	Rates of Duty			Part II Ref.	List No.	Effective	
			B.P.	MFN.	Gen.			From	To
	84.61	<i>Current Approval:</i> Cocks and valves: .. .. . Excluding—	Free	20%	25%	10.2			
		(1) Penstocks, floodgates .. .. .					45	2/69	12/69
		(2) Valves, gate, of the following types: ..					45	2/69	12/69
		(a) Stainless steel 3 in. to 18 in., or cast iron 3 in. to 14 in., specially suited for use with pulp or paper stock							
		(b) Brass, ½ in. and ¾ in.							
		(c) ¾ in. to 4 in. of any kind of bronze							
		(3) Valves, globe, of any kind of bronze, suited for use with steam at working pressures of 50 lb psi or over, of the following types:					45	2/69	12/69
		(a) Stainless steel seats, screwed ¾ in. to 2 in.							
		(b) Yoke top with bronze or stainless steel seats, flanged ¾ in. to 6 in.							
		(c) Angle yoke top with bronze or stainless steel seats, flanged, 1 in. to 3 in.							
		(d) Valves, safety, spring-loaded, screwed or flanged, ¾ in. to 4 in.							
		(e) Fibre or teflon seats, screwed, sizes ½ in. to 2 in.							
		(4) Valves, foot, of copper alloy, not exceeding 2 in.					45	2/69	12/69
		(5) Valves, float (sometimes known as "ball"), of brass or other copper alloy, not exceeding 6 in.	45	2/69	12/69				
		(6) Sluice or wedge gate valves, cast iron, 4 in., 6 in., and 8 in. double flange or spigot ends, hand-operated waterworks pattern, for test pressures not exceeding 600 ft head of water, not including similar valves with zinc free bronze trim (U.K. Specification BS 1218 class 1)	45	2/69	12/69				
		(7) Check valves (reflux), cast iron, 3 in., 4 in., and 6 in. Standard type for test pressures not exceeding 600 ft head of water, not including special non-concussive types of valves with external operating levers	45	2/69	12/69				
		(8) Plugcocks, bronze, screwed and flanged straight through or 3-way, sizes ½ in. to 4 in. (but not sleeve packed plugcocks)	45	2/69	12/69				
		(9) Valves of a type used on bulk fuel tankers, viz:	45	2/69	12/69				
		(a) Pressure vacuum valves, aluminium, screwed							
		(b) Bottom outlet valves, aluminium or bronze, sizes 3 in. and 4 in., flanged							
		(NOTE—This approval does not cover taps, bibcocks, or fire hydrants)							
6930	84.61	<i>Requested Approval:</i> Cocks and valves .. .. . Excluding—	Free	20%	25%	10.2			
		(1) Penstocks, floodgates							
		(2) Valves, gate, of the following types:							
		(a) Stainless steel 3 in. to 18 in., or cast iron 3 in. to 14 in., specially suited for use with pulp or paper stock							
		(b) Brass, ½ in. and ¾ in.							
		(c) ¾ in. to 4 in. of any kind of bronze							
		(3) Valves, globe, of any kind of bronze, suited for use with steam at working pressures of 50 lb psi, or over, of the following types:							
		(a) Stainless steel seats, screwed ¾ in. to 2 in.							
		(b) Yoke top with bronze or stainless steel seats, flanged ¾ in. to 6 in.							
		(c) Angle, yoke top with bronze or stainless steel seats, flanged, 1 in. to 3 in.							
		(d) Valves, safety, spring-loaded, screwed or flanged, ¾ in. to 4 in.							
		(e) Fibre or teflon seats, screwed, sizes ½ in. to 2 in.							
		(4) Valves, foot, of copper alloy, not exceeding 2 in.							
		(5) Valves, float (sometimes known as "ball")—							
		(a) Brass or other copper alloy, not exceeding 6 in.							
		(b) Screwed, stainless steel and mild steel bodies, sizes ¾ in. to 2 in. B.S.P.							
		(c) Flanged, cast stainless steel or cast steel, sizes 3 in. and 4 in.							