

Tariff Notice No. 1970/16—continued

Appn No.	Tariff Item	Goods	Rates of Duty			Part II Ref.	List No.	Effective	
			B.P.	MFN.	Gen.			From	To
8134 8135	84.61	<p><i>Requested Approval:</i> Cocks and valves:</p> <p>Excluding:</p> <ol style="list-style-type: none"> (1) Penstocks, floodgates (2) Valves, gate, of the following types— <ol style="list-style-type: none"> (a) Stainless steel 3 in. to 18 in., or cast iron 3 in. to 14 in., specially suited for use with pulp or paper stock (b) Brass, $\frac{1}{2}$ in. and $\frac{3}{4}$ in. (c) $\frac{3}{8}$ in. to 4 in. of any kind of bronze (3) Valves, globe, of any kind of bronze, suited for use with steam at working pressures of 50 p.s.i. or over, of the following types— <ol style="list-style-type: none"> (a) Stainless steel seats, screwed $\frac{3}{8}$ in. to 2 in. (b) Yoke top with bronze or stainless steel seats, flanged $\frac{3}{4}$ in. to 6 in. (c) Angle, yoke top with bronze or stainless steel seats, flanged, 1 in. to 3 in. (d) Valves, safety, spring-loaded, screwed or flanged, $\frac{3}{8}$ in. to 4 in. (e) Fibre or teflon seats, screwed, sizes $\frac{1}{2}$ in. to 2 in. (f) Flanged bonnet top $\frac{3}{4}$ in. to 3 in., with bronze or stainless steel seats and a working pressure of up to 125 psi (g) Flanged regulating check angle or straight type $\frac{3}{4}$ in. to 6 in. with bronze or stainless steel seats and a working pressure up to 250 psi (4) Valves, foot, of copper alloy, not exceeding 2 in. (5) Valves, float, of brass or other copper alloy, not exceeding 6 in. (6) Valves, ball— <ol style="list-style-type: none"> (a) Screwed, stainless steel and mild steel bodies, sizes $\frac{3}{8}$ in. to 2 in. B.S.P. (b) Flanged, cast stainless steel or cast steel, sizes 3 in. and 4 in. (7) Sluice or wedge gate valves, cast iron, 4 in., 6 in., and 8 in. double flange or spigot ends, hand-operated waterworks pattern, for test pressures not exceeding 600 ft head of water, not including similar valves with zinc free bronze trim (U.K. Specification BS 1218 class 1) (8) Check valves (reflux), cast iron, 3 in., 4 in., and 6 in. Standard type for test pressures not exceeding 600 ft head of water, not including special non-concussive types of valves with external operating levers (9) Plugcocks, bronze, screwed and flanged straight through or three-way, sizes $\frac{1}{2}$ in. to 4 in. (but not sleeve packed plugcocks) (10) Valves of a type used on bulk fuel tankers, viz: <ol style="list-style-type: none"> (a) Pressure vacuum valves, aluminium, screwed (b) Bottom outlet valves, aluminium or bronze, sizes 3 in. and 4 in. flanged <p>(NOTE)—This approval does not cover taps, bibcocks, or fire hydrants</p> <ol style="list-style-type: none"> (11) Check valves of any kind of bronze, suited for use with steam or water, of the following types and working pressures— <ol style="list-style-type: none"> (a) Flanged horizontal type $\frac{3}{4}$ in. to 6 in. with stainless steel or bronze seat and a working pressure of 50 to 250 psi (b) Flanged and screwed swing type $2\frac{1}{2}$ in. to 4 in. with bronze seat and a working pressure of 50 to 100 psi (c) Screwed vertical type $2\frac{1}{2}$ in. to 3 in. with bronze seat and a working pressure of 50 to 200 psi (d) Horizontal check valves, $\frac{1}{2}$ in. to 2 in. fibre or teflon seats and a working pressure up to 150 psi (12) Treacle cocks, bronze 1 in. to 3 in. (13) Blow down plug cock, flanged, asbestos packed, double gland bronze 1 in. to 2 in. used for blowing down boilers or pressure vessels and tested up to 500 psi (14) Needle valves, of bronze, in-line types, sizes $\frac{1}{4}$ in., $\frac{3}{8}$ in. and $\frac{1}{2}$ in. B.S.P. 	Free	20%	25%	10.2