

TARIFF DECISION LIST No. 164

Decisions of the Minister of Customs Under the Customs Tariff (Subject to Amendment or Cancellation by Notification in the Gazette)

APPROVALS

Tariff Item No.	Goods	Rates of Duty			Part II Ref.	List No.	Effective	
		B.P.	MFN	Gen.			From	To*
84.61	<p>Cocks and valves:</p> <p>Excluding:</p> <p>(1) Penstocks, floodgates</p> <p>(2) Valves, gate, of the following types:</p> <p>(a) Stainless steel 3 in. to 8 in., or cast iron 3 in. to 14 in., specially suited for use with pulp or paper stock</p> <p>(b) Brass, $\frac{1}{2}$ in. and $\frac{3}{4}$ in.</p> <p>(c) $\frac{3}{8}$ in. to 4 in. of any kind of bronze</p> <p>(3) Valves, globe, of any kind of bronze, suited for use with steam at working pressures of 50 p.s.i. or over, of the following types:</p> <p>(a) Stainless steel seats, screwed $\frac{3}{8}$ in. to 2 in.</p> <p>(b) Yoke top with bronze or stainless steel seats, flanged $\frac{3}{4}$ in. to 6 in.</p> <p>(c) Angle, yoke top with bronze or stainless steel seats, flanged, 1 in. to 3 in.</p> <p>(d) Valves, safety, spring-loaded, screwed or flanged, $\frac{3}{8}$ in. to 4 in.</p> <p>(e) Fibre or teflon seats, screwed, sizes $\frac{1}{2}$ in. to 2 in.</p> <p>(f) Flanged bonnet top $\frac{3}{4}$ in. to 3 in., with bronze or stainless steel seats and a working pressure of up to 125 p.s.i.</p> <p>(g) Flanged regulating check angle or straight type $\frac{3}{4}$ in. to 6 in. with bronze or stainless steel seats and a working pressure up to 250 p.s.i.</p> <p>(4) Valves, foot, of copper alloy, not exceeding 2 in.</p> <p>(5) Valves, float, of brass or other copper alloy, not exceeding 6 in.</p> <p>(6) Valves, ball:</p> <p>(a) Screwed, stainless steel and mild steel bodies, sizes $\frac{3}{8}$ in. to 2 in. B.S.P.</p> <p>(b) Flanged, cast stainless steel or cast steel, sizes 3 in. and 4 in.</p> <p>(7) Sluice or wedge gate (or stop) valves of cast iron, and of alloyed iron, for waterworks purposes and like application, in sizes, 4 in., 6 in., 8 in., 10 in., 12 in., double flange spigot and socket ends, hand operated waterworks pattern, for test pressures not exceeding 800 foot head of water, with or without copper based trims and spindles in accordance with UKBS 1218 and NZSS 784</p> <p>(8) Check valves (reflux) cast iron 3 in., 4 in., 6 in., and 8 in., free acting, 4 in., 6 in., 8 in., external lever operated, standard types for test pressures not exceeding 600 foot head of fluid, not including non-concussive types</p> <p>(9) Plugcocks, bronze, screwed and flanged straight through or 3-way, sizes $\frac{1}{2}$ in. to 4 in. (But not sleeves packed plugcocks).</p> <p>(10) Valves of a type used on bulk fuel tankers, viz:</p> <p>(a) Pressure vacuum valves, aluminium, screwed</p> <p>(b) Bottom outlet valves, aluminium or bronze sizes 3 in. and 4 in. flanged</p> <p>(11) Check valves of any kind of bronze, suited for use with steam or water, of the following types and working pressures:</p> <p>(a) Flanged horizontal type $\frac{3}{4}$ in. to 6 in. with stainless steel or bronze seat and a working pressure of 50 to 250 p.s.i.</p>	Free	20%	25%	10.2	164	1/1/71	30/6/71