TARIFF DECISION LIST No. 164-continued

APPROVALS—continued

Tariff Item No.	Goods		Rates of Duty			List	Effective	
		B.P.	MFN	Gen.	Part II Ref.	No.	From	To*
84.61	Cocks and valves—continued: Excluding—continued:	Free	20%	25%	10.2	164	1/1/71	30/6/71
	(b) Flanged and screwed swing type $2\frac{1}{2}$ in. to 4 in. with bronze seat and a working pressure							
	of 50 to 100 p.s.i. (c) Screwed vertical type $2\frac{1}{2}$ in. to 3 in. with						ı	
	bronze seat and a working pressure of 50 to 200 p.s.i.	ı						
	(d) Horizontal check valves $\frac{1}{2}$ in. to 2 in. fibre or teflon seats and a working pressure up	· · · · · · · · · · · · · · · · · · ·						
	to 150 p.s.i. (12) Treacle cocks, bronze 1 in. to 3 in.							
	(13) Blow down plugcock, flanged, asbestos packed, double gland bronze 1 in. to 2 in. used for blowing down boilers or pressure vessels and tested up	,					·	
	to 500 p.s.i. (14) Needle valves, of bronze, in-line types, sizes ½ in., ¾ in. and ½ in. B.S.P.							
	(15) Pressure reducing valves of bronze, pilot operated, flanged and screwed, stainless steel seat and valve,							
	sizes ½ in. to 2 in. up to 250 p.s.i. (16) Valves of a type used by service station petrol pumps: (a) Petrol pump dispensing nozzles							
	(b) Petrol pump dispensing nozzles, automatic shut-off types, which operate at up to 30 g.p.m. at pressures from 5-90 p.s.i.							
	(17) Valves, drum compensating types, being air reducing valves of the types used to pressurise oil storage							
	containers having a capacity of 12½, 44, and 60 gallons or more.							
	(18) Solenoid valves(19) Aerosol valves, with or without actuators, suitable for 1 in. neck-opening aerosol containers.					-	:	
	(20) Check valves: (a) Wafer type, ductile iron body, stainless steel						4. (s. 5. No.	
	flap and seat, sizes 2 in. to 12 in. Working pressure: water, oil, gas, 275 p.s.i. (600 ft. head) saturated steam at 150 p.s.i. (As						7.	
	options these valves may have soft seat insert and/or fitted with back flush lever,							
	adjustable counter balance and cam operated micro switch). (b) Backflow preventor double check valves, 2 in.					-		
	to 12 in. suitable working pressure 275 p.s.i. (NOTE—This approval does not cover taps, bibcocks, or fire hydrants.)							

^{*}Approvals lapse on the dates indicated, the goods thereafter being dutiable according to their substantive Tariff classification. If continuation of an approval is desired for a further period, formal application should be made to the Collector at least 6 weeks prior to the date of expiry.

MISCELLANEOU	S
--------------	---

Decisions C	ancelled:								
84.61	Cocks and valves: Excluding: (1) Penstocks (17) gallons or more	·	••	••	••	••	136	••	••