Tariff Notice No. 1971/15-Applications for Approval

Appn No.	Tariff Item	Goods	Rates of Duty			Part
			B.P.	MFN.	Gen.	
2394 2395	30.03.09 30.03.09	Aerosporin Polymyxin B Sulphate—powder Super-Suntax, 100cc multi-dose vials—Vitamin D ₃ (Dihydrotachy- sterol), to prevent or cure rickets in growing birds and animals, and to prevent osteomalacia in the adult	Free Free	20 % 20 %*	25% 25%*	23 10
2394 2394 2396	30.03.09 30.03.09 30.03.09	Tubarine injection	Free Free Free	 20%*	20 % 20 % 25 %*	23 23 10
2184	34.02.00	whipworm disease Standamid CM, SD, LD, LP (superamide) being lauric myristic acid diethanol amides used as surface active agents and emulsifiers for	25%*	•••	25%*	10
2185	34.02.00	the manufacture of shampoos, bubble baths, etc. Standamul 02 (ethoxylated (2) oleyl alcohol) polyglycol ether of primary highly unsaturated alcohol (oleyl) used to make toilet	25%*	•••	25%*	10
2186	34.02.00	preparations Standamul 1414-E, being a myristyl ethoxy myristate used to make	25 %*	••	25%*	10
2183	34.02.00	toilet preparations Standapol ES-40 conc (Namyristyl tri-ether sulphate) used for making shampoos, bubble baths, etc.	25%*	••	25%*	10
2180	34.02.00	Teric 303, being a nonionic ethylene oxide derivative and used as an iodine stabiliser for preparation of medium foam and low foam	25%*		25%*	10
2202	38.11.99	iodophors 4-The-Birds, being a bird repellant composed mainly of polybutene	25%*	••	25%*	10
2182	38.19.99	combined with a jelling agent Niax isocyanate A.F.P.I. being a polymeric isocyanate suited for use	25%*	••	25 %*	10
2224	38.19.19	in rigid urethane foams Oticon ear impression material AZ 6800 a silicon rubber polymer which contains silicon dioxide and silicon oil with polymer re- action to expedite the process of hardening used for the purpose	Free	10%	12 1 2%	23
2212	38.19.99	of making impressions of the human ear Talase, a special enzyme formulation, which contains amylolytic and proteolytic enzymes, used to digest starches, gums, gelatins,	25%*	••	25%*	10
2178	39.07.10	and various warp-sizing formulae used in all types of fabrics Snyder Hemovac wound tubing of polythene perforated and pre- sterilised is used to connect a Hemovac evacuator in order to drain body fluids from surgical wounds	Free	10%	12 1 %	23
2346	59.04.09	Nylon and terylene "tow" unbulked yarn, weighing over 9,000 denier which is used in the manufacture of rope. This is high tenacity yarn	25%*	••	25%*	10
2171	73.15.86	"Rigidtex" embossed stainless steel sheet in strip form less than 6" in width used as decorative trim on commercial refrigeration cabinets	Free	20%*	25%*	10
2363	84.10.09	Pumps, sliding shoe, self-priming, rotary, used for pumping clear water, factory effluent, ships' bilge etc.	Free	20%*	25%*	10
2195	84.10.09	Titan pumps, positive displacement continuous flow, open throat for pumping liquid fat in a "Titan" continuous rendering plant	Free	20%*	25%*	10
2237	84.14.01	Oil fired rotary furnace, end tilting model used for the melting of cast iron in the manufacture of cast iron porcelain enamel baths and basins	Free	20 %*	25 %*	10
2196 2194	84.15.39 84.22.19	Ice making machine One Dover Escalift Model S/R electric chair seat used on a home stairway to transport sick person. Capacity 250 lbs, and with a	Free Free	20 %* 20 %*	25 %* 25 %*	10
2220	84.56.01	speed of 32 ft per minute on a 45 degree angle Warman Series "R" rubber lined cyclone classifier separators used to separate fine and coarse solid particles by centrifugal force	Free	20%*	25%*	10
2166	84.59.49	generated by the high tangential velocities entering the cyclone Polynodulite hexagonal transferable plating barrels used for the electroplating of small metal components	Free	20%*	25%*	10
2208	84.63.09	PIV gears, used for varying the speed of a drive while still retaining positive engagement	Free	20%*	25%*	10
2215	85.11.01	McCulloch 170 portable arc welding machines, weighing 55 lbs, gasoline powered, 170 amps	Free	20%*	25%*	10
2241	85.14.02	Components used in the manufacture of loudspeaker enclosures. Consisting of:	Free	20%	25%	.
1.1		(a) High frequency loudspeakers, diameter 50 mm, Impedance 4-6 ohms, frequency range 2,000-20,000 H2, Flux density 12,000 Oersteds, plastic coned	···· ·· ··			
		 (b) Low frequency loudspeakers, diameter 300 mm, Impedance 4 ohms, frequency range 45-1750 H2 (13 H2 free air), Flux density 12,000 Oersteds (c) Mid frequency loudspeakers, diameter 150 mm, Impedance 				
		(d) High frequency loudspeakers, diameter 70 mm, Impedance 6				

*or such lower rate of duty as the Minister may in any case direct

NOTICE is hereby given that applications have been made to the Minister of Customs for concessionary entry of the following goods at the rates of Customs duty shown: