

TARIFF DECISION LIST NO. 191

Decisions of the Minister of Customs Under the Customs Tariff (Subject to Amendment or Cancellation by Notification in the Gazette)

APPROVALS

Tariff Item No.	Goods	Rates of Duty			Part II Ref.	List No.	Effective	
		B.P.	MFN.	Gen.			From	To*
Chapter 39	Plates, sheets, strip, film, and foil, exceeding 15 cm in width, printed, embossed, or otherwise surface worked, viz: (1) Pliable, whether or not supported, reinforced or coated, but not coated with adhesive, and not printed, embossed, lithographed or ruled. (2) Pliable, (other than quilted), excluding adhesive backed products, printed and/or embossed with an overall pattern and whether or not reinforced, with textile or threads, suited for the manufacture of soft furnishings, apparel, or wallets and similar articles and for covering walls and furniture. (Self-adhesive and pressure sensitised products designed or specifically suited for use in covering walls and furniture are excluded from the above concession).	Free	..	Free	..	191	1/9/70	31/12/71
84.61	Cocks and valves: Excluding: (1) Penstocks, floodgates. (2) Valves, gate, of the following types— (a) Stainless steel 3 in. to 18 in., or cast iron 3 in. to 14 in., specially suited for use with pulp or paper stock. (b) Brass, $\frac{1}{2}$ in. and $\frac{3}{4}$ in. (c) $\frac{3}{8}$ in. to 4 in. of any kind of bronze. (3) Valves, globe, of any kind of bronze, suited for use with steam at working pressures of 50 p.s.i. or over, of the following types— (a) Stainless steel seats, screwed $\frac{3}{8}$ in., to 2 in. (b) Yoke top with bronze or stainless steel seats, flanged $\frac{3}{4}$ in. to 6 in. (c) Angle, yoke top with bronze or stainless steel seats, flanged, 1 in. to 3 in. (d) Valves, safety, spring-loaded, screwed or flanged, $\frac{3}{8}$ in. to 4 in. (e) Fibre or teflon seats, screwed, sizes $\frac{1}{2}$ in. to 2 in. (f) Flanged bonnet top $\frac{3}{4}$ in. to 3 in., with bronze or stainless steel seats and a working pressure of up to 125 p.s.i. (g) Flanged regulating check angle or straight type $\frac{3}{4}$ in. to 6 in. with bronze or stainless steel seats and a working pressure up to 250 p.s.i. (4) Valves, foot, of copper alloy, not exceeding 2 in. (5) Valves, float, of brass or other copper alloy, not exceeding 6 in. (6) Valves, ball— (a) Screwed, stainless steel and mild steel bodies, sizes $\frac{3}{8}$ in. to 2 in. B.S.P. (b) Flanged, cast stainless steel or cast steel, sizes 3 in. and 4 in. (7) Sluice or wedge gate (or stop) valves of cast iron, and of alloyed iron, for waterworks purposes and like application, in sizes, 4 in., 6 in., 8 in., 10 in., 12 in., double flange spigot and socket ends, hand operated waterworks pattern, for test pressures not exceeding 800 foot head of water, with or without copper based trims and spindles in accordance with UKBS 1218 and NZSS 784. (8) Check valves (reflux) cast iron 3 in., 4 in., 6 in., and 8 in., free acting, 4 in., 6 in., 8 in., external lever operated, standard types for test pressures not exceeding 600 foot head of fluid, not including non-concussive types.	Free	20%	25%	10.2	191	1/1/71	30/6/74