

TARIFF DECISION LIST No. 191—continued

APPROVALS—continued

Tariff Item No.	Goods	Rates of Duty			Part II Ref.	List No.	Effective	
		B.P.	MFN.	Gen.			From	To*
84.61	<p>Cocks and valves—<i>continued</i></p> <p>(9) Plugcocks, bronze, screwed and flanged straight through or 3-way, sizes $\frac{1}{2}$ in. to 4 in. (But not sleeves packed plugcocks).</p> <p>(10) Valves of a type used on bulk fuel tankers, viz:</p> <p>(a) Pressure vacuum valves, aluminium, screwed.</p> <p>(b) Bottom outlet valves, aluminium or bronze sizes 3 in. and 4 in. flanged.</p> <p>(11) Check valves of any kind of bronze, suited for use with steam or water, of the following types and working pressures—</p> <p>(a) Flanged horizontal type $\frac{3}{4}$ in. to 6 in. with stainless steel or bronze seat and a working pressure of 50 to 250 p.s.i.</p> <p>(b) Flanged and screwed swing type $2\frac{1}{2}$ in. to 4 in. with bronze seat and a working pressure of 50 to 100 p.s.i.</p> <p>(c) Screwed vertical type $2\frac{1}{2}$ in. to 3 in. with bronze seat and a working pressure of 50 to 200 p.s.i.</p> <p>(d) Horizontal check valves $\frac{1}{2}$ in. to 2 in. fibre or teflon seats and a working pressure up to 150 p.s.i.</p> <p>(12) Treacle cocks, bronze 1 in. to 3 in.</p> <p>(13) Blow down plugcock, flanged, asbestos packed, double gland bronze 1 in. to 2 in. used for blowing down boilers or pressure vessels and tested up to 500 p.s.i.</p> <p>(14) Needle valves, of bronze, in-line types, sizes $\frac{1}{4}$ in., $\frac{3}{8}$ in. and $\frac{1}{2}$ in. B.S.P.</p> <p>(15) Pressure reducing valves of bronze, pilot operated, flanged and screwed, stainless steel seat and valve, sizes $\frac{1}{2}$ in. to 2 in. up to 250 p.s.i.</p> <p>(16) Valves of a type used by service station petrol pumps—</p> <p>(a) Petrol pump dispensing nozzles.</p> <p>(b) Petrol pump dispensing nozzles, automatic shut-off types, which operate at up to 30 g.p.m. at pressures from 5-90 p.s.i.</p> <p>(17) Valves, drum compensating types, being air reducing valves of the types used to pressurise oil storage containers having a capacity of $12\frac{1}{2}$, 44 and 60 gallons or more.</p> <p>(18) Solenoid valves.</p> <p>(19) Aerosol valves, with or without actuators, suitable for one inch neck-opening aerosol containers.</p> <p>(20) Check valves:</p> <p>(a) Wafer type, ductile iron body, stainless steel flap and seat, sized 2" to 12". Working pressure: water, oil, gas, 275 p.s.i. (600 ft. head) saturated steam at 150 p.s.i. (As options these valves may have soft seat insert and/or fitted with back flush lever, adjustable counter balance and cam operated micro switch).</p> <p>(b) Backflow preventor double checkvalves, 2" to 12" suitable working pressure 275 p.s.i.</p> <p>(NOTE—This approval does not cover taps, bibcocks, or fire hydrants).</p>	Free	20%	25%	10.2	191	1/1/71	30/6/74

*Approvals lapse on the dates indicated, the goods thereafter being dutiable according to their substantive Tariff classification. If continuation of an approval is desired for a further period, formal application should be made to the Collector at least 6 weeks prior to the date of expiry.

Dated at Wellington this 1st day of July 1971.

V. W. THOMAS, Comptroller of Customs.