

Tariff Notice No. 1972/146—Applications for Approval

NOTICE is hereby given that applications have been made to the Minister of Customs for concessionary entry of the following goods at the rates of Customs duty shown:

Appn. No.	Tariff Item	Goods	Rates of Duty			Part II Ref.
			B.P.	MFN.	Gen.	
3993	34.02.000	Bevaloid Dispersant 35—used as a general purpose anionic dispersing agent	25%*	..	25%*	10.8
3739	37.08.009	One stop X-ray developing solution	25%*	..	25%*	10.8
3990	39.02.061	Special polyethylene airpipe—minimum thickness of 0.5 mm, used for tunnel ventilation	Free	..	25%	..
3989	39.07.399	Flexible P.V.C. hose clamps	Free	20%*	25%*	10.2
3958	48.21.039	Filter cartridges, used in oil filters for filtering cooking oils ..	Free	20%*	25%*	10.2
3942	73.18.371	Electrical resistance welded steel pipes, 4" but less than 9" nominal diameter, for the transmission of natural gas underground, in rural, suburban and urban areas, up to pressures of 400 p.s.i.	Free	20%*	25%*	10.2
3939	84.11.029	Suction pumps—compressor pumps and combination suction and compression pumps, for surgical and hospital use	Free	20%*	25%*	10.2
3923	84.15.219	Electrically heated refrigerator doors, of extruded aluminium with glass panels	25%*	..	25%*	10.8
3978	84.19.059	Advance VCM automatic carton erecting, filling and closing machine for cartons of powder, flakes etc., up to 2 Kg in weight, and up to 35 per minute	Free	20%*	25%*	10.2
3946	84.21.009	Knapsack sprayers for forest release work, of polypropylene, 4 gallon capacity	Free	Free	Free	10.3
3972	84.59.129	Floating suction assemblies, used for the refuelling of aircraft ..	Free	20%*	25%*	10.2
3926	84.63.049	Crofts vertical type RARV size 50 worm reduction units, ratio 40:1, 5" centres, fan cooled with lighthouse type housings standard shaft extensions and vertical output shafts (assembly No. 1), for use in mixing vessels for agitator duty	Free	20%*	25%*	10.2
3883	90.24.011	"Autocon" C and R switch/floatrol/selectrol—instrument for liquid level control applications over tanks, sumps, sewage, etc., for single up to 4 or up to 9 circuit controls. A single float and counterweight operates an assembly of mercury switches that gives completely automatic control of independently adjustable circuits	Free	20%	25%	..
3882	90.24.011	"Autocon" Duotrol—automatic air and pump control for constant water pressure in hydropneumatic systems. Air Add, Air Vent or combination of both types, Basic one and two pump models, to regulate liquid level in a water supply tank and tank air pressure for constant head supply	Free	20%	25%	..
3884	90.24.011	"Autocon" Tankrol—Instrument for pressure operated control of pumps, valves, alarms, etc. "Start" and "Stop" pressure sensors can be adjusted to maintain accurate pressure levels, compensate for friction loss and other variables existing between pump and storage tank. Adjustable time delay on start and stop prevents false operation due to surge, hammer, etc.	Free	20%	25%	..
3881	90.24.011	C17-140 Ranio thermostats used as components for manufacture of packaged air conditioners, some lines of remote air conditioners and unit heaters	Free	20%	25%	..
3986	90.24.011	Decompression meters being safety ancillary equipment for divers and skin divers	Free	20%	25%	..
3965	90.24.011	Foxboro Pneumatic model 40 recording, alternatively indicating, recorder controller for temperature, pressure, flow, differential pressure, dew point, liquid level and pneumatic receiving control applications with: On-Off, full proportional ($\frac{1}{4}$ to 200%), proportional plus derivative, proportional plus reset plus derivative, differential gap, automatic shut-down, pneumatic set control, ratio control, duplex control, auto-selector control, batch control, and dual control The instrument's accuracy is plus or minus .5 of 1% of full scale, repeatability 0.25 of 1% of full scale and Controller Dead Band 0.02 of 1% of full scale, also with automatic manual sub-panels with internal regulators, and or Electric alarm contacts and or pneumatic limit operators	Free	20%	25%	..
3966	90.24.011	Foxboro Pneumatic model 43A all purpose indicating controller for temperature, pressure, flow, differential pressure, dew point, liquid level and pneumatic receiving control applications from field mounted pneumatic transmitters with: Proportional, adjustable from 4% to over 400% of scale, Proportional plus reset. Reset adjustable from 0.1 to 25 mins. per repeat plus fast reset of 0.1 to 2.5 mins. per repeat Differential gap, adjustable from 1 to 100% of scale with an Automatic Manual transfer switch, and electric alarm contacts	Free	20%	25%	..
3742	90.24.011	Penn Lube Oil Protection Controls for refrigeration and associated equipment. Viz. Series P28—differential pressure controls with built-in time delay switch. Used for protection against failure of oil pressure in commercial type refrigeration compressors and associated equipment	Free	20%	25%	..