

Tariff Notice No. 1973/4—Applications for Approval

NOTICE is hereby given that applications have been made to the Minister of Customs for concessionary entry of the following goods at the rates of Customs duty shown:

Appn. No.	Tariff Item	Goods	Rates of Duty			Part II Ref.
			B.P.	MFN.	Gen.	
4880	34.02.000	Armostat 300—an antistatic agent used in the manufacture of plastics	25%*	..	25%*	10.8
5038	34.02.000	“Valclene” fluorocarbon fluid—dry cleaning fluid ..	25%*	..	25%*	10.8
4908	38.11.021	Trusty Aerosol insecticide spray used for the eradication and prevention of infestation of fleas, lice, ticks and sarcoptic mites in dogs and cats	22½%	..	22½%	..
5025	38.18.000	Thinners: DL 422, DL 2238 DL 2227—used as diluents to give special finishes to leather and vinyl coatings	25%*	..	25%*	10.8
5026	38.19.299	Nipanox P—BHA, used as an antioxidant in the manufacture of animal feedstuffs	25%*	..	25%*	10.8
5095	38.19.299	Pearl pigments for incorporation in cosmetic lines to give interference and luster to products	25%*	..	25%*	10.8
4906	38.19.299	Flovon FL, a flameproofing agent for use by drycleaners ..	25%*	..	25%*	10.8
4882	38.19.299	Zeolith T paste, Zeolith L paste used for water removal in polyurethane systems	25%*	..	25%*	10.8
5103	40.05.009	Fusible tissue strip, Silverleaf grade 23–5149 (Gutta Percha) ..	25%*	..	25%*	10.8
5113	44.14.009	Fijian Kauri veneer 1/16" (1.6mm) thickness in sheets 8 ft × 4in. ..	25%*	..	25%*	10.8
4971	59.04.009	68" length tapered twine used for hand lacing moccasins ..	25%*	..	25%*	10.8
5102	59.17.019	Hyprocel-Pellon self adhesive foam fabric circular polishing cloths being commonly used in machinery	Free	20%*	25%*	10.2
5111	62.05.099	Woven felt alphabet numbers coated with a nylon adhesive backing which will adhere to textile apparel when high frequency heat is applied	25%*	..	25%*	10.8
4944	73.35.009	Orthodontic preformed springs used in correcting deformities of the teeth	Free	10%	12½%	23.8
4898	84.10.009	Holder agricultural high pressure spray pumps, models Z 70 and Z 110, used for the manufacture or repair of agricultural power-driven sprayers	Free	Free	Free	10.3
4912	84.10.009	Hypno model 5500 series, and model 5400 series, being 4-piston pumps—for use in the manufacture of washing machines	Free	Free	Free	10.3
5079	84.15.219	Taylor freezer shakemaster model 452 to make thick shakes in four different flavours yet disperse from one single tube	Free	Free	Free	10.3
4896	84.18.129	Stainless steel vent gas scrubber to entrain fumes, gases and vapours during the manufacture of resins	Free	20%*	25%*	10.2
5005	84.22.029	“Richards” motorised conveyor driving drums	Free	20%*	25%*	10.2
4894	84.22.038	“Demag Autovac 5” vacuum operated lifting device	Free	20%*	25%*	10.2
4996	84.59.129	Portable hydraulic presses which operate in the range of 30 to 100 tons	Free	20%*	25%*	10.2
4978	84.63.011	MA8E 2:1 ratio gearboxes used in the construction of portable grain augers	Free	Free	Free	10.3
4976	85.12.019	Barrel heating elements for use in a plastic extruding machine ..	Free	20%*	25%*	10.2
4829	85.14.022	Sony Audio frequency electric amplifiers—models: SQA100, SQA200, SQD1000, TA88, TA200E, TA1130, TA2240, TA3130F, TA3140F, TA3200F, TA4300F, TAD43F	Free	20%	25%	..
4937	85.14.022	Ringmaster amplifiers—types FC11 and FD133	Free	20%	25%	..
4992	85.19.001	Rocker switches for use in the manufacture of electrical appliances	25%*	..	25%*	10.8
4990	85.19.001	Switches, multi-push-button for use in the manufacture of electrical appliances	25%*	..	25%*	10.8
4988	87.06.059	Electric-pneumatic door engines for use in the manufacture of bus bodies	25%*	..	25%*	10.8
4766	90.24.011	Compression tester—specially designed for use with motor vehicles, for pinpointing trouble in valves, pistons, rings, cylinders. 300 lb capacity. Heavy duty construction	Free	20%	25%	..
4766	90.24.011	Motor monitor—dashboard mount combination vacuum and fuel pump tester and motor monitor; gives continuous indication. Calibrated 0–30" vacuum. 0–7 lb pressure	Free	20%	25%	..
4766	90.24.011	Vacuum and fuel pump tester. For locating troubles such as sticky valves, leaky intake manifold, late timing, choked muffler; worn rings or cylinder walls; check fuel pump pressure; test all vacuum operated devices. 2½" diameter; calibrated 0–30" for vacuum, and 0–7 lb pressure	Free	20%	25%	..

*or such lower rate of duty as the Minister may in any case direct

Any person wishing to lodge an objection to the granting of these applications should do so in writing on or before 15 February 1973. Submissions should include a reference to the application number, Tariff item, and description of goods concerned, be addressed to the Comptroller of Customs, Private Bag, Wellington, and supported by information as to:

- The range of equivalent goods manufactured locally;
- The proportion of New Zealand and imported material used in manufacture;
- Present and potential output; and
- Details of Factory cost in terms of materials, labour, overhead, etc.

Dated at Wellington this 25th day of January 1973.

J. A. KEAN, Comptroller of Customs.