THE NEW ZEALAND GAZETTE

Tariff Notice No. 1974/110-Applications for Approval

NOTICE is hereby given that applications have been made to the Minister of Customs for concessionary entry of the following goods at the rates of Customs duty shown:

| Appn. No. | Tariff Item | Goods | Rates of Duty | | | Part |
|--------------|------------------------|---|---|----------------|----------------|------------|
| | | | Normal | B.P. | Other Pref. | II Ref. |
| 19388 | 29.08.000 | Isopropyl Oxitol-ethylene glycol mono isopropyl ether, used as a solvent in the surface coating industry | Free* | Free* | Free* | 10 |
| 19387 | 29.13.009 | Diacetone alcohol-4 hydroxy 4 methyl pentanone-2, used as a high boiling point solvent in the surface coating industry | Free* | Free* | Free* | 10 |
| 19332 | 29.24.009 | Dowicill 200, used in the manufacture of cosmetic surfactants | Free* | Free* | Free* | 10 |
| 19333 | 29.40.009 | Lipase powder, a powered product containing fat splitting enzymes, used to impart a sharp flavour to hard type cheeses | Free* | Free* | Free* | 10 |
| 19293 | 32.09.003 | Araldite 488N-40; a resin produced from epichlorhydrin and bisphenol "A", used to manufacture specialised coatings for aluminium products where good adhesion is required to the substrat | Free* | Free* | Free* | 10 |
| 9422 | 35.06.001 | Loctite 504, used for the elimination of gaskets | Free | Free | | 1 . |
| 9295 | 38.19.299 | Maxwell descaler dry, a flushing agent for water cooling of electric induction melting furnace | Free* | Free* | Free* | 10 |
| 9304 | 40.09.001 | Vulcanised rubber tubing, unhardened, unground in the rough, for use in reconditioning typewriter platens and other office machine rollers | Free* | Free* | | |
| 8829 | 51.01.029 | 940 decitex (840 denier) F96 filament high tenacity bright raw white nylon, 6 yarn on returnable aluminium bobbins | Free* | Free* | Free* | 10 |
| 8828 | 51.01.038 | 1100 decitex (1000 denier) 250 filament bright high tenacity raw white type P502Z polyester yarn on paper cheeses | Free* | Free* | Free* | 10 |
| 8776 | 55.09.049 | Blowing wrappers, for use on decoclave and decotizing machines in the textile industry | Free* | Free* | Free* | 10 |
| 9381 | 59.15.009 | Textile fire fighting hose | Free* | Free* | Free* | 12 |
| 8706 | 60.05.159 | Knitted banding, for use in manufacturing caps | Free* | Free* | Free* | 10 |
| 9421 | 73.14.011 | Galvanised steel wire 0.9 mm (19 S.W.G.), used in the manufacture of wire netting | Free* | Free* | Free* | 10 |
| 9073 | 73.40.497 | Drop forged rings to BSS 781:1290 and BSS 781: 2902 | Free* | Free* | Free* | 10 |
| 9329 | 76.16.098 | Alumina grinding beads, used in making a fungicide for pastures | Free* | Free* | Free* | 1 |
| 3909 | 83.01.018 | Electric strikes, for access control in high grade security areas | Free* | Free* | Free* | 1 |
| 9357 9374 | 84.14.001 | Diesel engine or electric motor driven centrifugal fire pumps, for use in the manufacture of fire pumps Specially designed and fabricated fire-research test furnaces, to be | Free* | Free* | Free* | 1 |
| 9374 | 84.17.129 | used for scientific research and testing Rocking type high pressure hydrogenation autoclave, used for | Free* | Free* | Free* | 10 |
| 282 | 84,45,029 | research and educational purposes Whitney Universal manual duplicator No. 635, used in the fabri- | Free* | Free* | Free* | 1 |
| | | cation of earthworking machine cabs, with a 30 ton (30.48 t) capacity able to punch holes up to 5" (127.0 mm) diameter in material up to \frac{3}{8}" (0.375 mm) thick, with 30" \times 50" (762.0 mm \times 1270.0 mm) template capacity | | | | |
| 9317 | 84.17.129 | Vinamold melter, electrically heated and thermostatically con- trolled, used in the manufacture of paua shell souvenirs | Free* | Free* | Free* | 1 |
| 3924 3925 | 85.01.011 | | Free* | Free* | Free* | 1 |
| 3868 | 85.11.009 | Carbolite CFM2/1450/AUX/BACH furnace, for coal analysis conforming to the British Standards Institute BS1016 Part 6, 1958 | Free* | Free* | Free* | 1 |
| 9316 8862 | 85.22.209 85.23.031 | JVC CD-4 Disc Demodulator Prefabricated cables of grey P.V.C. insulated single core cable with tinned conductor of copper, rated voltages 0.5 mm ² : 250 V; 0.75 mm ² : 400V and 1 - 2.5 mm ² : 700V | Free* Free* | Free* | Free* | 1 |
| 9283 | 90.28.009 | Du Pont blasting galvanometer, used for testing individual electric blasting caps and firing circuits | Free* | Free* | Free* | 1 |
| 397 | 90.28.009 | Electronic voltmeters, used for laboratory, industrial and service applications where an analogue or digital measurement of a potential difference is required | Free* | Free* | Free* | 1 |
| 8684 9395 | 90.28.009 90.28.009 | Field strength meters LKB Uvichord and calculating absorptiometers, used for laboratory | Free* Free* | Free* Free* | Free* Free* | 10 |
| 9393 | 90.28.009 | analysis and scientific research Recording voltmeters, ammeters, wattmeters and power factor meters, used for measuring and subsequent analysis of the basic | Free* | Free* | Free* | 10 |
| 9285 | 90.28.009 | units found in power distribution VME Velocity siesmograph, used for recording ground vibrations and air blasts simultaneously | Free* | Free* | Free* | 10 |
| | | and an Diasts simultaneously | *or such higher rate of duty as the Minister may in any case decide | | | |

Any person wishing to lodge an objection to the granting of these applications should do so in writing on or before 14 November 1974. Submissions should include a reference to the application number, Tariff item and description of goods concerned, be addressed to the Comptroller of Customs, Private Bag, Wellington, and supported by information as to:

⁽a) The range of equivalent goods manufactured locally;
(b) The proportion of New Zealand and imported material used in manufacture;
(c) Present and potential output; and
(d) Details of factory cost in terms of materials, labour, overhead, etc.

Dated at Wellington this 24th day of October 1974.