

Tariff Notice No. 1974/40—Applications for Continuation of Approval

NOTICE is hereby given that applications have been made for continuation of the following approvals of the Minister of Customs:

Appn. No.	Tariff Item	Goods	Rates of Duty			Part II Ref.	List No.	Effective	
			B.P.	MFN.	Gen.			From	To
12447	33.06.009	“Lipstick colour base” concentrated, when declared by a manufacturer for use by him only in making lipsticks	Free	..	Free	10.8	30	1/1/72	30/6/74
12649	34.02.000	Acetulan	Free	..	Free	10.8	..	1/1/72	31/3/74
12686	34.02.000	Redicote H.B.	Free	..	Free	10.8	..	1/1/72	31/3/74
12746	34.02.000	Utex	Free	..	Free	10.8	..	1/1/72	31/3/74
12607	38.19.299	Platinum Catalyst R16H	Free	..	Free	10.8	127	1/7/73	30/6/74
12677	38.19.299	YK Carrier OL	Free	..	Free	10.8	110	1/3/73	31/3/74
12685	39.07.398	Laminated plastic cards for use with imprinting machines	Free	Free	Free	10.2	117	1/7/73	31/1/74
12708	40.14.069	Radial tyre bead expanders for tubeless tyres ..	Free	Free	Free	10.2	121	1/7/73	31/12/73
12743	48.01.409	Paper felt, when declared by a manufacturer for use by him only in making bituminous roofing or building paper	Free	..	Free	10.8	5	1/1/72	30/6/74
12688	65.06.001	Helmets, crash, peculiar for use by aircraft pilots ..	Free	20%	25%	..	7	1/1/72	31/12/73
12612	68.16.009	Chesterton style 375 pure graphite filament packing, braided into continuous length	Free	..	Free	10.8	..	1/1/72	31/3/74
12558	73.36.001	Parts of gas burners (excluding burner jets) when declared by a manufacturer for use by him only in making gas burners	Free	..	Free	10.8	91	1/1/72	30/4/74
12558	73.36.001	Piezo ignitors	Free	..	Free	10.8	91	1/1/72	30/4/74
12620	73.40.497	Mountings, antivibration, for machinery	Free	Free	Free	10.2	157	1/1/74	30/6/74
12557	84.30.013	Sausage filling and linking machines	Free	Free	Free	10.2	..	1/1/72	31/8/74
12619	84.59.128	Buffing machines peculiar to use with tyres	Free	Free	Free	10.2	157	1/1/74	31/7/74
12695	84.61	Cocks and valves:	Free	Free	Free	10.2
		Excluding:							
		(1) Penstocks, floodgates	1/1/72	30/6/74
		(2) Valves, gate, of the following types:	1/1/72	30/6/74
		(a) Stainless steel 3 in. to 18 in., or cast iron 3 in. to 14 in., specifically designed for use with pulp or paper stock							
		(b) Brass, $\frac{1}{2}$ in. and $\frac{3}{4}$ in.							
		(c) $\frac{3}{8}$ in. to 4 in. of any kind of bronze							
		(d) Flanged cast iron, to B.S. 3464, size 4 in.							
		(3) Valves, globe, of any kind of bronze, commonly used with steam at working pressures of 50 p.s.i. or over, of the following types:					..	1/1/72	30/6/74
		(a) Stainless steel seats, screwed $\frac{3}{8}$ in. to 2 in.							
		(b) Yoke top with bronze or stainless steel seats, flanged $\frac{3}{4}$ in. to 6 in.							
		(c) Angle, yoke top with bronze or stainless steel seats, flanged, 1 in. to 3 in.							
		(d) Valves, safety, spring-loaded, screwed or flanged, $\frac{3}{8}$ in. to 4 in.							
		(e) Fibre or teflon seats, screwed, sizes $\frac{1}{2}$ in. to 2 in.							
		(f) Flanged bonnet top $\frac{3}{4}$ in. to 3 in., with bronze or stainless steel seats and a working pressure of up to 125 p.s.i.							
		(g) Flanged regulating check angle or straight type $\frac{3}{4}$ in. to 6 in. with bronze or stainless steel seats and working pressure up to 250 p.s.i.							
		(4) Valves, foot, of copper alloy not exceeding 2" of cast iron or steel of all types of seats (excluding leather flap type) sizes 2"-12"					72	1/10/72	30/6/74
		(5) Valves, float, of brass or other copper alloy, not exceeding 6 in.					..	1/1/72	30/6/74
		(6) Valves, ball:					149	1/12/73	30/6/74
		(a) Screwed, stainless steel and cast carbon steel bodies, sizes 9.52 mm to 50.8 mm B.S.P. (other than multiport and jacketed types)							
		(b) Flanged, cast stainless steel or cast steel, sizes 3 in. and 4 in.							
		(7) Sluice or wedge gate (or stop) valves of cast iron, and of alloyed iron, for waterworks purposes and like application, in sizes 4 in., 6 in., 8 in., 10 in., 12 in., double flange spigot and socket ends, hand operated waterworks pattern, for test pressures not exceeding 800 foot head of water, with or without copper based trims and spindles in accordance with UKBS 1218 and NZSS 784					..	1/1/72	30/6/74
		(8) Check valves (reflux) cast iron 3 in., 4 in., 6 in., and 8 in., free acting, 4 in., 6 in., 8 in., external lever operated, standard types for test pressures not exceeding 600 foot head of fluid, not including non-convulsive types					..	1/1/72	30/6/74