

TARIFF DECISION LIST No. 9

Decisions of the Minister of Customs Under the Customs Tariff (Subject to Amendment or Cancellation by Notification in the Gazette)

APPROVALS

Tariff Item No.	Goods	Rates of Duty			Part II Ref.	List No.	Effective	
		Normal	B.P.	Other Pref.			From	To*
73.40.489	Bobbins, reels, cones and similar supports peculiar for holding yarn during storage or processing in woollen or hosiery mills	Free	Free	Free	10.1	9	1/7/74	31/12/74
73.40.497	Wire, welding, tubular steel, with granular metallic core, designed for automatic or semi-automatic hard facing of metal surfaces	Free	Free	Free	10.8	9	1/7/74	30/6/80
74.03.002	Bars, brass, 7.1 mm × 20 s.w.g. (0.91 mm)	Free	Free	Free	10.8	9	1/7/74	30/6/77
84.06	Water cooled engines, as may be approved: Approved:	Free	Free	Aul Free	..			
	Volva Penta AQD70B/750					9	1/7/74	31/12/76
84.61	Cocks and valves:	Free	Free	Free	10.2			
	EXCLUDING:							
	(1) Penstocks, floodgates					9	1/7/74	..
	(2) Valves, gate, of the following types:					9	1/7/74	..
	(a) Stainless steel 76.2 mm to 457.2 mm, or cast iron 76.2 mm to 355.6 mm specifically designed for use with pulp or paper stock							
	(b) Brass, 12.7 mm and 19.05 mm							
	(c) 9.52 mm to 101.6 mm of any kind of bronze							
	(d) Flanged cast iron, to B.S. 3464, size 101.6 mm							
	(3) Valves, globe, of any kind of bronze, commonly used with steam at working pressures of 344.7 kPa or over of the following types:					9	1/7/74	..
	(a) Stainless steel seats, screwed 9.52 mm to 50.8 mm							
	(b) Yoke top with bronze or stainless steel seats, flanged 19.05 mm to 152.4 mm							
	(c) Angle, yoke top with bronze or stainless steel seats, flanged, 25.4 mm to 76.2 mm							
	(d) Valves, safety, spring-loaded, screwed or flanged, 9.52 mm to 101.6 mm							
	(e) Fibre or teflon seats, screwed, sizes 12.7 mm to 50.8 mm							
	(f) Flanged bonnet top 19.05 mm to 76.2 mm with bronze or stainless steel seats and a working pressure of up to 861.84 kPa							
	(g) Flanged regulating check angle or straight type 19.05 mm to 152.4 mm with bronze or stainless steel seats and working pressure up to 1723.7 kPa							
	(4) Valves, foot, of copper alloy not exceeding 50.8 mm of cast iron or steel of all types of seats (excluding leather flap type) sizes 50.8 mm to 304.8 mm					9	1/7/74	..
	(5) Valves, float, of brass or other copper alloy, not exceeding 152.4 mm					9	1/7/74	..
	(6) Valves, ball:					9	1/7/74	..
	(a) Screwed, stainless steel and cast carbon steel bodies, sizes 9.52 mm to 50.8 mm B.S.P. (other than multiport and jacketed types)							
	(b) Flanged, cast stainless steel or cast steel, sizes 50.8 mm, 76.2 mm, and 101.6 mm tested fire safe							
	(7) Sluice or wedge gate (or stop) valves of cast iron, and of alloyed iron, for waterworks purposes and like application, in sizes 101.6 mm, 152.4 mm, 203.2 mm, 254.0 mm, and 304.8 mm double flange spigot, and socket ends, hand operated waterworks pattern, for test pressures not exceeding 243.84 m head of water, with or without copper based trims and spindles in accordance with BS 1218 and NZS 784					9	1/7/74	..