

TARIFF DECISION LIST No. 9—continued

APPROVALS—continued

| Tariff Item No. | Goods | Rates of Duty | | | Part II Ref. | List No. | Effective | |
|------------------------|--|---------------|------|-------------|--------------|----------|-----------|---------|
| | | Normal | B.P. | Other Pref. | | | From | To* |
| 84.61 <i>cont'd</i> | Cocks and valves— <i>continued</i> EXCLUDING— <i>continued</i> | | | | | | | |
| | (20) Check valves: | | | | | 9 | 1/1/74 | .. |
| | (a) Wafer type, all materials sized 50.8 mm to 609.6 mm. Pressure temperature rating ASA 150, 300, 600 B.S. table, D, E, F, H, suitable for chemicals, water, oil, gas (as options these valves may be fitted with back flush lever, adjustable counter balance, and cam-operated micro switch) | | | | | | | |
| | (b) Backflow preventor double check valves, 50.8 mm to 304.8 mm peculiar to working pressure 1896 kPa | | | | | | | |
| | (c) Swing check valves, bronze, to BS 1953:1964 NZS 1430:1966 in sizes 12.7 mm to 50.8 mm | | | | | | | |
| | (21) Valves for hydraulic pumps of tractors, loaders, excavators, and similar machines | | | | | 9 | 1/7/74 | .. |
| | (22) Purpose made 152.4 mm and 101.6 mm diameter Fullway wet pipe sprinkler alarm, basic non-return valves, flanged, cast iron | | | | | 9 | 1/7/74 | .. |
| | (23) Oil control valves, constant level, for vapourising and other types of burner requiring a metering control. Suitable for use with light fuel oil, diesel or kerosene, up to a 9.1 m head. Standard head mounting, manually or thermostatically controlled | | | | | 9 | 1/7/74 | .. |
| | (24) Diaphragm valves of cast iron, screwed B.S.P., hand wheel operated, suitable for use with compressed air, water and other non-corrosive liquids, but not suitable for steam: Screwed: 12.7 mm, 19.05 mm, 25.4 mm, up to 1723.7 kPa (17.5 kg/cm ²) 38.1 mm, up to 1206.58 kPa (12.5 kg/cm ²) 50.8 mm up to 861.85 kPa (8.75 kg/cm ²) Flanged: to B.S. table D. 50.8 mm up to 861.85 kPa (8.75 kg/cm ²) | | | | | 9 | 1/7/74 | .. |
| | (25) Butterfly valves 76.2 mm, 101.6 mm, 152.4 mm, of cast iron, wrench operated, with rubber liners, working pressure 1378.00 kPa | | | | | 9 | 1/7/74 | .. |
| | (NOTE: This approval does not cover taps, bibcocks, or fire hydrants) | | | | | | | |
| 85.22.209 | Electrolytic polishing machine, peculiar to use for polishing dental castings | Free | Free | Free | 23.7 | 9 | 1/7/74 | 30/6/80 |
| 90.07 | Cameras of the following kinds and parts therefor, when made to take negatives of quarter plate size (10.795 cm × 8.255 cm) or larger: Kodak view camera, reflex (including Graflex and Speed Graphic) | Free | Free | Free | 10.2 | 9 | 1/7/74 | 30/6/80 |
| 90.10.049 | Film-splicing machines | Free | Free | Free | 10.2 | 9 | 1/7/74 | 30/6/80 |
| 90.10.049 | Printing machines, automatic, projection type, for printing photographs | Free | Free | Free | 10.2 | 9 | 1/7/74 | 30/6/80 |
| 90.10.049 | Silver recovery units | Free | Free | Free | 10.2 | 9 | 1/7/74 | 30/6/80 |
| 90.10.049 | Tanks, dishes or trays, 2.27 litres capacity or over, composed of, or lined with acid resisting material, peculiar to use in developing films or plates | Free | Free | Free | 10.2 | 9 | 1/7/74 | 30/6/80 |
| 90.10.049 | Washing machines, photoprint, including stainless steel dishes and baskets therefor | Free | Free | Free | 10.2 | 9 | 1/7/74 | 30/6/80 |
| 92.11.021 | Tape recorders, professional type: | Free | Free | Free | 10.2 | | | |
| | Approved: | | | | | | | |
| | Ampex AG440 | | | | | 9 | 1/7/74 | 30/9/77 |
| | Ampex AG500 | | | | | 9 | 1/7/74 | 30/9/77 |