

Tariff Notice No. 1975/1—Applications for Approval

NOTICE is hereby given that applications have been made to the Minister of Customs for concessionary entry of the following goods at the rates of Customs duty shown:

Appn. No.	Tariff Item	Goods	Rates of Duty			Part II Ref.
			Normal	B.P.	Other Pref.	
21159	23.07.009	Chlortetracycline feed grade antibiotic, used for the manufacture of stock and poultry foods	Free*	Free*	Free*	10.2
21129	34.02.000	Oakite fleetline 111, a heavy duty detergent for cleaning aircraft . .	Free*	Free*	Free*	10.8
21185	34.02.000	12.5% solution of dioctyl ester of sulpho succinic acid in water with a trace of commercial perfume, for cleaning optical lenses	Free*	Free*	Free*	10.8
21239	34.02.000	Toximul AP, an anionic-nonionic emulsifier, used for pesticide formulations	Free*	Free*	Free*	10.8
21132	35.06.001	Resorcinol formaldehyde glue: viz, Kauresen 440 and 457 hardeners, used for the utilisation of timber by finger jointing and manufacture of glue laminated timber beams	Free	Free		..
21240	39.01.022	Resin ERL 4221, a stabiliser for Diazinon	Free*	Free*		..
20803	73.15.249	Circles, with or without centre holes, cut from still plate, used for the manufacture of saw blades for cutting concrete	Free*	Free*	Free*	10.8
21119	73.15.291	Alloy steel and high carbon steel, etc: Sheets and plates, etc: Of alloy steel: Other kinds: Other: Polished	Free*	Free*	Free*	10.8
21123	73.27.039	Stainless steel mesh, used in the manufacturing and construction industries, etc	Free*	Free*	Free*	10.8
21174	73.40.497	Schneebeli tree bicycle, used for collecting seeds from mature trees without damaging the bark, and for climbing	Free*	Free*	Free*	10.2
21179	74.04.012	1.62 mm × 33 mm and 1.62 mm × 30 mm brass strip, used for the manufacture of pins for moulding on electric plugs	Free*	Free*	Free*	10.8
17114	83.01.018	Suitcase locks	Free*	Free*	Free*	10.8
21220	84.10.009	Grouting pump, hand generated with 76.2 mm diameter piston and 101.6 mm stroke, capable of a working pressure of 1.034 MPa and has an output at 60 strokes per minute of 27 litres per minute	Free*	Free*	Free*	10.2
21114	84.15.219	Upright biological storage freezer, to be used for the storage of biological samples at low temperatures for long periods of time	Free*	Free*	Free*	10.2
21111	84.16.009	Hydraulic sammying press, used for the sammying of all kinds of vegetably tanned or chrome tanned leather	Free*	Free*	Free*	10.2
21113	84.17.129	Freeze-dryer and manifold assembly, used for preparation of hormone solution	Free*	Free*	Free*	10.2
18869	84.21.009	Airless paint spraying outfits (excluding compressors)	Free*	Free*	Free*	10.2
18869	84.21.009	Portable paint spraying outfits (excluding motors), other than airless	Free*	Free*	Free*	10.2
21137	84.22.028	FN Hopper loaders, used for carrying and supplying pellets and powders mixed with pigments and other additives for plastic moulding machines	Free*	Free*	Free*	10.2
21112	84.22.028	Side conveyors with a bonded belt rib and angle adjustment between 20° and 45°, used for conveyance of spool runners from moulding machines	Free*	Free*	Free*	10.2
20091	84.43.009	Ingot moulds	Free*	Free*	Free*	10.2
21064	84.45.009	Ficep model 32V and 32 Beton shear and bender, for use in the engineering industry	Free*	Free*	Free*	10.2
21164	84.45.029	Nova Major and Super Brown cut-off machines, used for cutting solid bars, tubes and shapes of metal	Free*	Free*	Free*	10.2
21165	84.45.029	Tauring model Alfa 40-RV bar, pipe and bending machine, used for the manufacture of furniture	Free*	Free*	Free*	10.2
21168	84.54.021	Postage stamp affixer without calculating device, used to position and fix postal stamps upon envelopes, purchased in bulk	Free*	Free*		..
21152	84.63.049	Borg-Warner agricultural gear boxes	Free*	Free*	Free*	10.2
21153	84.63.049	Gears, reduction (EXCLUDING co-axial gears, designed for input 0.37 to 7.46 kW with output r.p.m. from 12-611): (i) With two or more reductions EXCLUDING: (a) Worm types (b) Single helical, double reduction shaft mounted types (c) Spur and helical parallel axis reduction boxes designed for 0.37 to 3.73 kW (ii) Single helical types for transmitting powers exceeding 14.91 kW EXCLUDING: (a) Double reduction shaft mounted types (iii) Double helical types (iv) Worm types, in which the shortest distance between the axes of the input and output shafts exceeds 20.95 cm	Free*	Free*	Free*	10.2