

TARIFF DECISION LIST No. 82—continued

APPROVALS—continued

Tariff Item No.	Goods	Rates of Duty			Part II Ref.	List No.	Effective	
		Normal	B.P.	Other Pref.			From	To*
73.20.051	Mueller line stopper fittings 152.4 mm to 203.2 mm (6 in. to 8 in.)	Free	Free	Free	10.2	82	1/2/75	30/6/79
73.20.059	Mueller line stopper fittings 254 mm to 304.8 mm (10 in. to 12 in.)	Free	Free	Free	10.2	82	1/2/75	30/6/79
73.36.011	Piezo ignitors, peculiar to use in the manufacture of gas fires	Free	Free	Free	10.8	82	1/7/75	30/6/77
73.40.497	Dished and flanged ends of semi-ellipsoidal shapes formed from not more than two pieces, with an internal diameter of over 2133.6 mm (84 in.) and a thickness of over 28.58 mm (1½ in.)	Free	Free	Free	10.2	82	20/5/75	30/6/77
73.40.497	Dished and flanged ends of torispherical shape, formed from not more than two pieces, of the following nominal sizes: 1524 mm (60 in.) outside diameter × 9.53 mm (¾ in.) thickness 1828.8 mm (72 in.) outside diameter × 12.70 mm (½ in.) thickness 1981.2 mm (78 in.) outside diameter × 9.53 mm (¾ in.) or greater thickness 2133.6 mm (84 in.) outside diameter × 12.70 mm (½ in.) or greater thickness 2438.4 mm (96 in.) outside diameter × 9.53 mm (¾ in.) or greater thickness 2590.8 mm (102 in.) outside diameter × 19.05 mm (¾ in.) or greater thickness	Free	Free	Free	10.2	82	20/5/75	30/6/77
73.40.497	Forged sling hooks, grab hooks, factory hooks, latch lock hooks, choker hooks of herc alloy	Free	Free	Free	10.2	82	1/1/75	30/6/78
76.07.000	Foreman night caps	Free	Free	Free	10.2	82	1/3/75	31/3/78
83.09.029	Caps and rivets, commonly used for making footwear	Free	Free	Free	10.8	82	1/3/75	31/3/80
84.10.009	Centrifugal, single stage, heavy duty paper stock pumps	Free	Free	Free	10.2	82	1/7/75	30/9/75
84.10.009	Pumps, centrifugal, single stage, as may be approved, excluding chokeless sump or sewage pumps: Approved: Designed to pump liquids containing solids such as sand or gravel Gear driven Having delivery connections of a nominal internal diameter exceeding 17.78 cm (7 in.) Having delivery heads exceeding 76.2 m (250 ft) when rotating at speeds not exceeding 2900 r.p.m. Self-priming, or portable, having delivery connections of a nominal internal diameter exceeding 7.62 cm (3 in.)	Free	Free	Free	10.2	82	1/7/74	30/9/75
84.10.009	Pumps specially sealed, for use with L.P. gas, ammonia and petro-chemicals	Free	Free	Free	10.2	82	1/8/75	30/9/75
84.18.139	Hydraulic filter elements, peculiar to use with Acker drill rigs	Free	Free	Free	10.2	82	1/3/75	30/6/78
84.18.139	Perry filters and components: EXCLUDING: Cartridges for models 5020, 5020 PAF, 5025, 5030	Free	Free	Free	10.2	82	1/2/75	31/3/77
84.21.003	Rotary barrel shot blasting machines, excluding dust collecting equipment	Free	Free	Free	10.2	82	1/2/75	30/9/79