

Rounds—		Per Tonne	
Reinforcing and engineering:		\$	c
6.5 mm	10	75
10 mm	8	00
12 mm	4	00
16 mm	1	00
Squares, 10 mm	3	50
Flats—		Per Tonne	
25 mm × 5 mm	7	00
25 mm × 6 mm	5	00
25 mm × 8 mm	5	00
25 mm × 10 mm	4	00
25 mm × 11 mm	4	00
25 mm × 12 mm	4	00
30 mm × 5 mm	7	00
30 mm × 6 mm	5	00
30 mm × 8 mm	5	00
30 mm × 10 mm	4	00
30 mm × 11 mm	4	00
30 mm × 12 mm	4	00
40 mm × 5 mm	6	00
40 mm × 6 mm	4	00
40 mm × 8 mm	4	00
40 mm × 10 mm	4	00
40 mm × 11 mm	4	00
40 mm × 12 mm	2	00
50 mm × 6 mm	4	00
50 mm × 8 mm	4	00
50 mm × 10 mm	2	00
50 mm × 11 mm	2	00
60 mm × 6 mm	4	00
60 mm × 8 mm	4	00
60 mm × 10 mm	2	00
80 mm × 6 mm	3	00
80 mm × 8 mm	3	00
100 mm × 6 mm	3	00
100 mm × 8 mm	3	00
100 mm × 10 mm	1	00
100 mm × 12 mm	1	00
Angles—		Per Tonne	
25 mm × 25 mm × 5 mm	10	00
25 mm × 25 mm × 6 mm	8	00
30 mm × 30 mm × 5 mm	7	00
30 mm × 30 mm × 6 mm	6	00
40 mm × 40 mm × 5 mm	4	00
40 mm × 40 mm × 6 mm	2	00
50 mm × 50 mm × 5 mm	2	00
Channels—		Per Tonne	
3" × 1½"	8	00
4" × 2"	6	00
5" × 2½"	3	00
6" × 3"	3	00

Each of the following extras may be added to basis price plus appropriate size extras.

(2) Quantity		Per Tonne	
		\$	c
For products bundled in 1 Tonne Lifts			
1 tonne to under 2 tonnes	6	00
2 tonnes to under 3 tonnes	4	00
3 tonnes to under 4 tonnes	2	00
Minimum order 1 tonne			
For products bundled in 2 Tonne Lifts			
2 tonnes to under 4 tonnes	4	00

The above quantity extras apply to items of one size, quality, and length.

Where quantities under 10 tonnes of an item incur any extra freight, cartage, or other charges, such charges are to customer's account.

- (3) Length
 - Over 10 m to 12 m 1 00
 - Over 12 m to 15 m 1 50
- (4) Cold Straightening
 - Flats only 1 00
- (5) Deformed Bars 4 00
- (6) Bar marking HY. 60 4 50
- (7) Quality

This section includes quality extras added to basis price, plus any extras added under 6 (1, 2, 3, 4, and 5) above.

Standard Specifications			Per Tonne Extra
Specification	Analysis		\$ c
NZSS 3402P	Grade 275 Deformed Sulphur .06 max. Phosphorus .06 max.	1 00
NZSS 3402P:	Grade 275 Plain Sulphur .06 max. Mild .06 max.	Basis price
Medium Tensile 500/580 MPa	Sulphur .06 max. Phosphorus .06 max.	1 50
High Tensile 570/660 MPa	Sulphur .06 max. Phosphorus .06 max.	1 50
NZSS 4360 ..	Sulphur .06 max. Phosphorus .06 max.	Basis price
NZSS 3402P	Grade 380 High Yield Steel	8 75

- (8) Tests
 - Government inspection 1 00
 - To Lloyds, etc. 1 50
 - By buyer at supplier's works 8 00

			Per Tonne Extra
			\$ c
Surface inspection	2 00
Proof stress	3 00
Additional chemical analysis	3 00
Impact	3 50
Brinnell on not less than 10 percent of the bars	7 50
Inspection or testing of lots less than 1 tonne	75
			lump sum per test or set of tests or 20c per tonne whichever is the greater

Where test certificates are called for giving mechanical properties covering any of the numerical series of steels 1 00

- (9) Special Paint Marking or Hand Stamping 1 00
- (10) Cutting Margin

The standard cutting margin is — 0 + 50 mm is covered in the basis price.

- (11) Extras for exact lengths are by arrangement between buyer and seller.

Dated at Wellington this 5th day of June 1975.
 The seal of the Price Tribunal was affixed in the presence of:
 K. R. CONGREVE, President.
 A. G. BEADLE, Member.
 M. A. HERCUS, Member.
 F. F. SIMMONS, Member.

*Gazette, 30 May 1974, Vol. I, p. 1088.

(T. and I.)