

TARIFF DECISION LIST No. 108

Decisions of the Minister of Customs Under the Customs Tariff (Subject to Amendment or Cancellation by Notification in the Gazette)

DETERMINATION

Tariff Item No.	Goods	Rates of Duty			Part II Ref.	List No.	Effective	
		Normal	B.P.	Other Pref.			From	To
82.05.021 Deter'n	<p>(1) Drills: 1974 Jobbers, standard Helix type 1975 only, right hand 3/64 in. to 1976 ½ in., 1.00 mm to 13.00 mm 1977 Straight Shank Stub, standard Helix type, right hand, 3/64 in. to ½ in. Long Series, standard Helix type, right hand, 3/64 in. to ½ in. Straight Shank Long Series, Long Reach, HSS, 1/8 in. to ½ in. Tungsten Carbide Twist, from 2.381 mm Blacksmith or HSS Twist, with 12.7 mm Shank, 33/64 in. to 1½ in. Reduced Shank, HSS (metal and woodworking), 6.00 mm to 13.00 mm Masonry: Rotary 3.00 mm to 25.50 mm Impact 3.00 mm to 25.50 mm Twist Drill Sets, 1.00 mm to 13.00 mm, 1/16 in. to ½ in.</p> <p>(2) Countersinks, single flute: ½ in. shank 9.52 mm to 19.05 mm ½ in. shank 15.88 mm to 19.05 mm</p> <p>(3) Reamers, Parallel Machine, Tungsten Carbide tipped, non-adjustable: Straight shank, all sizes under 14.29 mm Morse taper shank, all sizes over 14.29 mm</p> <p>(4) Router Bits—HSS —Tungsten Carbide tipped</p> <p>(5) Milling Cutters: Tungsten Carbide tipped, circular, other than throw away tip type</p> <p>(6) Facing Cutters, Tungsten Carbide tipped, circular, other than throw away tip type</p> <p>(7) Profile and Cutter Heads, Tungsten Carbide and HSS tipped</p> <p>(8) Tool Bits, HSS: Square Section—Special Cobalt —Super Cobalt Bevel Section—Special Cobalt Round Section—Super Cobalt</p> <p>(9) Lathe Tools (brazed on tips), Tungsten Carbide Tipped, standard pattern</p> <p>(10) Knives—Tungsten Carbide tipped —Steel</p> <p>(11) Taps, Carbon Steel Cut Thread, right hand, in the following sizes: B.S.W. 1/8 in. to 1 in. U.N.F. 3/16 in. to 1 in. I.S.O. Coarse, 3.00 mm × 0.50 mm to 24.00 mm × 3.00 mm</p> <p>(12) Button Dies, Carbon Steel, Circular split, 1 in. or 2 in. outside diameter, right hand, in the following sizes: B.S.W. 1/8 in. to 1 in. U.N.F. 3/16 in. to 1 in. I.S.O. Coarse 3.00 mm × 0.50 mm to 24.00 mm × 3.00 mm</p>	45%	29%	Aul Free Can 25% CPC 25%	..	108	11/4/75	..