## Tariff Notice No. 1976/148—Applications for Approval

NOTICE is hereby given that applications have been made to the Minister of Customs for concessionary entry of the following goods at the rates of Customs Duty shown:

Appn. No.	Tariff Item	Goods	Rates of Duty			Part
			Normal	B.P.	Other Pref.	II Ref.
38006	23.07.009	Halquinol (chlorhydromyquinoline) 60%, in chalk and 4.8% halquinol (chlorhydroxyquinoline) in chalk, used as growth promotant for pigs and poultry	Free*	Free*	Free*	10.
37992	34.02.000	Aquavex D, a wetting agent for use in the manufacture of tyres, as lubricant for water bags in tyre presses	Free*	Free*	Free*	10.
38083	34.02.000	Ellisol emulsifying base 5665, used for blending with mineral oils to provide a water soluble lubricant suitable for the manufacture of metal cutting, metal drawing and wire drawing preparations	Free*	Free*	Free*	10.
38037	34.02.000	Lipsol liquid, being a biodegradable surfactant for the complete	Free*	Free*	Free*	10.
38010	34.02.000	removal of all biological residues and radioactive contamination Noigen EA 50, 80, 110, 140, 140L, 150N, being polyethylene glycol nonyl phenyl ethers, used as surfactants in industrial preparations	Free*	Free*	Free*	10.
38019	34.02.000	and wool scouring detergents Quadrilan AT, quaternised fatty amine ethoxylate, an antistatic agent for P.V.C. and other polymers	Free*	Free*	Free*	10.
38098 38095	34.02.000	Sorbitan glycerol laurate, used in the manufacture of yeast Sulfopon HS, used as a surface active agent	Free* Free*	Free* Free*	Free* Free*	10. 10.
38089	34.03.001	Inchem No. 1180, a wire drawing compound	Free*	Free*	Free*	10.
38099	35.06.001	Cartofix Z3318 an adhesive used in wallpaper manufacture	Free	Free		
38012 38126	38.11.098 38.19.297	Napotate (2, 3, 56-tetrachloromitrobenzene), to delay sprouting of seed potatoes Powder lake, for use in manufacture of cosmetics	Free* Free*	Free*	Free*	10.2
36757	38.19.297	Prepared additive, for genie smoke generator to give smell and colour to the smoke produced	Free*	Free*	Free*	10.2
38102 38086	39.01.022 39.01.022	Analidite GY255, used in the manufacture of epoxy resins Analdite LC264, is an aluminium filled epoxy resin system for highly specialised tooling applications	Free* Free*	Free* Free*		· · ·
38096	39.02.022	Pliovic A02 (P.V.C. polymer with 5% acrylate), used in the manu- facture of automotive sealants	Free*	Free*		
38084 38101	39.02.022 39.02.032	Vicol 170, being a vinyl acetate co-polymer, alkali-soluble Vydax AR, 5100, 550 and 525, fluorotelomer dispersions, used as a release agent or for its anti-stick properties	Free* Free*	Free* Free*		
38104	39.07.396	Proplene (of polypropylene) pipe fittings, used for connecting and redirecting proplene pipes, used for conveying liquids at high	Free*	Free*	Free*	10.2
37954	40.14.008	temperatures or of a corrosive nature Rubber gaskets for Rogers and Anhydro milk evaporators	Free*	Free*		10
38038 38057	48.15.009 51.01.129	Substrata paper, used in teaching and technology	Free* Free*	Free* Free*	Free*	20. 10.
38008	59.02.001	tapes, elastics, braids and fringes Sammying sleeve of needled felt, non-woven, seamless, for squeezing liquid from hides on sammying machines	Free*	Free*		
38054	59.12.009	Textile coated fabric, used in the manufacture of strip plaster (dressing strip)	Free*	Free*	Free*	10.
37991 38017	60.06.018 68.03.009	Tacky bead wrap, used in the manufacture of rubber tyres Areas of slate $26\frac{1}{2}$ in. $\times 26\frac{1}{2}$ in. $\times \frac{3}{4}$ in. thick and ground to within 0.010 in. of flatness across corners and smooth on top face	Free* Free*	Free* Free*	Free* Free*	10.2
38060 37609	68.16.009 73.15.272	Carbon and graphite bearings, for revolving shafts Alloy steel and high carbon steel in the forms mentioned in heading No. 73.06 to 73.14; sheets and plates, less than 3 mm in thickness, not plated, coated or clad: Of alloy steel: worked:	Free* Free*	Free* Free*	Free* Free*	10.2
		perforated or cellular but not further worked				
38005 37949	73.15.361 73.15.481	Sandvik die steel, for making clicking knives Copper-coated alloy wire, for use with semi-automatic and automatic welding machines	Free* Free*	Free*	Free* Free*	10.2
38105	73.20.009	Compensators, used in the manufacture of pumps	Free*	Free*	Free*	10.2
8111 8075	73.20.038 74.03.002	S.S. butt welding stub ends 154.2 mm (6 in.) SCH 10 316L Brass flats in 3.6576 m (12 ft) long extrusions	Free* Free*	Free* Free*	Free* Free*	10.2
8075	74.03.012	Equal section, equal angle brass, in 3.6576 m (12 ft) long extrusions	Free*	Free*	Free*	10.8
38080 38075	74.03.031 74.04.012	Drawn brass strip, soft VDP 67, used in making animal eartags Equal section, unequal angle brass, in 3.6576 m (12 ft) long extrusions	Free* Free*	Free* Free*	Free*	10.2
38039	74.04.021	Copper sheets polished one side and that side with a plastic coating, used as a raw material in metal manufacture	Free*	Free*	Free*	10.8
38075 38135	74.04.032 74.08.001	Brass channels, in 3.6576 m (12 ft) long extrusions	Free* Free*	Free* Free*	Free* Free*	10.8
38078	83.02.099	chamber, with bosses therefor, used in central heating systems Dzus fasteners, to be used in manufacture of electrical switchboxes, coach bodies and the like	Free*	Free*	Free*	10.2
38051	84.10.009	Dishwasher pump Singer Controls Ltd model 19125/1111 and 19126/1118, for incorporation into domestic dish washers	Free*	Free*	Free*	10.2
38033 37980	84.10.009 84.10.009	Gusmer beer filter pumps Milton Roy Proportioning pumps, with liquid ends of stainless steel, for delivery at pressures above 40 p.s.i. of liquids or slurries and	Free* Free*	Free* Free*	Free*	10.2
37947	84.11.051	with flow adjustable during operation Component parts for the manufacture of portable air compressors, with outputs of 85, 125 and 160 c.f.m.	Free*	Free*	Free*	10.2
37999	84.11.069	Ingersoll rand 2-stage compressors, stationary under 50 c.f.m., used to power pneumatic tools	Free*	Free*	Free*	10.2