THE NEW ZEALAND GAZETTE

TARIFF DECISION LIST No. 180—continued Approvals—continued

Tariff Item No.	Goods	Rates of Duty			Part	List	Effective	
		Normal	B.P.	Other Pref.	II Ref.	No.	From	То•
40.09.011	Delivery and suction hoses, of 20.32 mm (8 in.)	Free	Free			180		30/9/83
	and above internal diameter, of unhardened vulcanised rubber, reinforced with 4 ply nylon							
	and 2 ply cotton, with earthing wire and ASA flanges operating at 1034 kPa (150 p.s.i.), in	,	. '* . 					
40.09.011	6.09 m (20 ft) lengths Delivery and suction hose over 3.048 m (10 ft)	Free	Free			180		30/9/83
	in length, 317.5 mm ($12\frac{1}{2}$ in.) internal diameter		- F-4					
40.09.011	Dunlop synthetic rubber and fabric reinforced bitumen hose, incorporating one ply asbestos lining fabric, 15.25 cm and 20.32 cm bore size	Free	Free		••	180		30/9/83
40.09.011	Gates Adaptapipe 50 hose 101.6 mm (4 in.) and 152.4 mm (6 in.) diameter, in 4.2672 m (14 ft) lengths and over with or without fittings	Free	Free			180		30/9/83
40.09.011	Gates materials handling hose, 5.79 m (19 ft) lengths or over, of 30.5 cm (12 in.) I.D. or	Free	Free		••	180		30/9/83
40.09.011	larger Heavy duty rubber dock hoses, flanged, ANS	Free	Free			180		30/9/83
	150, electrically bonded FTP 225, PSI, smooth bore, sizes 50.8 mm (2 in.) I.D.,	·						, '
	152.4 mm (6 in.) I.D. and 254.00 mm (10 in.)							
40.09.011	High pressure booster hose, 19.05 mm or 25.4 mm (\frac{1}{4} in. or 1 in.) tested to 6890 kPa (1000 p.s.i.), peculiar to use with pumps incor-	Free	Free		• •	180		30/9/83
40.09.011	porated in fire fighting appliances High pressure water jetting hose, with couplings, 12.7 mm (½ in.) 25.4 mm (1 in.) nominal bore 8268 kPa (1200 p.s.i.)	Free	Free			180		30/9/83
40.09.011	Hose reinforced with cords of high tensile steel wire, with bursting pressure from 6.89 MPa upwards	Free	Free		••	180		30/9/83
40.09.011	Hydraulic brake hose (excluding fittings), to SAE J1401 specification	Free	Free		••	180		30/9/83
40.09.011	Hydraulic hose, reinforced with wire braid, but not including such hose in lengths with fittings attached	Free	Free		•••	180		30/9/83
40.09.011	Radiator hose, moulded or shaped, convoluted or corrugated, when declared for use in the repair of motor vehicles	Free	Free	The management of the second o	•••	180		30/9/83
40.09.011	Rubber delivery hose of 5 cm, 7.5 cm, 10 cm, 12.5 cm (or 2 in., 3 in., 4 in., 5 in.) internal diameter, for delivery of ready-mixed concrete	Free	Free			180	· .	30/9/83
40.09.011	Squeeze Crete pump tubes	Free	Free		••	180		30/9/83
40.09.011	Steam cleaner hose, (excluding fittings) Gates 12B	Free	Free		••	180		30/9/83
40.09.021	Hose, flameproof, flexible, with fittings attached, conforming to N.Z.S.S. 379 or other approved specifications under N.Z. Electrical Wiring Regulations 1961	Free	Free		••	180		30/9/83
40.09.021	Lined hose: Thiokol	Free	Free			180		30/9/83
40.09.021	Neoprene seamless tubing, OSC and OSK grades, in lengths of less than 304.8 m (1,000 ft)	Free	Free			180		30/9/83
40.09.021	Tubing, translucent, surgical, for pressure drainage, transfusion, and stethoscopic pur-	Free	Free		••	180		30/9/83
	poses, and conforming to British Standard Specification No. 1881/1966						16.	