

## Tariff Notice No. 1976/25—Applications for Approval

NOTICE is hereby given that applications have been made to the Minister of Customs for concessionary entry of the following goods at the rates of Customs duty shown:

Appn. No.	Tariff Item	Goods	Rates of Duty			Part II Ref.
			Normal	B.P.	Other Pref.	
32271	15.10.101	VRO fatty acid, used in the manufacture of synthetic resins ..	Free*	Free*		..
32153	27.10.909	Visconorust 2090 PD corrosion preventive grease ..	Free*	Free*	Free*	10.2
32269	29.16.098	Sunarome WMO 2-ethyl-N-hexyl salicylate, used as an oil soluble sunscreen agent	Free*	Free*	Free*	10.8
32135	34.02.000	Hodag PX93 (antifoam) ..	Free*	Free*	Free*	10.8
32286	34.02.000	Surfynol 61, used as a surfactant in the manufacture of paint ..	Free*	Free*	Free*	10.8
32258	35.06.001	Bondmaster 86-2019, a synthetic rubber resin glue which is a tacky, fast drying, liquid adhesive, especially developed for the bonding of polythene sheeting to itself in soil fumigation and mulching applications	Free	Free		..
32189	38.19.298	Carapor paste R, a flame retardant additive for rigid urethane foam	Free*	Free*	Free*	10.8
32285	38.19.298	Fluid base 58 DOT 3, inhibitor concentrate F, used in the manufacture of brake fluids	Free*	Free*	Free*	10.8
32270	38.19.298	Manalox 30A, used as a gellant in the manufacture of synthetic resins	Free*	Free*	Free*	10.8
32215	39.01.012	Embossing powder, used in the printing industry to manufacture Christmas and greeting cards and wedding invitations	Free*	Free*		..
32154	39.01.012	Meldam MP 221, water soluble melamine formaldehyde powder, used in the manufacture of decorative laminates	Free*	Free*		..
32272	39.01.012	Pentalyn 860, 450, used in the manufacture of printing inks ..	Free*	Free*		..
32283	39.01.022	Cyanaprene A8, a liquid urethane rubber, used for custom mould products made for industrial use under conditions of high wear and stress	Free*	Free*		..
32139	39.01.022	Paraplex RG-2, used in making synthetic resin for coatings	Free*	Free*		..
32284	39.01.022	Solithane 291, a liquid urethane rubber, used for custom moulded products made for industrial use under conditions of high wear and stress	Free*	Free*		..
32273	39.02.131	Acrilgraph acrylic sheet, being cast polymethyl methacrylate sheets incorporating decorative motifs, signstyle, etc., during polymerisation	Free	Free	Aul Free	..
32182	39.07.396	I.D. Williamson thinsulators, a high density polyethylene injection mould product, used when pipelines have to be put inside a steel casing usually under roads and railway lines	Free*	Free*	Free*	10.2
31783	39.07.396	Tyrap harnessing system of cable ties and clamps, used for harnessing, tying, clamping and identifying electrical and electronic wire bundles in multi-wire systems	Free*	Free*	Free*	10.8
32121	40.10.005	Co-link vee section transmission belting, constructed of vulcanised rubber links joined by metal rivets, used for transmission drives when endless V belts cannot be used	Free*	Free*		..
32101	40.14.049	Oil hydraulic wiper seals, for the manufacture of oil hydraulic cylinders	Free*	Free*	Free*	10.2
32180	40.14.069	I.D. Williamson U and Z type casing seals, used to cap off the ends of a carrying pipe and casing pipe of	Free*	Free*	Free*	10.2
32239	50.04.009	Yarns of man-made fibres (discontinuous), not bulked, stretched or texturised, not put up for retail sale, and weighing approximately 225 grams per 9000 metres, Polyester/Silk (80%/20%)	Free*	Free*	Free*	10.8
32235	51.01.109	Yarn of man-made fibre (continuous), not bulked, stretched or texturised, weighing 900 grams per 9000 metres, Bouclette boutonne 64% triacetate, 18% polyester, 18% polyamide	Free*	Free*	Free*	10.8
32240	56.05.009	Yarns of man-made fibres (discontinuous), not bulked, stretched or texturised, not put up for retail sale, and weight approximately 225 grams per 9000 metres, Polyester/Cotton (88%/12%), Polyester/Polyacrylic/Viscose/Silk. (50%/38%/4%/8%) (Dolan Tweed) Polyester/Flax (75%/25%)	Free*	Free*	Free*	10.8
32236	56.05.012	Yarns of man-made fibre (discontinuous) containing fine animal hair and weighing approximately 240 grams per 9000 metres 70% dralon/30% mohair	Free*	Free*	Free*	10.8
32237	56.05.014	Yarn of man-made fibre (discontinuous) not bulked, stretched or texturised, weighing approximately 235 grams per 9000 metres, 85% Acrylic/15% Viscose	Free*	Free*	Free*	10.8
32238	56.05.019	Polyester/Linen (72%/28%) spun knitting fibre, weighing approximately 118 grams per 9000 metres	Free*	Free*	Free*	10.8
32112	73.11.119	Hot-rolled steel H and Z sections, less than 80 mm, used in the manufacture of steel window frames	Free*	Free*	Free*	10.2
32164	73.13.449	Tinfree steel, used for the local manufacture of 20 litre small lithographed pails	Free*	Free*	Free*	10.8
31262	73.40.497	Tile racks and parts thereof, for use with automatic concrete roof tile machines	Free*	Free*	Free*	10.2
32155	74.04.031	Copper sheets, used for making hot water cylinders, copper supply tanks and flushing cisterns	Free*	Free*	Free*	10.8
32183	74.04.039	Silver bearing copper strips, in coil, used in the manufacture of tractor, truck and car radiators	Free*	Free*	Free*	10.2
32163	83.02.099	Adjustable metal stays, to be used in making adjustable beds specially for invalids or hospital use	Free*	Free*	Free*	10.2
32126	84.17.101	Low temperature refrigerated incubator, used for the incubation of laboratory cultures	Free*	Free*	Free*	10.2
32265	84.17.128	Industrial fluidised bath, for cleaning of tools and dies and machine parts from plastic residue	Free*	Free*	Free*	10.2