

Tariff Notice No. 1976/65—Applications for Variation of Approval

NOTICE is hereby given that applications have been made for variation of a current approval of the Minister of Customs as follows:

Appn. No.	Tariff Item	Goods	Rates of Duty			Part II Ref.	List No.	Effective	
			Normal	B.P.	Other Pref.			From	To
	84.61	CURRENT APPROVAL: Cocks and valves: Excluding: (6) Valves, ball: (a) Screwed, stainless steel and cast carbon steel bodies, 9.52 mm ($\frac{3}{8}$ in.) to 50.8 mm (2 in.) B.S.P. (other than multiport and jacketed types) (b) Screwed, brass or bronze, sizes 12.7 mm ($\frac{1}{2}$ in.), 19.05 mm ($\frac{3}{4}$ in.) and 25.4 mm (1 in.) B.S.P. (c) Flanged, cast stainless steel, or cast steel, sizes 50.8 mm (2 in.), 76.2 mm (3 in.), 101.6 mm (4 in.), 152.4 mm (6 in.), tested fire safe	Free	Free	Free	10.2			
34323	84.61	REQUESTED APPROVAL: Cocks and valves: Excluding: (6) Valves, ball: (a) Screwed, stainless steel and cast carbon steel bodies 10 mm ($\frac{3}{8}$ in.) to 50 mm (2 in.) B.S.P. (other than multiport and jacketed types) (b) Screwed, brass or bronze, sizes 15 mm ($\frac{1}{2}$ in.), 20 mm ($\frac{3}{4}$ in.) and 25 mm (1 in.) B.S.P. (c) Screwed, cast iron, sizes 15 mm ($\frac{1}{2}$ in.), 20 mm ($\frac{3}{4}$ in.), 25 mm (1 in.), 32 mm ($1\frac{1}{4}$ in.), 40 mm ($1\frac{1}{2}$ in.), 50 mm (2 in.) (d) Flanged, cast stainless steel or cast steel, sizes 50 mm (2 in.), 80 mm (3 in.), 100 mm (4 in.), 150 mm (6 in.), tested fire safe					141	1/7/74	..
	84.61	CURRENT APPROVAL: Cocks and valves: Excluding: (25) Butterfly valves of cast iron, with rubber liners and suitable for working pressures up to 1378 kPa (200 p.s.i.): wrench operated: 50.8 mm (2 in.), 63.5 mm ($2\frac{1}{2}$ in.), 76.2 mm (3 in.), 101.6 mm (4 in.), 152.4 mm (6 in.) gear operated: 50.8 mm (2 in.), 76.2 mm (3 in.), 101.6 mm (4 in.), 152.4 mm (6 in.) pneumatically operated: 50.8 mm (2 in.), 63.5 mm ($2\frac{1}{2}$ in.), 76.2 mm (3 in.), 101.6 mm (4 in.)	Free	Free	Free	10.2			
34324	84.61	REQUESTED APPROVAL: Cocks and valves: Excluding: (25) Butterfly valves of cast iron, with rubber liners and suitable for working pressures up to 1378 kPa (200 p.s.i.): wrench operated: 50.8 mm (2 in.), 63.5 mm ($2\frac{1}{2}$ in.), 76.2 mm (3 in.), 101.6 mm (4 in.), 152.4 mm (6 in.), 200 mm (8 in.) gear operated: 50.8 mm (2 in.), 76.2 mm (3 in.), 101.6 mm (4 in.), 152.4 mm (6 in.), 200 mm (8 in.) pneumatically operated: 50.8 mm (2 in.), 63.5 mm ($2\frac{1}{2}$ in.), 76.2 mm (3 in.), 101.6 mm (4 in.)					126	1/7/74	..