

Tariff Notice No. 1976/106—Applications for Variation of Approvals

NOTICE is hereby given that applications have been made for variation of current approvals of the Minister of Customs as follows:

Appn. No.	Tariff Item	Goods	Rates of Duty			Part II Ref.	List No.	Effective	
			Normal	B.P.	Other Pref.			From	To
33010	34.02.000	CURRENT APPROVAL: Products, as may be approved, when imported in bulk and not being soaps or containing soap: Approved: Texapon K12	Free	Free	Free	10.8	113		
	34.02.000	REQUESTED APPROVAL: Products, as may be approved, when imported in bulk and not being soaps or containing soap: Approved: Texapon K12, when declared for use only in: (i) medicaments, toothpastes, denturifices (ii) animal remedy preparations (iii) cattle bloat preventative preparations (iv) pharmaceuticals						1/8/75	30/9/82
36123	60.05.159	CURRENT APPROVAL: Welt edging collars of P.V.C. coated textiles	Free	Free	Free	10.8	..	1/7/74	31/10/76
	60.05.159	REQUESTED APPROVAL: Edging collars of P.V.C. coated fabrics							
36287	84.63.049	CURRENT APPROVAL: Gears, reduction (EXCLUDING co-axial gears, designed for input 0.37 to 7.46 kW (0.5 to 10 h.p.) with output r.p.m. from 12.611): (i) With two or more reductions: EXCLUDING: (a) Worm types (b) Single, helical double reduction shaft mounted types (c) Spur and helical parallel axis reduction boxes designed for 0.37 to 3.73 kW (0.5 to 5 h.p.) (ii) Single helical types for transmitting powers exceeding 14.91 kW (20 h.p.): EXCLUDING: (a) Double reduction shaft mounted types (iii) Double helical types (iv) Worm types, in which the shortest distance between the axis of the input and output shafts exceeds 20.95 cm (8.25 in.)	Free	Free	Free	10.2	63	1/7/74	30/6/77
		REQUESTED APPROVAL: Gears, reduction (EXCLUDING co-axial gears, designed for input 0.37 to 7.46 kW (0.5 to 10 h.p.) with output r.p.m. from 12.611 and excluding all types of epitrochoid, heliocentric and epicyclic speed reducers upto and including 40 kW): (i) With two or more reductions: EXCLUDING: (a) Worm types (b) Single, helical, double reduction shaft mounted types (c) Spur and helical parallel axis reduction boxes designed for 0.37 to 3.73 kW (0.5 to 5 h.p.)						1/7/74	30/6/77
								1/7/74	30/6/77
								1/7/74	30/6/77