Per Tonne

Price Order No. 51 (Steel Products Manufactured by Pacific Steel Ltd.)

Pursuant to the Commerce Act 1975, I, Peter Edward Donovan, pursuant to a delegation from the Secretary of Trade and Industry, hereby make the following price order:

PRELIMINARY

- 1. This order may be cited as Price Order No. 51 and shall come into force on the 25th day of March 1977.
 - 2. (1) Price Order No. 42 is hereby revoked.
- (2) The revocation of the said order shall not affect the liability of any person for any offence in relation thereto committed before the coming into force of this order.
 - 3. In this order:

The expression "f.o.r." means "free on rail", and the expression "c and f" means "cost and freight".

APPLICATION OF THIS ORDER

4. This order applies to the following steel products manu factured by Pacific Steel Ltd.:

Rolled and Revolled Steel Bars

- 1. Rounds
- Squares
 Flats
- Angics 5. Channels

MAXIMUM PRICES TO BE CHARGED

- 5. (1) The maximum factory selling prices that may be charged or received by Pacific Steel Ltd. for any steel products to which this order applies shall be the basis price shown in this order, with adjustments in the form of extras as specified hereunder being made as appropriate.
- (2) The maximum prices, as aforesaid, are fixed for deliveries as follows:
 - (a) Within a radius of 40 kilometres of Otahuhu, free on truck
 - (a) Within a radius of 40 knowledges of Orandru, free of duck at mill.
 (b) "f.o.r." Whangarei, Hamilton, Rotorua, Tauranga, Gisborne, Napier, Hastings, Palmerston North, New Plymouth, Wanganui, Masterton, Lower Hutt, Wellington Blenheim, Christchurch, and Invercargill.
 (c) Landed on wharf or at railhead at Lyttelton, Timaru, Oamaru, Nelson, Greymouth, Dunedin, and Bluff.
 (d) For sales to other areas the approved maximum selling.

 - (d) For sales to other areas, the approved maximum selling prices may be surcharged with the amount which does not exceed the actual freight incurred for transport of steel from the nearest freight paid point mentioned above.
- (3) The maximum basis price shall be \$312.25 per tonne, and shall apply to mild steel concrete reinforcing bars made in conformity with New Zealand Standard 3402 P: 1973, angles, channels, flats, squares, and rounds other than reinforcing made in conformity with British Standard 4360: Grades 43A, 43A. 1.
 - (4) The basis price shall cover the following sizes:

Rounds 20 mm diameter and over

Squares 12 mm to 75 mm

Flats All shapes and sizes not included in 6 (1)

Angles below.

(N.B. The company is not making basis size channels— $203 \text{ mm} \times 76 \text{ mm} \times 24 \text{ kg/m}$ and over.)

- (5) The basis price shall cover lengths from 5 m to 10 m.
- (6) The basis price shall cover the following quantities:

Rounds, 4 tonnes and over Squares, 4 tonnes and over In one size and thickness or Flats, 4 tonnes and over diameter and in one quality

Angles, 4 tonnes and over

(7) The basis price shall cover the cold straightening of angles.

EXTRAS

6. The maximum charges for extras as appropriate are as follows:

(1) Size (ad	ded to	Basis Pric	ce)					
Rounds— Reinforcing and engineering:						Per Tonne		
						\$ c		
6.5 mm	• •		• •		••	10 75		
10 mm	• •	• •	• •	. •		8 00		
12 mm	• •	• •	• •		• •	4 00		
16 mm	• •	• •	• •	• •	• •	1 00		
Squares, 10 mm		••	••	••	••	3 50		

	\$ c
Flats—	J . C
25 mm × 5 mm	7 00
25 mm × 6 mm	5 00
25 mm × 8 mm	5 00
25 mm × 10 mm	4 00
25 mm × 11 mm	4 00
25 mm × 12 mm	4 00
30 mm × 5 mm	7 00
30 mm × 6 mm	5 00
30 mm × 8 mm	5 00
30 mm × 10 mm	4 00
30 mm × 11 mm	4 00
40 mm × 5 mm	6 00
40 mm × 6 mm	4 00
40 mm × 8 mm	4 00
40 mm × 10 mm	4 00
40 mm × 11 mm	4 00
40 mm × 12 mm	2 00
50 mm × 6 mm	4 00
50 mm × 8 mm	4 00
50 mm × 10 mm	2 00
50 mm × 11 mm	2 00
60 mm × 6 mm	4 00
60 mm × 8 mm	4 00
60 mm × 10 mm	2 00
80 mm × 6 mm	3 00
80 mm × 8 mm	3 00
100 mm × 6 mm	3 00
100 mm × 8 mm	3 00
100 mm × 10 mm	1 00
100 mm × 12 mm	1 00
Angles—	
25 mm × 25 mm × 5 mm	10 00
25 mm × 25 mm × 6 mm	8 00
30 mm × 30 mm × 5 mm	7 00
30 mm × 30 mm × 6 mm	6 00
$40 \text{ mm} \times 40 \text{ mm} \times 5 \text{ mm} \dots \dots \dots$	4 00
$40 \text{ mm} \times 40 \text{ mm} \times 6 \text{ mm} \dots \dots \dots$	2 00
50 mm × 50 mm × 5 mm	2 00
Channels—	
$76 \text{ mm} \times 38 \text{ mm} \times 6.5 \text{ kg/m} \dots$	8 00
$102 \text{ mm} \times 51 \text{ mm} \times 10.0 \text{ kg/m} \dots$	6 00
$127 \text{ mm} \times 64 \text{ mm} \times 15.0 \text{ kg/m} \qquad \dots$	3 00
$152 \text{ mm} \times 76 \text{ mm} \times 18.0 \text{ kg/m} \qquad \dots$	3 00
Each of the following extras may be added to bas	
anneonriata siza avtras	4 4 7

Per Tonne (2) Quantity
For products bundled in 1 Tonne Lifts \$ c 1 tonne to under 2 tonnes 6 00 2 tonnes to under 3 tonnes 3 tonnes to under 4 tonnes 4 00 Minimum order 1 tonne For products bundled in 2 Tonne Lifts 2 tonnes to under 4 tonnes ...

appropriate size extras.

The above quantity extras apply to items of one size, quality, and length.
Where quantities under 10 tonnes of an item incur any extra

freight, cartage, or other charges, such charges are to customer's account.

(3) Length		Per	S c
Over 10 m to 12 m			1 00
Over 12 m to 15 m			
(4) Cold Straightening			
Flats only	• •	 	1 00
(5) Deformed Bars		 	4 00
(6) Bar marking grade 380 a	 	4 50	
(7) Quality			

This section includes quality extras added to basis price, plus any extras added under 6 (1, 2, 3, 4, and 5) above.

Standard Specifications

Specification	Analysis	Per Tonne Extra
NZS 3402P	Grade 275 Deformed Sulphur .06 max. Phosphorus .06 max.	
NZS 3402P: Mild Medium Ten- sile 500/580 MPa	Grade 275 Plain Sulphur .06 max. Phosphorus .06 max. Sulphur .06 max. Phosphorus .06 max.	. Basis price
High Tensile 570/660 MP: BS 4360 NZS 3402P	Sulphur .06 max. Phosphorus .06 max. Sulphur .06 max. Phosphorus .06 max. Crade 380 High Yield Steel	. 1 50