

Tariff Notice No. 1977/75—Application for Variation of Determination

NOTICE is hereby given that an application has been made for variation of a current determination of the Minister of Customs as follows:

Appn. No.	Tariff Item	Goods	Rates of Duty			Part II Ref	List No.	Effective	
			Normal	B.P.	Other Pref.			From	To
82.05.021 Deter'n	CURRENT DETERMINATION:	(1) Drills: 1975	45%	33%	Aul Free Can 25% CPC 25%	..	131	12/3/76	..
		Jobbers, standard 1976	45%	37%					
		Helix type 1977	45%	45%					
		only, right hand 3/64 in. to 1/2 in., 1.00 mm to 13.00 mm							
		Straight Shank Stub, standard							
		Helix type, right hand, 3/64 in. to 1/2 in.							
		Long Series, standard Helix type, right hand, 3/64 in. to 1/2 in.							
		Straight Shank Long Series, Long Reach, HSS, 1/4 in. to 1/2 in.							
		Blacksmith or HSS Twist, with 12.7 mm shank, 33/64 in. 1 1/2 in. (excluding 64th's in sizes other than 33/64 in.)							
		Reduced Shank, HSS (metal and woodworking), 6.00 mm to 13.00 mm							
		Masonry:							
Rotary 3.00 mm to 25.50 mm impact 3.00 mm to 25.50 mm									
Twist Drill Sets, 1.00 mm to 13.00 mm, 1/8 in. to 1/2 in.									
(2) Countersinks, single flute:									
1/4 in. shank 9.52 mm to 19.05 mm									
1/2 in. shank 15.88 mm to 19.05 mm									
(3) Reamers, Parallel Machine, Tungsten Carbide tipped, non-adjustable:									
straight shank, all sizes under 14.29 mm morse taper shank all sizes over 14.29 mm									
(4) Router Bits-HSS-Tungsten Carbide tipped									
(5) Milling Cutters:									
Tungsten Carbide tipped Twist, from 2.381 mm									
Tungsten Carbide tipped, circular, other than throw away tip type									
(6) Facing Cutters, Tungsten Carbide tipped, circular, other than throw away tip type									
(7) Profile and Cutter Heads, Tungsten Carbide and HSS Tipped Round Section - Super Cobalt									
(8) Tool bits, HSS:									
Square Section—Special Cobalt-Super-Cobalt									
Bevel Section—Special Cobalt									
Round Section—Super Cobalt									
(9) Lathe Tools (brazed on tips), Tungsten Carbide Tipped, standard pattern									
(10) Knives—Tungsten Carbide tipped—steel									
(11) Taps, carbon steel cut thread, right hand, in the following sizes:									
B.S.W. 1/8 in. to 1 in. (excluding 3/32 in., 1/16 in., 1/8 in., 1/4 in.)									
U.N.F. 1/16 in. to 1 in. (excluding 1/32 in., 1/16 in.)									
I.S.O. Coarse 3 mm, × 0.50 mm, 4 mm × 0.70 mm, 5 mm × 0.80 mm, 6 mm × 1.00 mm, 8 mm × 1.25 mm, 10 mm × 1.50 mm, 12 mm × 1.75 mm, 16 mm × 2.00 mm, 20 mm × 2.50 mm, 24 mm × 3.00 mm									