

Tariff Notice No. 1977/75—Applications for Variation of Determination—continued

Appn. No.	Tariff Item	Goods	Rates of Duty			Part II Ref.	List No.	Effective	
			Normal	B.P.	Other Pref.			From	To
42125	82.05.021 Deter'n cont'd	<p><b>CURRENT DETERMINATION—cont'd</b></p> <p>(12) Button Dies, Carbon Steel, Circular split, 1 in. or 2 in. outside diameter, right hand, in the following sizes:                      B.S.W. <math>\frac{1}{8}</math> in. to 1 in.                      U.N.F. <math>\frac{3}{16}</math> in. to 1 in.                      I.S.O. Coarse 3.00 mm × 0.50 mm to 24.00 mm × 3.00 mm</p> <p>(13) Die nuts, Hexagon, Carbon Steel right hand, in the following sizes:                      B.S.W. <math>\frac{3}{16}</math> in., <math>\frac{1}{4}</math> in., <math>\frac{5}{16}</math> in., <math>\frac{3}{8}</math> in., <math>\frac{7}{16}</math> in., <math>\frac{1}{2}</math> in., <math>\frac{9}{16}</math> in., <math>\frac{5}{8}</math> in., 1 in.                      U.N.F. <math>\frac{3}{16}</math> in., <math>\frac{1}{4}</math> in., <math>\frac{5}{16}</math> in., <math>\frac{3}{8}</math> in., <math>\frac{7}{16}</math> in., <math>\frac{1}{2}</math> in., <math>\frac{9}{16}</math> in., <math>\frac{5}{8}</math> in., 1 in.                      I.S.O. Coarse 3 mm × 0.50 mm, 4 mm × 0.70 mm, 5 mm × 0.80 mm, 6 mm × 1.00 mm, 8 mm × 1.25 mm, 10 mm × 1.50 mm, 12 mm × 1.75 mm, 16 mm × 2.00 mm, 20 mm × 2.50 mm, 24 mm × 3.00 mm</p>					131	12/3/75	..
42125	82.05.021 Deter'n	<p><b>REQUESTED DETERMINATION:</b></p> <p>(1) Drills: 1976                      HSS and Carbon/ 1977                      Chrome/Vanadium steels, straight shank Jobber length standard Helix right hand:                      1.00 mm to 13.00 mm  <math>\frac{3}{64}</math> in. to <math>\frac{1}{2}</math> in.                      HSS and Carbon/Chrome/Vanadium steels, straight shank double and single ended stub length, standard helix right hand:                      1.00 mm to 13.00 mm  <math>\frac{3}{64}</math> in. to <math>\frac{1}{2}</math> in.                      HSS and Carbon/Chrome/Vanadium steels, straight shank long series length standard helix right hand:                      1.00 mm to 13.00 mm  <math>\frac{3}{64}</math> in. to <math>\frac{1}{2}</math> in.                      HSS and Carbon/Chrome/Vanadium steels, straight shank long reach length standard helix right hand:                      3.00 mm to 13.00 mm  <math>\frac{1}{8}</math> in. to <math>\frac{1}{2}</math> in.                      Tungsten carbide tipped twist from:                      2.381 mm                      HSS and Carbon/Chrome/Vanadium steels, reduced shank of any diameter including (Blacksmith type) standard helix right hand:                      13.00 mm to 32.00 mm  <math>\frac{33}{64}</math> in. to <math>1\frac{1}{4}</math> in.                      HSS and Carbon/Chrome/Vanadium steels, reduced shank of any diameter (metal and woodworking) with standard or dowelling bit points, right hand:                      6.00 mm to 13.00 mm  <math>\frac{1}{4}</math> in. to <math>\frac{1}{2}</math> in.                      HSS and Carbon/Chrome/Vanadium steels, straight shank (4 flute core type) right hand:                      3.00 mm to 13.00 mm  <math>\frac{1}{8}</math> in. to <math>\frac{1}{2}</math> in.                      Drill sets, containing above type drills in diameter ranges:</p>	45% 45%	37% 45%	Aul Free Can 25% CPC 25%				