

TARIFF DECISION LIST No. 218—continued
APPROVALS—continued

Tariff Item No.	Goods	Rates of Duty		Part II Ref.	List No.	Effective	
		Normal	Other Pref.			From	To*
84.59.148	Hose reels, self-winding, peculiar to use with self-servicing equipment and in the refuelling of light aircraft	Free	Free	10.2	218	1/4/77	30/9/80
84.59.148	Industrial safety belt anchors and rewind drums	Free	Free	10.2	218	1/7/77	30/9/83
84.61.019	Valves of ductile iron, peculiar to use in l.p.g. and ammonia systems, as may be approved:	Free	Free	10.2			
	Approved:						
	Bypass valves, screwed 19.05 mm ($\frac{3}{4}$ in.), 25.4 mm (1 in.) and 38.1 mm ($1\frac{1}{2}$ in.)				218	1/3/77	30/9/83
	Bypass valves, flanged, 34.925 mm ($1\frac{1}{4}$ in.), 38.1 mm ($1\frac{1}{2}$ in.), 50.8 mm (2 in.) and 63.5 mm ($2\frac{1}{2}$ in.)				218	1/3/77	30/9/83
	Sight flow glass/horizontal check valves:				218	1/3/77	30/9/83
	Screwed 38.1 mm ($1\frac{1}{2}$ in.), Flanged 38.1 mm ($1\frac{1}{2}$ in.), 50.8 mm (2 in.), 76.2 mm (3 in.) and 101.6 mm (4 in.)						
85.01.051	C 15 Battery chargers for use with Oticon auditory training equipment	Free	Free	10.2	218	1/5/77	30/6/84
85.17.009	Stone-Chance Type ZP20 "Seagull" flashing marine navigation beacon	Free	Free	10.2	218	1/1/77	31/12/80
85.19.059	Allen-Bradley limit switches, bulletins:	Free	Free	10.2			
	801				218	1/4/77	31/3/84
	802				218	1/4/77	31/3/84
	802G				218	1/4/77	31/3/84
	802R				218	1/4/77	31/3/84
	802T				218	1/4/77	31/3/84
	802X				218	1/4/77	31/3/84
	802XR				218	1/4/77	31/3/84
	803				218	1/4/77	31/3/84
	803M				218	1/4/77	31/3/84
85.19.059	ASEA mechanically latched-in contactors	Free	Free	10.2	218	1/7/77	30/6/79
85.19.059	ASEA plug-in contactors	Free	Free	10.2	218	1/7/77	30/6/79
85.19.059	Crabtree limit switches, dust tight and splash proof	Free	Free	10.2	218	1/4/77	31/3/80
85.19.059	Pole mounted reclosers, 11,000 volts	Free	Free	10.2	218	1/7/74	30/6/80
85.19.059	Reed and miniature relays:	Free	Free	10.2			
	Miniature, low power relays of either vacuum reed or open contact construction, maximum of 8 contacts per relay, contact rating 0.05 to 5 amp, 50 to 1000 volts, coil voltage 5 to 60 volts, coil voltage 0.02 to 5 watt				218	1/6/77	30/6/84
85.19.059	Series M539 electronic reactive power control units	Free	Free	10.2	218	1/7/77	30/6/79
85.19.059	Series R terminal bases and/or connectors	Free	Free	10.2	218	1/7/77	30/6/79
85.19.059	Series RXM auxiliary relays	Free	Free	10.2	218	1/7/77	30/6/79
85.19.059	Spare parts (excluding parts of general use) for ASEA contactors only	Free	Free	10.2	218	1/7/77	30/6/79
85.19.059	Thermal overload relays	Free	Free	10.2	218	1/7/77	30/6/79
85.19.072	NX current limiting (H.R.C.) fuse links 15.5 kV	Free	Free	10.2	218	1/4/77	30/9/84
85.19.099	M.T.L. shunt-diode safety barriers	Free	Free	10.2	218	1/5/77	30/6/84
85.23	Wires and cables, excluding winding wires and strip, insulated with:	Free	Free	10.2			
	Cotton, silk, rayon, glass, enamel, or any combination of these materials with asbestos and whether or not varnished				218	1/7/74	30/6/84
	Mineral				218	1/7/74	30/6/84
	Polytetrafluoroethylene (P.T.F.E.)				218	1/7/74	30/6/84
85.23.081	Telcon 61RG1/01, 1 x 16/.005 hard brass bunched wire with PVC insulation	Free			218	1/4/77	30/6/80
85.26.000	Amber mica pieces	Free	Free	10.8	218	1/5/77	30/6/80
87.06.059	Wheel base rims and spacers when declared:	Free	Free	10.8	218	1/12/74	30/9/81
	(1) by a manufacturer for use by him only in making trailer axle assemblies, or;						
	(2) by an importer that they will be sold by him to a manufacturer for use by him only in making trailer axle assemblies						