Januari (j. 1818-1818), zeman engi na minanakari kasasa yang menantu.	Per Tonne	Standard Specifications	
	\$ c	Specification Analysis	Per Tonne Extra
60 mm × 8 mm	4 00	NZS 3402P Grade 275 Deformed Sulphur .06	\$ C
60 mm × 10 mm	3 00	max. Phosphorus .06 max	
80 mm × 6 mm	3 00	NZS 3402P: Grade 275 Plain Sulphur .06 max.	
100 mm × 6 mm	3 00	Mild Phosphorus .06 max	Basis Price
100 mm × 8 mm	3 00	Medium Ten-Sulphur .06 max. Phosphorus .06	1 50
100 mm × 10 mm	1 00	sile 500/580 max MPa	1 30
100 mm × 12 mm	1 00	High Tensile Sulphur .06 max, Phosphorus .06	
Angles	10 00	570/660 MPa max	1 50
25 mm × 25 mm × 5 mm 25 mm × 25 mm × 6 mm	8 00	BS 4360 Sulphur .06 max. Phosphorus .06	
30 mm × 30 mm × 5 mm	7 00	max. NZS 3402P Grade 380 High Yield Steel	Basis Price 8 75
30 mm × 30 mm × 6 mm	6 00	NZS 3402P Grade 380 High Yield Steel	Per Tonne Extra
$40 \text{ mm} \times 40 \text{ mm} \times 5 \text{ mm} \dots$	4 00	(8) Tests	S c
40 mm × 40 mm × 6 mm	2 00	Covernment inspection	1 00
50 mm × 50 mm × 5 mm	2 00	To Lloyds, etc.	1 50
Channels—	8 00	By buyer at supplier's works	8 00
$76 \text{ mm} \times 38 \text{ mm} \times 6.5 \text{ kg/m} \dots$	C 00		lump sum per
102 mm × 51 mm × 10.0 kg/m 127 mm × 64 mm × 15.0 kg/m	3 00		test or set of
$152 \text{ mm} \times 76 \text{ mm} \times 13.0 \text{ kg/m} \qquad \dots$	3 00		tests or 20c
Each of the following extras may be added to	hasis price plus		per tonne whichever is
appropriate size extras.			the greater
(2) Quantity	Per Tonne	Surface inspection	2 00
For products bundled in 1 Tonne Lifts	\$ c	Proof stress	3 00 3 00
1 tonne to under 2 tonnes	4 00	Additional chemical analysis	3 50
2 tonnes to under 3 tonnes 3 tonnes to under 4 tonnes	200	Brinnell on not less than 10 percent of the bars	7 50
Minimum order 1 tonne	200	Inspection or testing of lots less than 1 tonne	75
For products bundled in 2 Tonne Lifts			lump sum per
2 tonnes to under 4 tonnes	4 00		test
The above quantity extras apply to items of one s	ize, quality, and	. The state of $oldsymbol{I}$	Per Tonne Extra
length.			\$ c
Where quantities under 10 tonnes of an item incur any extra freight, cartage, or other charges, such charges are to customer's		Where test certificates are called for giving mechanical properties covering any of the numerical	
	re to customer s	series of steels	1 00
account.	Per Tonne	(9) Special Paint Marking or Hand Stamping	1 00
(3) Length	\$ c		1 00
Over 10 m to 12 m	1 00	(10) Cutting Margin	•
Over 12 m to 15 m	1 50	The standard cutting margin is $-0 +$	50 mm and
(4) Cold Straightening		is covered in the basis price.	
Flats only	1 00	(11) Extras for exact lengths are by arrangement and seller.	it between buyer
(5) Deformed Bars	4 00		
(6) Bar marking grade 380 deformed	4 30	(12) Deduction for steel rod supplied in coils \$1	
(7) Quality This section includes quality extres added to		Dated at Wellington this 29th day of November 1978.	
This section includes quality extras added to basis price, plus any extras added under 6 (1, 2,		P. E. DONOVAN	
3, 4, and 5) above.	- 1-1-1	Director, Stabilisation of Price	es and Research.
-, ·, ·································		*Gazette, No. 69, 10 August 1978, p.	

Standard Grade for the Export of Potatoes Notice 1978 (Notice No. 2048, Ag. 12/15/1/4)

PURSUANT to regulation 13 of the New Zealand Grown Fruit and Vegetables Regulations 1975, the Director-General of Agriculture and Fisheries hereby gives notice that the standard grade for the export of potatoes shall be as set out in this

NOTICE

1. Short title and commencement—(1) This notice may be cited as the Standard Grade for the Export of Potatoes Notice 1978.

(2) This notice shall come into force on the day after the date of its notification in the New Zealand Gazette.

2. Application of notice (1) This notice determines the standard grade applicable for the export of tubers grown from cultivars of the potato plant (Solanum tuberosum) and, subject to subclause (2) of this clause, shall be the minimum grade standard for potatoes exported from New Zealand to be supplied in their natural state to consumers.

(2) The sizing requirements as set out in 6 shall not apply to potatoes exported from New Zealand to those countries listed in the First Schedule to this notice.

3. Interpretation—(1) Unless the context otherwise requires, terms used in this notice shall have the same meaning as in the New Zealand Grown Fruit and Vegetable Regulations 1975*.

(2) Definitions contained in those regulations applicable to potatoes are set out in the Second Schedule to this notice.

*S.R. 1975/57

Amendment No. 1: S.R. 1977/5 Amendment No. 2: S.R. 1977/39 Amendment No. 3: S.R. 1977/209

4. Grade Mark—The grade mark assigned to this standard grade shall be Class I (hereinafter referred to as "the grade").

- 5. Quality Requirements—(a) The potatoes must be-
- (i) Intact, whole tubers;

(T. and I.)

- (ii) Sound;
 (iii) Clean;
 (iv) Well formed;
 (v) Free from abnormal external moisture;

(vi) Free from foreign smell or taste.(b) The tubers must be free from greening, storage defects, or any other defects which impair their general appearance or keeping quality.

(c) The tubers must be free from pests, diseases, and contamination with toxic materials.

(d) Skin defects which are not liable to impair the keeping qualities are permitted on each tuber within the limits specified in the Third Schedule to this notice.

6. Size of Export Potatoes—(1) Subject to the tolerance contained in the Third Schedule to this notice, and to subclause (2) of this clause, the minimum size of potatoes for export shall be—

(a) 50 mm; or

(b) the smallest tuber which does not pass through a square, the sides of which are 51 mm in length.

the sides of which are 51 mm in length.