

## TARIFF DECISION LIST No. 263

Decisions of the Minister of Customs Under the Customs Tariff (Subject to Amendment or Cancellation by Notification in the Gazette)  
DETERMINATIONS

Tariff Item No.	Goods	Rates of Duty		Part II Ref.	List No.	Effective	
		Normal	Other Pref.			From	To
60.01.028 } 60.01.029 } Deter'n	Fabrics, unprinted, other than: .. .. .	40% or* 66.14c plus 15% per kg	25% or* 66.14c per kg	..			
	Hyton super covers .. .. .				263	1/12/77	..
	Hyton dampener cover .. .. .				263	1/12/77	..
	Hyton VIP dampener cover .. .. .				263	1/12/77	..
82.05.021 } Deter'n	(1) Drills: .. .. .	45%	Aul Free Can 25% CPC 25%	..			
	(A) HSS and carbon/chrome/vanadium/tungsten steels, right hand helix—				263	1/3/78	..
	(i) Straight shank Jobber length, double and single-ended stub length and long series length 1.00 mm to 13.00 mm ( $\frac{3}{8}$ in. to $\frac{1}{2}$ in.)						
	(ii) Straight shank long reach length 3.00 mm to 13.00 mm ( $\frac{1}{8}$ in. to $\frac{1}{2}$ in.)						
	(iii) Reduced shank of any diameter including Blacksmith type 13.00 mm to 32.00 mm ( $\frac{3}{8}$ in. to $1\frac{1}{4}$ in.)						
	(iv) Reduced shank of any diameter (metal and woodworking) with standard or dowelling bit points 6.00 mm to 13.00 mm ( $\frac{1}{4}$ in. to $\frac{1}{2}$ in.)						
	(v) Straight shank (4 flute core type) 3.00 mm to 13.00 mm ( $\frac{1}{8}$ in. to $\frac{1}{2}$ in.)						
	(B) Tungsten carbide tipped twist from 2.381 mm ..				263	1/3/78	..
	(C) Drill sets, containing above type drills in diameter ranges:				263	1/3/78	..
	Straight shank:						
	1.00 mm to 13.00 mm						
	$\frac{1}{8}$ in. to $\frac{1}{2}$ in.						
	Reduced shank:						
	6.00 mm to 20.00 mm ( $\frac{1}{4}$ in. to $\frac{3}{4}$ in.) ..						
	(D) Tungsten carbide tipped masonry, straight also reduced shank of any shank diameter "short" or "long" overall lengths within diameter range: 3.00 mm to 32.00 mm ( $\frac{1}{8}$ in. to $1\frac{1}{4}$ in.)				263	1/3/78	..
	(E) Countersinks, single flute: .. .. .				263	1/3/78	..
	$\frac{1}{4}$ in. shank 9.52 mm to 19.05 mm						
	$\frac{1}{2}$ in. shank 15.88 mm to 19.05 mm						
	(F) Reamers, Parallel Machine, Tungsten Carbide tipped, non-adjustable, straight shank, all sizes under 14.29 mm Morse taper shank, all sizes over 14.29 mm				263	1/3/78	..
	(G) Router Bits—HSS—Tungsten Carbide tipped ..				263	1/3/78	..
	(H) Milling Cutters: .. .. .				263	1/3/78	..
	Tungsten Carbide tipped, circular, other than throw away tip type						
	(I) Facing Cutters, Tungsten Carbide tipped, circular, other than throw away tip type				263	1/3/78	..
	(J) Profile and Cutter Heads, Tungsten Carbide and HSS tipped, for use with woodworking machines				263	1/3/78	..