

## Tariff Notice No. 1978/121—Applications for Variation of Approval

NOTICE is hereby given that applications have been made for variation of current approvals of the Minister of Customs as follows:

Port	Appn. No.	Tariff Item	Goods	Rates of Duty		Part II Ref.	List No.	Effective	
				Normal	Pref.			From	To
AK	883	39.02.015	CURRENT APPROVAL: Hostaflex VP 150 .. .. .	Free		..	84	1/7/78	30/9/79
		39.02.015	REQUESTED APPROVAL: Hostaflex CM 150 .. .. .						
AK	883	39.02.015	CURRENT APPROVAL: Hostaflex M 133 .. .. .	Free		..	110	1/7/78	30/6/80
		39.02.015	REQUESTED APPROVAL: Hostaflex CM 133 .. .. .						
AK	883	39.02.015	CURRENT APPROVAL: Hostaflex M 131 resin .. .. .	Free		..	39	1/7/78	30/9/79
		39.02.015	REQUESTED APPROVAL: Hostaflex CM 131 .. .. .						
AK	771	68.12.021	CURRENT APPROVAL: Marinite and Colorceram non-combustible thermal insulation	Free	Free	15	223	1/7/78	30/9/84
		68.12.021	REQUESTED APPROVAL: Marimet 45, Marinite and Colorceram non-combustible insulation						
AK	830	73.40.069	CURRENT APPROVAL: Heel stems for reinforcing stiletto heels .. .	Free	Free	99	244	1/7/78	30/9/80
		73.40.069	REQUESTED APPROVAL: Heel stems and top piece pins for reinforcing stiletto heels						
AK	868	84.21.011	CURRENT APPROVAL: Aerograph, air brushes, when declared for use only with A.C.A.-1, 2, 3, compressors	Free	Free	10	165	1/7/78	31/3/83
		84.21.011	REQUESTED APPROVAL: Aerograph, air brushes: (a) when declared for use only with A.C.A.-1, 2, 3, compressors; (b) Aerograph Super 63 models A-504, E-504						
H.O.	48947	84.63.029	CURRENT APPROVAL: Speed reducers, excluding the following: (1) Worm gear reducers: (a) Single reduction, with shaft centres 209.5 mm or less; (b) Multi-reduction, where the final stage worm reduction has shaft centres 209.5 mm or less (2) Speed reducers of all other types with an output torque of 3125 Nm or less rated at 1500 r.p.m. input	Free	Free	10	273	1/7/78	30/6/79
		84.63.029	REQUESTED APPROVAL: Speed reducers, excluding the following: (1) Worm gear reducers: (a) Single reduction, with shaft centres 209.5 mm or less; (b) Multi-reduction, where the final stage worm reduction has shaft centres 209.5 mm or less (2) Speed reducers of all types with an output torque of 10475 Nm or less rated at 1500 r.p.m. input						
AK	285	85.04.001	CURRENT APPROVAL: Accumulators, lead acid, of the following types: (1) Having a capacity of less than 20 ampere hours (at the 10-hour rate of discharge) (2) - (4)	Free		..	192	1/7/78	30/6/80
		85.04.001	REQUESTED APPROVAL: Accumulators, lead acid, of the following types: (1) having a capacity of less than 24 ampere hours (at the 10 hour rate of discharge) (2) - (4)						
		85.11	CURRENT APPROVAL: Machines, electric welding: EXCLUDING: (1) (2) M.I.G. welding machines having a welding output of 200 amps or less at 100% duty cycle; (3) - (4)	Free	Free	10	234	1/7/78	31/3/85