2778

THE NEW ZEALAND GAZETTE

Tariff Notice No. 1978/171—Applications for Approval

NOTICE is hereby given that applications have been made to the Minister of Customs for concessionary entry of the following goods at the rates of Customs Duty shown:

Port	Appn. No.	Tariff Item	Goods	Rates of Duty		– Part – II
				Normal	Pref.	Ref
.0.	50272	21.07.009	Lyophilized homogenised mussel extract in capsule form for health	Free*	Free*	99
.0.	50226	34.02.000	food Aero dip, for use in the removal of rust and carbon deposits from hot	Free*	Free*	1:
.0. .0.	50231 50221	39.07.299 40.09.001	sections of jet engines Plastic fire hose couplings, for coupling fire hoses	Free* Free*	Free*	99
.0.		40.13.001	paper plant Hysol brand drycleaners' gloves to protect operators' hands against	Free*	Free*	99
.0.	50181	40.13.002 ∫ 48.07.049	solvents and other chemicals Recording paper for Koden weather facsimile receivers model FX-750, for recording automatic satellite weather receiving data	Free*	Free*	9
.0. K	50236 1900	48.07.151 51.01.021	White interlining material for use as stiffening in hats	Free* Free*		
.0.	50267	58.07.000	use in manufacture of textile fasteners Mattress handle cord, for use in manufacture of mattress handles	Free*	Free*	99
.0. .0.	50080 50239	59.02.001 59.08.009	 Mason type F felt antivibration pads (rectangular) Woven coated polyester and coated nylon sail cloth, when declared: (1) by a manufacturer for use by him only for making sails; or (2) by an importer that it will be sold by him only to manufacturers for use by them only in making sails 	Free* Free*	Free*	13
К	1892	68.06.009	Sandscreen, screen bak and fabricut discs, peculiar to use in the wet sanding of priming and/or undercoats in the automotive industry	Free*	Free*	99
.0.	50259	73.14.000	2.24 mm galvanised wire 1225 mPa, 2.50 mm galvanised wire 925/ 1075 mPa, 2.80 mm galvanised wire 1225 mPa, 3.15 mm galvanised wire 775/925 mPa, 4.00 mm galvanised wire 700/850 mPa, 5.38 mm galvanised wire 625/850 mPa, for use as reinforcing of industrial hoses	Free*	Free*	99
.0.	50191	73.15.141	Heavy galvanised spring wire 1400/1700 mPa for manufacture of preformed steel dead ends for terminating stay wire and bare copper conductors	Free*	Free*	99
.0.	50149	73.18.009	3050 m (10 000 ft) slurry pipe seamless 323.85 mm (12.75 in.)	Free*	Free*	99
.0.	49938	73.18.009	O.D. 12.7 mm (0.500 in.) W.T. Ammonia tube E.R.W. to BS 3602/62 grade 23 or equivalent, viz: Up	Free*	Free*	99
.0.	49938	73.18.009	to and including 150 mm n.b. Cold drawn welded carbon steel tubes—Jack Bore finish S.A.E. 1020 or equivalent viz:	Free*	Free*	99
.0.	49938	73.18.009	Up to and including 150 n.b. ERW carbon steel linepipe to API SL Gr. "B" or equivalent, viz: (i) Up to and including 80 mm n.b.	Free*	Free*	99
.0.	49938	73.18.009	 (ii) Greater than 300 mm n.b. ERW steel pipe to B.S.S. 1387/1967 or equivalent screwed and socketed and plain end, viz: 8 mm, 10 mm, 125 mm, 150 mm galv. light, galv. medium, black 	Free*	Free*	99
.0.	49938	73.18.009	medium, black heavy Hydraulic linepipe to B.S.S. 3601/62 grade 27 or equivalent and BS 3602 grade 23, viz: (i) B.S.S. 3601/27—Up to and including 50 mm n.b.	Free*	Free*	99
.0. .0. .0.	50241 50219 50183	73.18.009 73.18.009 73.18.009	(ii) B.S. $3602/23$ —Up to and including 1 in. O.D. Seamless, cold-drawn, steel hydraulic tube Welded steel conduit for use in the electrical industry Welded rectangular steel tubing, size $40 \times 20 \times 1.5$ mm, for repair	Free* Free* Free*	Free* Free* Free*	99 99 99
.0.	49938	73.18.009	and modification of Mercedes-Benz buses Wellsinker tube (continuous welded) to B.S. 1387/67 or equivalent viz: Up to 150 mm	Free*	Free*	99
.O. K	50192 1858	73.21.000 83.08.000	Glide bearings to carry high loads with relatively small base fixing areas Packless vibration absorbers for use in refrigeration and air conditioning equipment	Free* Free*	Free* Free*	99
.0. /N	50182 1234	83.09.011 84.10.029	Safety locks for schoolbags Fuller Kinyon cement pump parts comprising of the hopper body and	Free* Free*	Free* Free*	1: 10
'N	1266	84.11.031	nosepiece for pumping and discharging cement Atlas Copco portable rotary screw air compressors, capacity of 3.5 m^3 (125 c.f.m.), 4.8 m^3 (170 c.f.m.), 7.1 m^3 (250 c.f.m.) and 9.5 m^3 (335 c.f.m.) powered by air cooled diesel engines, models XAS 60, XAS 80, XAS 120 and XAS 160, for supplying compressed air for power rock drills, paving breakers, etc.	Free*	Free*	10
H	400	84.11.061	Corema Modulair cooled air generator, Model MD/W 1000, incorpor- ating a refrigeration unit, used for the supply of cooled air as required	Free*		
К	1970	84.11.061	in the manufacture of blown tubular plastic film Forward curved centrifugal blower wheels: Lav wheels in CKD form, peculiar to use in making evaporative air	Free*		.
K	1971	84.11.061	conditioning units Forward curved centrifugal blower wheels: Lav wheels size 457.2 mm \times 457.2 mm and smaller in fully made up form, peculiar to use in making evaporative air conditioning units	Free*		
.0. K	50200 2036	84.18.031 84.19.039	units Biohazard filters for use in medical laboratories Albro power filling machine, operates by transferring talc and face powders from mixer to bulk hopper then filling individual containers (Valumatria action)	Free* Free*	Free* Free*	10 10
K	1709	84.21.029	(Volumetric action) Oilers for thread cutting machinery:	Free*	Free*	10