

Price Order No. 143 (Steel Products Manufactured by Pacific Steel Ltd.)

PURSUANT to the Commerce Act 1975, I, Peter Edward Donovan, pursuant to a delegation from the Secretary of Trade and Industry, hereby make the following price order:

PRELIMINARY

1. This order may be cited as Price Order No. 143 and shall come into force on the 16th day of October 1979.

2. (1) Price Order No. 122* is hereby revoked.

(2) The revocation of the said order shall not affect the liability of any person for any offence in relation thereto committed before the coming into force of this order.

3. In this order:

The expression "f.o.r." means "free on rail".

APPLICATION OF THIS ORDER

4. This order applies to the following steel products manufactured by Pacific Steel Ltd.:

Rolled and Rerolled Steel Bars

1. Rounds
2. Squares
3. Flats
4. Angles
5. Channels

MAXIMUM PRICES TO BE CHARGED

5. (1) The maximum factory selling prices that may be charged or received by Pacific Steel Ltd. for any steel products to which this order applies shall be the basis price shown in this order, with adjustments in the form of extras as specified hereunder being made as appropriate.

(2) The maximum prices, as aforesaid, are fixed for deliveries as follows:

- (a) Within a radius of 40 kilometres of Otahuhu, free on truck at mill.
- (b) "f.o.r." Whangarei, Hamilton, Rotorua, Tauranga, Gisborne, Napier, Hastings, Palmerston North, New Plymouth, Wanganui, Masterton, Lower Hutt, Wellington, Blenheim, Christchurch, and Invercargill.
- (c) Landed on wharf or at railhead at Lyttelton, Timaru, Oamaru, Nelson, Greymouth, Dunedin, and Bluff.
- (d) For sales to other areas, the approved maximum selling prices may be surcharged with the amount which does not exceed the actual freight incurred for transport of steel from the nearest freight paid point mentioned above.

(3) The maximum basis price shall be \$489.50 per tonne, and shall apply to mild steel concrete reinforcing bars made in conformity with New Zealand Standard 3402 P: 1973, angles, channels, flats, squares, and rounds other than reinforcing made in conformity with British Standard 4360: Grades 43A, 43A. 1.

- (4) The basis price shall cover the following sizes:
- Rounds 20 mm diameter and over
 - Squares 12 mm to 75 mm
 - Flats } All shapes and sizes not included in 6 (1)
 - Angles } below.

(N.B. The company is not making basis size channels—203 mm x 76 mm x 24 kg/m and over.)

- (5) The basis price shall cover lengths from 5 m to 10 m.
- (6) The basis price shall cover the following quantities:

Rounds, 4 tonnes and over	}	In one size and thickness or diameter and in one quality
Squares, 4 tonnes and over		
Flats, 4 tonnes and over		
Angles, 4 tonnes and over		
- (7) The basis price shall cover the cold straightening of angles.

EXTRAS

6. The maximum charges for extras as appropriate are as follows:

(1) Size (added to Basis Price)

Rounds—	Per Tonne
Reinforcing and engineering:	\$ c
6.5 mm	10 75
10 mm	8 00
12 mm	4 00
16 mm	1 00
Squares, 10 mm	3 50

Flats—	Per Tonne
	\$ c
25 mm x 5 mm	7 00
25 mm x 6 mm	5 00
25 mm x 8 mm	5 00
25 mm x 10 mm	4 00
25 mm x 11 mm	4 00
25 mm x 12 mm	4 00
30 mm x 5 mm	7 00
30 mm x 6 mm	5 00
30 mm x 8 mm	5 00
30 mm x 10 mm	4 00
30 mm x 11 mm	4 00
30 mm x 12 mm	4 00
40 mm x 5 mm	6 00
40 mm x 6 mm	4 00
40 mm x 8 mm	4 00
40 mm x 10 mm	4 00
40 mm x 11 mm	4 00
40 mm x 12 mm	2 00
50 mm x 6 mm	4 00
50 mm x 8 mm	4 00
50 mm x 10 mm	2 00
50 mm x 11 mm	2 00
60 mm x 6 mm	4 00
60 mm x 8 mm	4 00
60 mm x 10 mm	2 00
80 mm x 6 mm	3 00
80 mm x 8 mm	3 00
100 mm x 6 mm	3 00
100 mm x 8 mm	3 00
100 mm x 10 mm	1 00
100 mm x 12 mm	1 00

Angles—	Per Tonne
	\$ c
25 mm x 25 mm x 5 mm	10 00
25 mm x 25 mm x 6 mm	8 00
30 mm x 30 mm x 5 mm	7 00
30 mm x 30 mm x 6 mm	6 00
40 mm x 40 mm x 5 mm	4 00
40 mm x 40 mm x 6 mm	2 00
50 mm x 50 mm x 5 mm	2 00

Channels—	Per Tonne
	\$ c
76 mm x 38 mm x 6.5 kg/m	8 00
102 mm x 51 mm x 10.0 kg/m	6 00
127 mm x 64 mm x 15.0 kg/m	3 00
152 mm x 76 mm x 18.0 kg/m	3 00

Each of the following extras may be added to basis price plus appropriate size extras.

(2) Quantity	Per Tonne
	\$ c
For products bundled in 1 Tonne Lifts	
1 tonne to under 2 tonnes	6 00
2 tonnes to under 3 tonnes	4 00
3 tonnes to under 4 tonnes	2 00
Minimum order 1 tonne	
For products bundled in 2 Tonne Lifts	
2 tonnes to under 4 tonnes	4 00

The above quantity extras apply to items of one size, quality, and length.

Where quantities under 10 tonnes of an item incur any extra freight, cartage, or other charges, such charges are to customer's account.

(3) Length	Per Tonne
	\$ c
Over 10 m to 12 m	1 00
Over 12 m to 15 m	1 50
(4) Cold Straightening	
Flats only	1 00
(5) Deformed Bars	4 00
(6) Bar marking grade 380 deformed	4 50
(7) Quality	

This section includes quality extras added to basis price, plus any extras added under 6 (1, 2, 3, 4, and 5) above.

Standard Specifications

Specification	Analysis	Per Tonne Extra
		\$ c
NZS 3402P: Grade 275 Deformed Sulphur .06 max. Phosphorus .06 max.		1 00
NZS 3402P: Grade 275 Plain Sulphur .06 max. Mild Phosphorus .06 max.		Basis Price
Medium Tensile 500/580 MPa	Sulphur .06 max. Phosphorus .06 max.	1 50
High Tensile 570/660 MPa	Sulphur .06 max. Phosphorus .06 max.	1 50
BS 4360	Sulphur .06 max. Phosphorus .06 max.	Basis Price
NZS 3402P: Grade 380 High Yield Steel		8 75