

TARIFF DECISION LIST No. 427—continued

APPROVALS—continued

Port	Tariff Item No.	Goods	Rates of Duty		Part II Ref.	Con-cession Code	Effective	
			Normal	Pref.			From	To*
H.O.	84.47.009	Loser RF 412 dowel milling machines	Free	Free	10	202737C	1/5/80	30/9/86
H.O.	84.47.009	Universal woodworker ZC21	Free	Free	10	202738A	1/7/80	30/9/86
H.O.	84.59.059	Wax injectors, peculiar to use in casting jewellery ..	Free	Free	10	112864H	1/7/78	30/9/86
AK	84.61.021	Aerosol valves and sprayheads producing variable fan spray, viz:	Free		..			
		PVA 4314 and Danvern fan spray				202739K	1/5/80	31/3/85
H.O.	84.61.021	Cocks and valves:	Free		..	202740C	1/3/80	30/6/86
		EXCLUDING:						
		(NOTE—This approval does not cover taps, bibcocks, or fire hydrants)						
		(1) Penstocks, floodgates						
		(2) Valves, gate, of the following types:						
		(a) Stainless steel 76 mm to 458 mm (3 in. to 18 in.) or cast iron 76 mm to 356 mm (3 in. to 14 in.) specifically designed for use with pulp or paper stock						
		(b) Brass, 12 mm ($\frac{1}{2}$ in.) and 19 mm ($\frac{3}{4}$ in.)						
		(c) 9 mm to 102 mm ($\frac{3}{8}$ in. to 4 in.) of any kind of bronze						
		(d) Flanged, cast iron, to B.S. 3464, other than outside screw and yoke types, sizes 51 mm (2 in.), 63.5 mm (2½ in.), 102 mm (4 in.), 150 mm (6 in.), 200 mm (8 in.)						
		(e) Flanged, cast iron, to B.S. 3464, with indicators, sizes 76 mm (3 in.), 100 mm (4 in.), 150 mm (6 in.), 200 mm (8 in.)						
		(3) Valves, globe, of any kind of bronze, peculiar for use with steam at working pressures of 345 kPa (50 p.s.i.) or over, of the following types:						
		(a) Stainless steel seats, screwed 9.5 mm to 51 mm ($\frac{3}{8}$ in. to 2 in.)						
		(b) Yoke top with bronze or stainless steel seats, flanged						
		(c) Angle, yoke type with bronze or stainless steel seats, flanged 25.4 mm to 76.2 mm (1 in. to 3 in.)						
		(d) Valves, safety or relief, spring-loaded, screwed or flanged, with bronze or stainless steel seats, 10 mm to 100 mm, and brass seats, 12 mm						
		(e) Fibre or teflon seats, screwed, sizes 12 mm to 51 mm ($\frac{1}{2}$ in. to 2 in.)						
		(f) Flanged bonnet top, 19 mm to 77 mm ($\frac{3}{8}$ in. to 3 in.), with bronze or stainless steel seats and a working pressure of up to 865 kPa (125 p.s.i.)						
		(g) Flanged regulating check angle or straight type, 19 mm to 153 mm ($\frac{3}{8}$ in. to 6 in.), with bronze or stainless steel seats and a working pressure up to 1725 kPa (250 p.s.i.)						