

## TARIFF DECISION LIST No. 427—continued

## APPROVALS—continued

Port	Tariff Item No.	Goods	Rates of Duty		Part II Ref.	Concession Code	Effective	
			Normal	Pref.			From	To*
	84.61.021 continued	<p>Cocks and valves—continued: EXCLUDING—continued: (NOTE—This approval does not cover taps, etc.)—continued: (3)—continued:     (h) Foot operated, quick action or slow closing (non-concussive), 15 mm to 25 mm</p> <p>(4) Valves, foot, of copper alloy not exceeding 51 mm (2 in.) of cast iron or steel of all types of seats (excluding leather flap type), sizes 51 mm to 305 mm (2 in. to 12 in.)</p> <p>(5) Valves, float, of brass or other copper alloy, not exceeding 153 mm (6 in.)</p> <p>(6) Valves, ball:     (a) Screwed, stainless steel and cast carbon steel bodies, 16 mm (<math>\frac{5}{8}</math> in.) to 50 mm (2 in.) B.S.P., other than multiport and jacketed types     (b) Screwed, brass sizes 15 mm, 20 mm, 25 mm, 32 mm, 40 mm, and 50 mm B.S.P.     (c) Screwed, cast iron, sizes 12 mm (<math>\frac{1}{2}</math> in.), 19 mm (<math>\frac{3}{4}</math> in.), 25 mm (1 in.), 32 mm (1<math>\frac{1}{4}</math> in.), 40 mm (1<math>\frac{1}{2}</math> in.), 50 mm (2 in.)     (d) Flanged, cast stainless steel or cast steel, sizes 50 mm (2 in.), 80 mm (3 in.), 100 mm (4 in.), 150 mm (6 in.), tested fire safe     (e) Screwed bronze, sizes 15 mm, 20 mm, and 25 mm B.S.P.</p> <p>(7) Sluice or wedge gate (or stop) valves of cast iron and alloyed iron for waterworks purposes and like application, in nominal sizes, 51 mm (2 in.), 76 mm (3 in.), 100 mm (4 in.), 150 mm (6 in.), 200 mm (8 in.), 254 mm (10 in.), 300 mm (12 in.), 380 mm (15 in.), 400 mm (16 in.), 450 mm (18 in.), 500 mm (20 in.) and 600 mm (24 in.) double flange and spigot or socket ends, hand operated, for test pressures not exceeding 244 metres (800 ft.) head of water with or without copper based trims. In accordance with BSS 1218, NZSS 784, BSS 5163, and same purpose valves for higher pressures above standards</p> <p>(8) Check valves (reflux) of iron and alloyed iron for general purposes, in nominal sizes 80 mm, 100 mm, 150 mm, 200 mm, 250 mm, 300 mm, double flanged, for test pressure 244 metres head, free acting and external lever operated in accordance with BSS 4090, not including non-concussive types</p>						