

TARIFF DECISION LIST No. 427—continued

APPROVALS—continued

Port	Tariff Item No.	Goods	Rates of Duty		Part II Ref.	Con- cession Code	Effective	
			Normal	Pref.			From	To*
	84.61.021 continued	<p>Cocks and valves—continued: EXCLUDING—continued: (NOTE—This approval does not cover taps, etc.)—continued:</p> <p>(9) Plugcocks, bronze, screwed and flanged straight through or 3-way, sizes 12 mm to 102 mm ($\frac{1}{2}$ in. to 4 in.), (but not sleeve packed plugcocks)</p> <p>(10) Valves, peculiar for use on bulk fuel tankers, viz:</p> <p>(a) Pressure vacuum valves, aluminium, screwed, 76 mm (3 in.) and 102 mm (4 in.) flanged</p> <p>(11) Check valves of any kind of bronze, peculiar for use with steam or water, of the following types and working pressures:</p> <p>(a) Flanged horizontal types, 19 mm to 153 mm ($\frac{3}{4}$ in. to 6 in.) with stainless steel or bronze seat and a working pressure of 344 kPa to 1725 kPa (50 p.s.i. to 250 p.s.i.)</p> <p>(b) Flanged and screwed swing type 63.5 mm to 102 mm ($2\frac{1}{2}$ in. to 4 in.) of 344 kPa to 690 kPa (50 p.s.i. to 100 p.s.i.)</p> <p>Screwed vertical type 63.5 mm to 76 mm ($2\frac{1}{2}$ in. to 3 in.) with bronze seat and a working pressure of 344 kPa to 690 kPa (50 p.s.i. to 100 p.s.i.)</p> <p>(d) Horizontal check valves 12 mm to 51 mm ($\frac{1}{2}$ in. to 2 in.) fibre or teflon seats and a working pressure up to 1035 kPa (150 p.s.i.)</p> <p>(12) Treacle cocks, bronze 25 mm to 76 mm (1 in. to 3 in.)</p> <p>(13) Blow down plug cock, flanged, asbestos packed, double gland bronze 25 mm to 51 mm (1 in. to 2 in.), peculiar for use for blowing down boilers or pressure vessels and tested up to 3450 kPa (500 p.s.i.)</p> <p>(14) Needle valves, of bronze and stainless steel, in-line types, sizes 6 mm ($\frac{1}{4}$ in.), 9.5 mm ($\frac{3}{8}$ in.) and 13 mm ($\frac{1}{2}$ in.) B.S.P.</p> <p>(15) Pressure reducing:</p> <p>(a) Valves of bronze, pilot operated, flanged and screwed, stainless steel seat and valve, sizes 12 mm to 51 mm ($\frac{1}{2}$ in. to 2 in.) up to 1725 kPa (250 p.s.i.)</p> <p>(b) Valves of bronze, for water, 12 mm to 25 mm ($\frac{1}{2}$ in. to 1 in.) screwed ends up to 1725 kPa (250 p.s.i.)</p>						