THE NEW ZEALAND GAZETTE

—

2627

TARIFF DECISION LIST No. 427-continued

APPROVALS—continued

Port	Tariff Item No.	Goods	Rates of Duty		Part	Con-	Effective	
			Normal	Pref.	II Ref.	cession Code	From	To *
	84.61.021	Cocks and valves—continued:						
	continued	EXCLUDING—continued:						
		(NOTE-This approval does not cover taps,						
		etc.)-continued:						
		(16) Valves, peculiar for use by service						
		station petrol pumps:	-					
		(a) Petrol pump dispensing nozzles			1			
		(b) Petrol pump dispensing nozzles, automatic shut-off types,					1	
		which operate at up to 2.3	3					
	-	litres/second (30 g.p.m.) at	1					
		pressures from 344 kPa (50	1				1	
		p.s.i. to 90 p.s.i.)						
		(17) Valves, drum compensating types,						
		being air reducing valves, peculiar					1	
		for use to pressurised oil storage con-						
		tainers having a capacity 57 litres						
		$(12\frac{1}{2} \text{ gal.}), 200 \text{ litre } (44 \text{ gal.}), 272$						
		litre (60 gal.) or more						
		(18) Solenoid valves, 2 port, with bodies			1		1	
		constructed entirely of brass or						
		cast iron, direct acting and pilot					-	
		operated, sizes 3 mm ($\frac{1}{3} \text{ in.}$) to 76 mm (3 in.) of pressures 0 to					1	
		1380 kPa (0 to 200 p.s.i.) not in-						
		corporating any of the following						
		features:					1	
		(a) manual reset construction	1					
		(b) slow open/fast close gas valve						
		construction approved by a						
		recognised gas approval body			4			
		(c) gas valves						
		(19) Aerosol valves, with or without actu-						
		ators, peculiar to use with 25 mm			1			
		(1 in.) neck-opening aerosol con- tainers						
		(20) Check valves:						
		(a) Wafer type, all materials; sizes						
		51 mm (2 in.) to 915 mm (36 in.)						
		ASA 150 or B.S. equivalent;						
		sizes 51 mm (2 in.) to 356 mm			:			
		(14 in.) ASA 300 or B.S.			4			è
		equivalent; sizes 51 mm (2 in.)						
		to 255 mm (10 in.) ASA 600 or						
		B.S. equivalent; sizes 51 mm			{			
		(2 in.) to 205 mm (8 in.) ASA						
		1500 or B.S. equivalent; suit- able for water, oil or steam,						
		bare or fitted with back flush						
		lever, adjustable counter bal-						
		ance or cam operated micro						
		switch, 51 mm to 305 mm			1 .			
		(2 in. to 12 in.), peculiar	· · · · · · · · · · · · · · · · · · ·					
		to working pressure 1895 kPa			.			
		(275 p.s.i.)		•				
		(b) Swing check valves, bronze to			4 1			
		BSS/1953/1964 NZ 1430/					}	
		1966 in sizes 12 mm to 51 mm						
		$(\frac{1}{2}$ in. to 2 in.)			1			
		(21) Valves for hydraulic pumps of tractors,						
	1	loaders, excavators, and similar machines			1			