## TARIFF DECISION LIST No. 427—continued

APPROVALS—continued

|   | Tariff Item No. | Goods   | Rates of Duty |       | Part       | Con-            | Effective |                 |
|---|-----------------|---|---------------|-------|------------|-----------------|-----------|-----------------|
| t |                 |   | Normal        | Pref. | II<br>Ref. | cession<br>Code | From      | To <sup>*</sup> |
|   |                 |   |               |       | <u> </u>   |                 |           | <u> </u>        |
|   | 84.61.021       | Cocks and valves—continued:                           |               |       |            |                 |           |                 |
|   | continued       | EXCLUDING—continued:                                  |               |       | 1          |                 |           |                 |
|   | Communica       | (NOTE—This approval does not cover taps,              |               |       |            |                 |           |                 |
|   | 1               | etc.)—continued:                                      | ·             |       |            |                 |           |                 |
|   |                 | (22) Purpose made 152 mm and 102 mm                   |               |       |            |                 |           |                 |
|   |                 | (6 in, and 4 in.) diameter Fullway wet                |               |       |            |                 |           |                 |
|   |                 | pipe sprinkler alarm, basic non-                      |               |       |            |                 |           |                 |
|   |                 | return valves, flanged, cast iron                     |               |       |            | i               |           |                 |
|   |                 | (23) Oil control valves, constant level, for          |               |       |            |                 |           |                 |
|   | į               |   |               |       |            |                 |           |                 |
|   |                 | vapourising and other types of burner                 |               | -     | ŀ          | !               |           |                 |
|   |                 | requiring a metering control. Suitable                |               |       | l .        |                 | l i       |                 |
|   |                 | for use with light fuel oil, diesel or                |               |       |            |                 |           |                 |
|   |                 | kerosene, up to a 9.1 m (30 ft.) head,                |               |       |            |                 |           |                 |
|   |                 | Standard head mounting, manually                      |               |       |            |                 |           |                 |
|   |                 | or thermo-statically controlled                       |               | . '   |            |                 |           |                 |
|   |                 | (24) Diaphragm valves of cast iron, screwed           |               |       |            |                 |           |                 |
|   |                 | B.S.P., hand wheel operated, suit-                    | ,             |       |            |                 |           |                 |
|   | :               | able for use with compressed air,                     |               |       |            |                 |           |                 |
|   | 1               | water, and other non-corrosive                        |               |       |            |                 |           |                 |
|   |                 | liquids, but not suitable for steam:                  | '             |       | ' '        |                 | ļ         |                 |
|   |                 | Screwed:  |               |       |            |                 | į         |                 |
|   |                 | 12 mm ( $\frac{1}{2}$ in), 19 mm ( $\frac{3}{4}$ in.) |               |       |            |                 |           |                 |
|   |                 | 25 mm (1 in.) up to 1725 kPa (250                     |               |       | -          |                 | 1         |                 |
|   |                 | p.s.i.)   |               |       | İ          |                 |           |                 |
|   |                 | 38 mm ( $1\frac{1}{2}$ in.) up to 1207 kPa (175       |               | _     |            |                 |           |                 |
|   |                 | p.s.i.)   |               |       |            |                 | İ         |                 |
|   |                 | 51 mm (2 in.) up to 862 kPa (125                      | i             |       | '          |                 | ĺ         |                 |
|   |                 | p.s.i.)   |               |       |            |                 | ì         |                 |
|   |                 | Flanged:  |               |       |            |                 |           |                 |
|   |                 | to B.S. table D. 51 mm (2 in.) up                     |               |       |            |                 |           |                 |
|   |                 | to 862 kPa (125 p.s.i.)                               | '             |       | i '        |                 | ·         |                 |
|   |                 | (25) Butterfly valves of cast iron, with rubber       |               |       |            |                 |           |                 |
|   |                 | liners and suitable for working                       |               |       |            |                 |           |                 |
|   |                 | pressures up to 1380 kPa (200 p.s.i.):                |               |       | . '        |                 |           |                 |
|   |                 | Wrench operated:                                      |               |       | 1 .        |                 |           |                 |
|   |                 | 51 mm (2 in.), 65 mm ( $2\frac{1}{2}$ in.),           |               |       |            |                 |           |                 |
|   |                 | 76 mm (3 in.)   |               | 1     | 1          |                 | 1         |                 |
|   |                 | M12:  |               |       | [ i        |                 | į         |                 |
|   |                 | 102 mm (4 in.), 152 mm (6 in.),                       | ]             |       | 1          |                 |           |                 |
|   |                 | 204 mm (8 in.), 254 mm (10 in.),                      |               | }     | }          |                 | ļ         |                 |
|   |                 | 305 mm (12 in.)                                       |               |       | 1.         | 1               |           |                 |
|   |                 | Gear operated:  |               |       | ]          |                 |           |                 |
|   |                 | 51 mm (2 in.), 76 mm (3 in),                          |               |       |            |                 |           |                 |
|   |                 | 102 mm (4 in.), 152 mm (6 in.),                       | *             |       | 1          |                 |           |                 |
|   |                 | 254 mm (10 in.), 305 mm (12 in.)                      |               |       | 1          |                 | ]         | 1               |
|   | <b> </b>        | Pneumatically operated:                               |               |       |            |                 |           |                 |
|   |                 | 51 mm (2 in.), 65 mm ( $2\frac{1}{2}$ in.),           |               | 1.0   |            |                 |           |                 |
|   | ļ               | 76 mm (3 in.), 102 mm (4 in.)                         |               |       | )          |                 | 1         |                 |
|   |                 | (26) Air control valves, 2, 3, 4 way and parts        | +1            |       |            |                 | l         |                 |
|   |                 | thereof, for use in either pneumatic                  |               |       |            |                 |           |                 |
|   | [               | or hydropneumatic circuit appli-                      |               |       | 1          |                 | }         |                 |
|   |                 | cation up to 25 mm (1 in.) B.S.P.                     |               |       |            |                 |           |                 |
|   |                 | port sizes, however actuated, con-                    |               |       | ŀ          |                 |           |                 |
|   | ļi              | structed or sealed, and the following                 |               |       |            |                 |           |                 |
|   | ] :             | accessory valves normally used in                     |               |       | 1          |                 |           |                 |
|   |                 | conjunction with these air control                    |               |       | 1          |                 |           |                 |
|   | ] : 1           | valves:   |               |       |            |                 |           |                 |
|   | <u> </u>        | Exhaust flow control up to 13 mm                      |               |       |            |                 |           |                 |
|   |                 | (½ in.) B.S.P.  |               | /     | 1          |                 |           |                 |
|   |                 | Exhaust silencers up to 13 mm ( $\frac{1}{2}$ in.)    | 4 2 4         |       | 1          |                 |           |                 |
|   | ]               | B.S.P.  | 1             |       | 1          |                 | 1         |                 |