

## TARIFF DECISION LIST No. 427—continued

## APPROVALS—continued

Port	Tariff Item No.	Goods	Rates of Duty		Part II Ref.	Con- cession Code	Effective	
			Normal	Pref.			From	To*
	84.61.021 <i>continued</i>	Cocks and valves— <i>continued</i> : EXCLUDING— <i>continued</i> : (NOTE—This approval does not cover taps, etc.)— <i>continued</i> : (26)— <i>continued</i> : Flow control up to 13 mm ( $\frac{1}{2}$ in.) B.S.P. port Hold back or lock up to 6 mm ( $\frac{1}{4}$ in.) B.S.P. Non return up to 13 mm ( $\frac{1}{2}$ in.) B.S.P. Quick exhaust up to 13 mm ( $\frac{1}{2}$ in.) B.S.P. port Sequence up to 6 mm ( $\frac{1}{4}$ in.) B.S.P. port Shuttle or tee up to 13 mm ( $\frac{1}{2}$ in.) B.S.P. port (27) Pneumatic and hydraulic quick release couplings up to 25 mm (1 in.) inlet diameter (28) Valves for compressed gas cylinders (29) Oxygen and acetylene single stage regulators (30) Compressed gas cylinder valves of brass or bronze, high or low pressure (31) Knife gate valves of the following types: (a) Stainless steel fabricated, flanged 75 mm–1000 mm (b) Stainless steel cast or nickel iron cast, flanged 100 mm– 200 mm (32) Rotary valves, 6-way multi-port (33) Valves, globe of cast iron of the follow- ing types: (a) Straight through valve, sizes 50 mm, 62 mm, 75 mm, 100 mm with maximum work- ing pressure at 221 $\square$ C being 1310 kPa and at 121 $\square$ C 2067 kPa (b) Right angle valve, sizes 50 mm, 62 mm, 75 mm, 100 mm with maximum working pressure at 221 $\square$ C being 1310 kPa, and at 121 $\square$ C 2067 kPa (34) Flushing valves, peculiar for use with effective water heads between 2 and 90 metres (35) Air control valves: (a) Ball diameter 7 mm (b) Inlet screw 25 mm B.S.P. (c) Maximum working pressure 150 mm head						
AK	84.61.021	Whitey brass and stainless steel cylinder valves, when declared by a manufacturer for use in the assembly or repair of Whitey and Nupro cylinders, up to 4.546 litres	Free		..	202741A	1/5/80	31/3/83
AK	84.61.021	Whitey stainless steel, copper or copper alloy, ball valves in the multiple position range 3-way, 4-way, 5-way, 6-way and 7-way and the same variations with vented ports	Free		..	202820E	1/5/80	31/3/83
H.O.	84.63.029	Gear boxes, specially designed for use with marine engines	Free	Free	10	113072C	1/7/78	30/6/86