

Tariff Notice No. 1980/183—Application for Variation of Exclusion from Approval

NOTICE is hereby given that an application has been made for a variation of a current exclusion from approval of the Minister of Customs and for admission of such goods at the rates of duty prescribed under the substantive Tariff item therefor:

Port	Appn. No.	Tariff Item	Goods	Rates of Duty		Part II Ref.	Concession Code	Effective	
				Normal	Pref.			From	To
		84.61.021	<p>CURRENT EXCLUSION: Cocks and valves:</p> <p>EXCLUDING: (Note: This approval does not cover taps, bibcocks, or fire hydrants) (3) Valves, globe, of any kind of bronze, commonly used with steam at working pressures of 345 kPa (50 p.s.i.) or over of the following types: (a) Stainless steel seats, screwed 9.5 mm to 51 mm ($\frac{3}{8}$ in. to 2 in.) (b) Yoke top with bronze or stainless steel seats, flanged (c) Angle, yoke top with bronze or stainless steel seats, flanged, 25.4 mm to 76.2 mm (1 in. to 3 in.) (d) Valves, safety or relief, spring-loaded, screwed or flanged, with bronze or stainless steel seats, 10 mm to 100 mm (e) Fibre or teflon seats, screwed, sizes 12 mm to 51 mm ($\frac{1}{2}$ in. to 2 in.) (f) Flanged bonnet top 19 mm to 77 mm ($\frac{3}{8}$ in. to 3 in.) with bronze or stainless steel seats and a working pressure of up to 865 kPa (125 p.s.i.) (g) Flanged regulating check angle or straight type 19 mm to 153 mm ($\frac{3}{8}$ in. to 6 in.) with bronze or stainless steel seats and a working pressure up to 1725 kPa (250 p.s.i.) (h) Foot operated, quick action or slow closing (non-concussive), 15 mm to 25 mm</p>	Free			202740C	1/7/78	30/6/86
H.O.	58416	84.61.021	<p>REQUESTED EXCLUSION: Cocks and valves: EXCLUDING: (Note: This approval does not cover taps, bibcocks, or fire hydrants) (3) Valves, globe, of any kind of bronze, peculiar for use with steam at working pressures of 345 kPa (50 p.s.i.) or over of the following types: (a) Stainless steel seats, screwed 9.5 mm to 51 mm ($\frac{3}{8}$ in. to 2 in.) (b) Yoke top with bronze or stainless steel seats, flanged (c) Angle yoke top with bronze or stainless steel seats, flanged, 20 mm to 150 mm ($\frac{3}{8}$ in. to 6 in.) (d) Valves, safety or relief, spring-loaded, screwed or flanged with bronze or stainless steel seats, 10 mm to 100 mm (e) Fibre or teflon seats, screwed, sizes 12 mm to 51 mm ($\frac{1}{2}$ in. to 2 in.) (f) Flanged bonnet top 19 mm to 77 mm ($\frac{3}{8}$ in. to 3 in.) with bronze or stainless steel seats and a working pressure of up to 865 kPa (125 p.s.i.) (g) Flanged regulating check angle or straight type 19 mm to 153 mm ($\frac{3}{8}$ in. to 6 in.) with bronze or stainless steel seats and a working pressure up to 1725 kPa (250 p.s.i.) (h) Foot operated, quick action or slow closing (non-concussive), 15 mm to 25 mm</p>						