## THE NEW ZEALAND GAZETTE

## Tariff Notice No. 1980/189-Applications for Variation of Approval

NOTICE is hereby given that applications have been made for variation of current approvals of the Minister of Customs as follows:

Port	Appn. No.	Tariff Item	Goods	Rates of Duty		Part		Effective	
				Normal	Pref.	II Ref.	Concession Code	From	То
		38.19.079	CURRENT APPROVAL: Polyquart H	Free	Free	15	105954J	1/7/78	30/6/8
AK	9252	38.19.079	REQUÉSTED APPROVAL: Polyquart H. 81			1.0	1009010	1/7/10	50/0/0
		39.02.125	CURRENT APPROVAL: Metallised and/or lacquered, pliable, un- plasticised P.V.C. film REQUESTED APPROVAL:	Free			107085B	1/7/78	30/9/8
н.о.	58481	39.02.125	Vacuum metallised unplasticised film CURRENT APPROVAL:					I	
		39.02.125	"Plastolam" PVC sheeting in jumbo rolls, when declared by an importer for sale by him, only to a manufacturer for use only in making "Coverall" self-adhesive con-	Free			107099B	1/7/78	30/9/8
AK	9230	39.02.125	tact vinyl <b>REQUESTED APPROVAL:</b> <b>PVC</b> sheeting in jumbo rolls, when declared by an importer for sale by him, to a manu- facturer for use only in making "Coverall" self-adhesive contact vinyl						
	ł	40.11.001	CURRENT APPROVAL: Please refer to T.D.L. 385	10	Free		107695H	1/4/79	30/9/8
H.O.	58544	40.11.001	REQUESTED APPROVAL: Pneumatic tyres, tyre cases and tubes therefor, EXCLUDING the following sizes or other equivalent (irrespective of ply rating, speed rating, tread type,					_/ ./	
			pattern construction or constituent materials):						
			EXPLANATORY NOTES: 1. Sizes have been listed in order from						
			<ol> <li>Shave bave over instead in order from smallest to largest in their respective series</li> <li>Bias and Radial tyres are shown to- gether under their respective rim dia- meters.</li> </ol>						
			3. The + shows where a letter indicating the "speed rating" of a tyre may appear in the size marking, e.g., 155+R13 in- corporates 155SR13, 155HR13 and						
			155VR13. Most common speed rating letters are:						
			S H						
			But can include F				-		
			M N P Q R						
			<ul> <li>(The effect of the symbol + is to disregard speed ratings)</li> <li>4. The letter "C" can also appear after the rim diameter and should be disregarded,</li> </ul>						
			e.g. 185R14C 500-16C 5. Group markings occur and vary ac- cording to country of origin. If a size						
			incorporated in a group marking appears in the list of sizes in T.D.L. 385 the tyre or tube with group marking is deemed to be included in T.D.L. 385 e.g., 575/						
			600/640-15 includes the sizes 575-15, 600-15 and 640-15. CARS, VANS AND LIGHT COM- MERCIAL VEHICLES						
			Tyres 10 in. Rim Diameter (or 255 mm) 5.20+10 145+R10 165/70+R10						
			12 in. Rim Diameter (or $305 \text{ mm}$ ) 4.40+12 Y78+12 4.40/125+12 Z78+12 5.20+12 125/5.35+12 5.35+12 155/6.15+12					l	