

TARIFF DECISION LIST No. 402—continued

APPROVALS—continued

Port	Tariff Item No.	Goods	Rates of Duty		Part II Ref.	List No.	Effective	
			Normal	Pref.			From	To*
	74.07.009 (cont'd)	69.85 mm × 1.63 mm 4.75 mm × 0.71 mm 6.35 mm × 0.71 mm				200579E 200580J 200581G	1/10/78 1/10/78 1/10/78	30/9/81 30/9/81 30/9/81
AK	84.17.009	Dryers, peculiar to use with plastic mouldings machines	Free	Free	10	200582E	1/7/78	31/3/85
WN	84.17.009	Thelco vacuum ovens, peculiar to use in laboratories	Free	Free	10	200583C	1/7/78	30/6/85
AK	84.17.009	Thomas Royce tri-heat temperature control unit ..	Free	Free	10	200584A	1/7/78	31/3/85
AK	84.19.039	Hammerle VT50 vacuum packaging machine ..	Free	Free	10	200586H	1/3/80	31/3/83
H.O.	84.22.009	Hiab cranes for mounting on trucks, models 900, 1100, and 1300, peculiar to use in loading and unloading logs	Free	Free	10	200587F	1/12/79	30/6/84
H.O.	84.61	Cocks and valves: Excluding: (NOTE: This approval does not cover taps, bibcocks, or fire hydrants) (18) Solenoid valves, 2 port, with bodies constructed entirely of brass or cast iron, direct acting and pilot operated, sizes 3 mm (1/8 in.) to 76 mm (3 in.) of pressure 0 to 1380 kPa (0 to 200 p.s.i.), not incorporating any of the following features: (a) manual reset construction (b) slow open/fast close valve construction (c) gas valves approved by a recognised gas approval body	Free	Free	10			
						200588D	1/3/80	..
H.O.	84.61.021	Valves, peculiar to use for operation by instruments, recording and non-recording, capable of being set to maintain automatically at a pre-determined level, temperature, humidity, liquid level, pressure, or any combination of these conditions: Excluding: (i) All valves having globe pattern body form, offset, in line, angle, barstock or three way design having a body rating of 1030 kPa and above, constructed of iron, steel and stainless steel alloys and fitted with air operated pneumatic actuators or cylinders (ii) All valve body assemblies of globe pattern form, offset, in line, angle, barstock or three way design having a body rating of 1030 kPa and above, constructed of iron, steel and stainless steel alloys, but not including manual wheel operated or self actuating regulating valves (iii) All control valve body assemblies designed for use with pneumatic operators whether or not fitted with air operated pneumatic actuators or cylinders for use with steam, gases and clean liquid (other than containing fibres) services having a rate of 150 lbs and above constructed of iron, steel and stainless steel alloys NOTE: These three exclusions do not cover valves of 75 mm and below nominal size and pressure rating of 1030 kPa and below, air actuated, when declared by importers for use on domestic and air-conditioning systems	Free		..	200589B	1/5/80	30/9/86