

## TARIFF DECISION LIST No. 413—continued

## APPROVALS—continued

Port	Tariff Item No.	Goods	Rates of Duty		Part II Ref.	List No.	Effective		
			Normal	Pref.			From	To*	
	84.61 continued	<p>Cocks and valves—continued: EXCLUDING—continued:</p> <p>(3) Valves, globe, of any kind of bronze, commonly used with steam at working pressures of 345 kPa (50 p.s.i.) or over, of the following types:</p> <p>(a) Stainless steel seats, screwed 9.5 mm to 51 mm (<math>\frac{3}{8}</math> in. to 2 in.)</p> <p>(b) Yoke top with bronze or stainless steel seats, flanged</p> <p>(c) Angle, yoke top with bronze or stainless steel seats, flanged 25.4 mm to 76.2 mm (1 in. to 3 in.)</p> <p>(d) Valves, safety or relief, springloaded, screwed or flanged, with bronze or stainless steel seats, 10 mm to 100 mm, and brass seats, 12 mm</p> <p>(e) Fibre or teflon seats, screwed, sizes 12 mm to 51 mm (<math>\frac{1}{2}</math> in. to 2 in.)</p> <p>(f) Flanged bonnet top 19 mm to 77 mm (<math>\frac{3}{4}</math> in. to 3 in.), with bronze or stainless steel seats and a working pressure of up to 865 kPa (125 p.s.i.)</p> <p>(g) Flanged regulating check angle or straight type 19 mm to 153 mm (<math>\frac{3}{4}</math> in. to 6 in.), with bronze or stainless steel seats and a working pressure up to 1725 kPa (250 p.s.i.)</p> <p>(h) Foot operated, quick action or slow closing (non-concussive), 15 mm to 25 mm</p> <p>(4) Valves, foot, of copper alloy not exceeding 51 mm (2 in.) of cast iron or steel of all types of seats (excluding leather flap type), sizes 51 mm to 305 mm (2 in. to 12 in.)</p> <p>(5) Valves, float, of brass or other copper alloy, not exceeding 153 mm (6 in.)</p> <p>(6) Valves, ball:</p> <p>(a) Screwed, stainless steel and cast carbon steel bodies, 16 mm (<math>\frac{5}{8}</math> in.) to 50 mm (2 in.) B.S.P., other than multiport and jacketed types</p> <p>(b) Screwed, brass sizes 15 mm, 20 mm, 25 mm, 32 mm, 40 mm, and 50 mm B.S.P.</p> <p>(c) Screwed, cast iron, sizes 12 mm (<math>\frac{1}{2}</math> in.), 19 mm (<math>\frac{3}{4}</math> in.), 25 mm (1 in.), 32 mm (1<math>\frac{1}{4}</math> in.), 40 mm (1<math>\frac{1}{2}</math> in.), 50 mm (2 in.)</p> <p>(d) Flanged, cast stainless steel or cast steel, sizes 50 mm (2 in.), 80 mm (3 in.), 100 mm (4 in.), 150 mm (6 in.), tested fire safe</p> <p>(e) Screwed bronze, sizes 15 mm, 20 mm, and 25 mm B.S.P.</p>						1/7/79	30/6/86