

TARIFF DECISION LIST No. 413—*continued*APPROVALS—*continued*

Port	Tariff Item No.	Goods	Rates of Duty		Part II Ref.	List No.	Effective	
			Normal	Pref.			From	To*
	84.61 <i>continued</i>	<p>Cocks and valves—<i>continued</i>:  EXCLUDING—<i>continued</i>:</p> <p>(12) Treacle cocks, bronze 25 mm to 77 mm (1 in. to 3 in.)</p> <p>(13) Blow down plug cock, flanged, asbestos packed, double gland bronze 25 mm to 51 mm (1 in. to 2 in.), commonly used for blowing down boilers or pressure vessels and tested up to 3450 kPa (500 p.s.i.)</p> <p>(14) Needle valves, of bronze and stainless steel, in-line types sizes 6 mm (<math>\frac{1}{4}</math> in.), 9.5 mm (<math>\frac{3}{8}</math> in.) and 13 mm (<math>\frac{1}{2}</math> in.) B.S.P.</p> <p>(15) Pressure reducing:</p> <p>(a) Valves of bronze, pilot operated, flanged and screwed, stainless steel seat and valve, sizes 12 mm to 51 mm (<math>\frac{1}{2}</math> in. to 2 in.) up to 1725 kPa (250 p.s.i.)</p> <p>(b) Valves of bronze, for water, 12 mm to 26 mm (<math>\frac{1}{2}</math> in. to 1 in.) screwed ends up to 1725 kPa (250 p.s.i.)</p> <p>(16) Valves, commonly used by service station petrol pumps:</p> <p>(a) Petrol pump dispensing nozzles</p> <p>(b) Petrol pump dispensing nozzles, automatic shut-off types, which operate at up to 2.3 litres/second (30 g.p.m.) at pressures from 344 kPa (50 p.s.i. to 90 p.s.i.)</p> <p>(17) Valves, drum compensating types, being air reducing valves, commonly used to pressurise oil storage containers having a capacity 57 litres (12<math>\frac{1}{2}</math> gal.) 200 litre (44 gal.), 272 litre (60 gal.) or more</p> <p>(18) Solenoid valves, 2 port, with bodies constructed entirely of brass or cast iron, direct acting and pilot operated, sizes 3 mm (<math>\frac{1}{8}</math> in.) to 76 mm (3 in.) of pressures 0 to 1380 kPa (0 to 200 p.s.i.) not incorporating any of the following features:</p> <p>(a) manual reset construction;</p> <p>(b) slow open/fast close gas valve construction approved by a recognised gas approval body</p> <p>(19) Aerosol valves, with or without actuators, peculiar to use with 25 mm (1 in.) neck-opening aerosol containers</p> <p>(20) Check valves:</p> <p>(a) Wafer type, all materials; sizes 51 mm (2 in.) to 915 mm (36 in.) ASA 150 or B.S. equivalent; sizes 51 mm (2 in.) to 356 mm (14 in.) ASA 300 or B.S. equivalent; sizes 51 mm (2 in.) to 255 mm (10 in.) ASA 600 or B.S. equivalent; sizes 51 mm (2 in.) to 205 mm (8 in.) ASA</p>						