## THE NEW ZEALAND GAZETTE

APPROVALS—continued

	Tariff Item No.	Goods	Rates of Duty		Part		Effective	
ort			Normal	Pref.	- II Ref.	List No.	From	То*
	84.61 continued	Cocks and valves—continued: EXCLUDING—continued:		l 				
		1500 or B.S. equivalent;						
		suitable for water, oil or steam, bare or fitted with back						
		flush lever, adjustable counter						
		balance or cam operated micro					1	
		switch, 51 mm to 305 mm (2 in.						
		to 12 in.), peculiar to working pressure 1895 kPa (275 p.s.i.)					1	
		(b) Swing check valves, bronze to BSS/						
		1953/1964 NZ 1430/1966 in						
		sizes 12 mm to 51 mm $(\frac{1}{2}$ in. to 2 in.)						
		(21) Valves for hydraulic pumps of tractors,			ĺ			
		loaders, excavators, and similar						
		machines (22) Purpose made 152 mm and 102 mm (6 in.					(	
		and 4 in.) diameter Fullway wet pipe						
		sprinkler alarm, basic non-return						
		valves, flanged, cast iron (23) Oil control valves, constant level, for						
		vapourising and other types of						
		burner requiring a metering control.						
		Suitable for use with light fuel oil, diesel or kerosene, up to a 9.1 m						
		(30 ft.) head, Standard head mount-						
		ing, manually or thermo-statically						
		controlled (24) Diaphragm valves of cast iron, screwed					í	
		B.S.P., hand wheel operated, suitable						
		for use with compressed air, water,					ł	
		and other non-corrosive liquids, but						
		not suitable for steam: Screwed:			[			
		13 mm ( $\frac{1}{2}$ in.), 19 mm ( $\frac{3}{4}$ in.)						
		25 mm (1 in.) up to 1725 kPa (250						
		p.s.i.) 38 mm (1½ in.) up to 1207 kPa (175						
		p.s.i.)						
		51 mm (2 in.) up to 862 kPa (125			Ì			
		p.s.i.) Flanged:						
		to B.S. table D. 51 mm (2 in.) up to						
		862 kPa (125 p.s.i.)					1/9/70	20/0
		(25) Butterfly valves of cast iron, with rubber liners and suitable for working pres-					1/8/79	30/9
		sures up to 1380 kPa (200 p.s.i.):						
		Wrench operated:					1	
		51 mm (2 in.), 65 mm ( $2\frac{1}{2}$ in.), 76 mm (3 in.)						
		M12:						
		102  mm (4 in.), $152  mm$ (6 in.),						
		204 mm (8 in.), 254 mm (10 in.), 305 mm (12 in.)						