

TARIFF DECISION LIST No. 413—*continued*APPROVALS—*continued*

Port	Tariff Item No.	Goods	Rates of Duty		Part II Ref.	List No.	Effective	
			Normal	Pref.			From	To*
	84.61 <i>continued</i>	<p>Cocks and valves—<i>continued</i>:  EXCLUDING—<i>continued</i>:  Gear operated:  51 mm (2 in.), 76 mm (3 in.), 102 mm (4 in.), 152 mm (6 in.), 254 mm (10 in.), 305 mm (12 in.)  Pneumatically operated:  51 mm (2 in.), 65 mm (2½ in.), 76 mm (3 in.), 102 mm (4 in.)</p> <p>(26) Air control valves 2, 3, 4 way and parts thereof, for use in either pneumatic or hydropneumatic circuit application up to 25 mm (1 in.) B.S.P. port sizes however actuated, constructed or sealed, and the following accessory valves normally used in conjunction with these air control valves:  Exhaust flow control up to 13 mm (½ in.) B.S.P.  Exhaust silencers up to 13 mm (½ in.) B.S.P.  Flow control up to 13 mm (½ in.) B.S.P. port  Hold back or lock up to 6 mm (¼ in.) B.S.P.  Non return up to 13 mm (½ in.) B.S.P.  Quick exhaust up to 13 mm (½ in.) B.S.P. port  Sequence up to 6 mm (¼ in.) B.S.P. port  Shuttle or tee up to 13 mm (½ in.) B.S.P. port</p> <p>(27) Pneumatic and hydraulic quick release couplings up to 25 mm (1 in.) inlet diameter</p> <p>(28) Valves for compressed gas cylinders</p> <p>(29) Oxygen and acetylene single stage regulators</p> <p>(30) Compressed gas cylinder valves of brass or bronze, high or low pressure</p> <p>(31) Knife gate valves of the following types:  (a) Stainless steel fabricated, flanged 75 mm—1000 mm  (b) Stainless steel cast or nickel iron cast, flanged 100 mm—200 mm</p> <p>(32) Rotary valves, 6-way multi-port</p> <p>(33) Valves, globe of cast iron of the following types:  (a) Straight through valve, sizes 50 mm, 62 mm, 75 mm, 100 mm with maximum working pressure at 221 °C being 1310 kPa and at 121 °C 2067 kPa  (b) Right angle valve, sizes 50 mm, 62 mm, 75 mm, 100 mm with maximum working pressure at 221 °C being 1310 kPa, and at 121 °C 2067 kPa</p>						