í

ı

## THE NEW ZEALAND GAZETTE

## TARIFF DECISION LIST No. 457

Decisions of the Minister of Customs Under the Customs Tariff (Subject to Amendment or Cancellation by Notification in the Gazette)

Approvals

	Tariff Item No.	Goods	Rates of Duty		Part	Con-	Effective	
ort			Normal	Pref.	II Ref.	cession Code	From	To*
		PNEUMATIC TYRES, TUBES AND FLAPS				a e e e		
<b>o</b> .	40.11.001	Pneumatic tyres, tyre cases, and tubes therefor	10	Free		204037K	1/1/81	31/3/8
		EXCLUDING the following sizes or their	· · · ·					
		equivalent (irrespective of ply rating, speed						
	e .	rating, tread-type, pattern construction or				e godini.		
		constituent materials): Explanatory Notes						
		1. Sizes have been listed in order from smallest						
		to largest in their respective series.	· · · ·		-		1	
		2. Bias and radial tyres are shown together						
		under their respective rim diameters.					-	
		3. The $+$ shows where a letter indicating the						
		"speed rating" of a tyre may appear in the						
		size marking, e.g. 155+R13 incorporates						
		155SR13, 155HR13, and 155VR13. Most	-					
		common speed rating letters are L, S, H, and						
		V; but can include F, M, N, P, Q, R, T, and						
		U (the effect of the symbol $+$ is to disregard						
		speed ratings).						
		4. The letter "C" can also appear after the rim						
		diameter and should be disregarded, e.g.						
		185R14C 500–16C. 5. Group markings occur and vary according to	19 A					
		country of origin. If a size incorporated in a						
		group marking appears in the list of sizes in						
		TDL 385 the tyre or tube with group marking						
		is deemed to be included in TDL 385, e.g.					:	
		575/600/640-15 includes the sizes 575-15,						
		600–15, and 640–15.						
		6. Any mud and snow tyres in the sizes listed						
		may be entered at the concessionary rate of			1			
		duty EXCEPT where indicated by the						
		symbol*	1.5.1					
		Cars, vans, and light commercial vehicles						
		Tyres	· ·					
		10 in. rim diameter (or $255 \text{ mm}$ )						
		5.20+10 145+R10 165/70+R10	e de la de la			1. A.		
		12 in. rim diameter (or 305 mm)		4				
		4.40+12 Y78+12						
		4.40/125+12 Z78+12				a tana a	1375	
		5.20+12 125/5.35+12						
	-	5.35+12 155/6.15+12		· · · ·	4.5			
		5.50+12 140+R12					- 45	
		5.60+12 145+R12						
		150+R12						
		6.00+12 155+R12						
		6.15+12 175/70+R12						
		6.2+12 P155/80+R12						
l		6.20+12 YR78+12						
		ZR70+12						
		13 in. rim diameter (or 330 mm)		1				
		5.20+13 $205/60+R13$						
		5.50+13 215/60+R13						
		5.60+13 P205/60+R13			1			
	1	P215/60+R13	а. А.		1			
		5.90+13					1	