

TARIFF DECISION LIST No. 478—continued

APPROVALS—continued

Port	Tariff Item No.	Goods	Rates of Duty		Part II Ref.	Con-cession Code	Effective	
			Normal	Pref.			From	To*
WN	84.21.029	Wagner airless spray units, explosion proof, dia-phragm type	Free	Free	10	205307B	1/11/80	30/6/84
H.O.	84.22.009	Atlas copco pusher legs and feeds, when declared for use with rock drilling machines	Free	Free	10	204942C	1/9/80	31/3/82
H.O.	84.22.009	Vacuum lifting machinery incorporating suction cup holders		Aul 16	33	205152E	1/1/81	31/12/82
				Aul 12	33	205153C	1/1/83	31/12/84
				Aul 8	33	205154A	1/1/85	31/12/86
				Aul 4	33	205155K	1/1/87	31/12/88
				Aul Free	33	205156H	1/1/89	..
H.O.	84.25.041	S.U. flexible control cable assemblies, when declared: (1) by a manufacturer that they will be used by him, only in making lawnmowers; or (2) by an importer that they will be sold only to a manufacturer for use by him, only in making lawnmowers	Free	Free	99	205221A	1/12/80	30/6/82
H.O.	84.25.041	Vicon disc mower-crimpler/conditioner Models KM165, OM165 and OM240	Free	Free	10	205236K	1/7/80	30/6/83
H.O.	84.45.009	Kwik-way grinding machine	Free	Free	10	205114B	1/11/80	31/3/82
H.O.	84.45.009	Omega model V213 double mitre saw	Free	Free	10	205112F	1/2/81	31/3/83
WN	84.59.059	Dental grinder/trimmers	Free	Free	10	205308L	1/2/81	30/6/84
WN	84.61.021	Cocks and valves: EXCLUDING: (NOTE: This approval does not cover taps, bibcocks or fire hydrants) (6) Valves ball (e) Screwed brass or bronze sizes: 8 mm (¼ in.) 10 mm (⅜ in.) 15 mm (½ in.) 20 mm (¾ in.) 25 mm (1 in.) with reduced bore and sizes 8 mm (¼ in.) 10 mm (⅜ in.) 15 mm (½ in.) 20 mm (¾ in.) with full bore	Free		..	202740C	1/3/80	30/6/86
WN	84.61.021	PVC sliding gate valves, sizes: 15 mm, 20 mm, 25 mm, 32 mm, 40 mm, 50 mm, 80 mm and 100 mm	Free		..	205309J	1/2/81	30/6/84
CH	85.19.009	Hyster electronic controller Part No. 278691	Free	Free	15	205064B	1/1/81	30/6/82
H.O.	85.19.011	Ceramic bodies for H.R.C. fuse link	Free	Free	10	113938L	1/7/81	30/6/83
H.O.	85.19.011	H.R.C. cartridge fuse links, medium voltage up to 600 volts, for the protection of silicone diode rectifiers, viz: Brush Types GEC, types: CT/5/20 GSB CMT 150/500 CMTI 150/350 GSA MT 150/250 GSB MMT 175/500 GSB LCT 5/20 GSH LET 7/175 GSH CMMT 275/400 ET 8/75 EET 65/150 MTI 150/250 GSA MMTI 175/500 GSB LETI 7/175 GSD LMT 150/300 GSA LMMT 400/700 GSA EETI 90/150 GSB ETI 30/40 GSB AET 15	Free	Free	10	113947K	1/7/81	30/9/84